## **Ring Shank Drywall Nails** Drywall to Wood




		Flat Round Ring Shank Diamond Point				
Description	Attaches gypsum board to wood.					
Specifications	Size   Gauge: 12.5 Length: 1 1/4 in. to 2 in. Head Type: Flat Round Shank Type: Ring Finish: Uncoated Steel (Bright)	<b>Quality Assurance:</b> Grabber <sup>®</sup> fasteners are manufactured in ISO 9001 and ISO 14001 certified and approved factories. <b>LEED Reporting:</b> The post-consumer recycled steel content is 25%. <b>Compliance:</b> The fasteners comply with ASTM F1667 performance requirements.				
Applications	<ul> <li>3/8 in., 1/2 in., and 5/8 in. single-layer gypsum board to wood studs</li> </ul>	<ul> <li>1/2 in. and 5/8 in. double-layer gypsum board to wood</li> </ul>				
Installation	The head is fully seated when it's just be	elow the surface of the gypsum board.				
Features	<ul> <li>Flat round head provides a large area to hold the gypsum board securely.</li> <li>Ring shank nails have robust holding power. As the nail penetrates wood, fibers lock around the grooves in the shank, creating a durable bond.</li> </ul>	<ul> <li>Long, diamond-shaped point is designed to easily drive into wood, and it helps prevent splitting.</li> </ul>				

## **Ring Shank Drywall Nails**

Drywall to Wood





Nail Gauge	B Head Diameter	Wire Diameter
12.5	0.3438 in.	0.099 in.

**Ordering Information and Product Options** 

ltem No.	Size	Head Type	Head Diameter	Gauge	Shank Type	Quantity	Weight	Special Features
Bright								
DWAT125	1 1/4 in.	Flat Round	0.3438 in.	12.5	Ring	16,250	50 lb.	
DWAT138	1 3/8 in.	Flat Round	0.3438 in.	12.5	Ring	14,900	50 lb.	
DWAT158	1 5/8 in.	Flat Round	0.3438 in.	12.5	Ring	12,770	50 lb.	
DWAT200	2 in.	Flat Round	0.3438 in.	12.5	Ring	10,520	50 lb.	

Note: Product availability is subject to change without prior notice, and the availability of products may differ from what is printed in literature and displayed on our website. The items listed are bulk size. Most are also available in smaller package sizes such as 5 lb. and 1 lb. Contact your local Grabber Branch or Grabber Pro for more information.

**Ring Shank Drywall Nails** PS1062 USA-ENG/Rev. 02-25

**GRABBER CONSTRUCTION PRODUCTS, INC.** 5255 W 11000 N., STE 100 HIGHLAND, UT 84003

(800) 477-8876 | GrabberPro.com

SAFETY FIRST: Wear appropriate personal protective equipment. Read applicable SDS and literature before handling and installation

TECHNICAL INFORMATION: Technical information contained herein is furnished without charge or

ى⊘ ISO 9001 CERTIFIED

obligation and is given and accepted at the recipient's sole risk. Because conditions of use may vary and are beyond our control, Grabber Construction Products makes no representation about, and is not responsible or liable for, the accuracy or reliability of data associated with uses of any product described herein. Grabber Construction Products reserves the right to modify this document without prior notice. © 2025 Grabber Construction Products, Inc. | All rights reserved | Printed in U.S.A. The trademarks Grabber, and Stylized G on Grabber Fasteners, are trademarks of Grabber Construction Products, Inc.

