

Fasteners for General Wood Construction

LAG-MASTER[™]

Multi-purpose **Wood Fastener** for

General Wood to Wood Construction • Ledger Boards • Laminated Beams
Under deck Connections • Angles & Brackets • Dimensional Lumber



- ▶ **3/8" hex drive**
- ▶ **DrawTite[™] shank**
Pulls both wood members together for a secure fastening job
- ▶ **Mechanical Galvanized**
- ▶ **Type 17 self-drilling point**
No need to pre-drill

G	SIZE	PART NO.	QTY	DESCRIPTION
	14 X 2-1/2	GLM250	500	HEX HEAD FRAMING SCREW, MECHANICAL GALVANIZED
	14 X 2-7/8	GLM278	500	HEX HEAD FRAMING SCREW, MECHANICAL GALVANIZED
	14 X 3-3/8	GLM338	500	HEX HEAD FRAMING SCREW, MECHANICAL GALVANIZED
	14 X 3-5/8	GLM358	500	HEX HEAD FRAMING SCREW, MECHANICAL GALVANIZED
	14 X 3-7/8	GLM378	500	HEX HEAD FRAMING SCREW, MECHANICAL GALVANIZED
	14 X 4-7/8	GLM378	500	HEX HEAD FRAMING SCREW, MECHANICAL GALVANIZED
	14 X 5-7/8	GLM578	500	HEX HEAD FRAMING SCREW, MECHANICAL GALVANIZED

Available in 10, 50 count packs or bulk

Performance Data:

Application: Structural
Compliance with the following codes:
2012, 2009, 2006 International Building Code[®] (IBC)
2012, 2009, 2006 International Residential Code[®] (IRC)
All local code requirements must be followed and a design professional should be consulted for proper spacing requirements.

Allowable fastener strength for shear ((1,046 lbf)(37,275 psi))
Allowable fastener strength for tension ((1,492 lbf)(53,180 psi))



TIE-MASTER[™]

The best **Timber Fastener** for

General Wood to Wood Construction • Retaining Walls • Decks • Docks
Boardwalks



- ▶ **Flat head design**
- ▶ **DrawTite[™] shank**
Pulls both wood members together for a secure fastening job
- ▶ **Mechanical Galvanized**
- ▶ **Type 17 self-drilling point**
No need to pre-drill
- ▶ **Countersinking head**
Sits flush to receive next timber

G	SIZE	PART NO.	QTY	DESCRIPTION
	14 X 2-1/2	GTIE212	500	FLAT HEAD FRAMING SCREW, STAR, MEC. GALVANIZED
	14 X 4	GTIE4	500	FLAT HEAD FRAMING SCREW, STAR, MEC. GALVANIZED
	14 X 4-1/2	GTIE412	500	FLAT HEAD FRAMING SCREW, STAR, MEC. GALVANIZED
	14 X 5	GTIE5	500	FLAT HEAD FRAMING SCREW, STAR, MEC. GALVANIZED
	14 X 6	GTIE6	500	FLAT HEAD FRAMING SCREW, STAR, MEC. GALVANIZED
	14 X 8	GTIE8	500	FLAT HEAD FRAMING SCREW, STAR, MEC. GALVANIZED
	14 X 10	GTIE10	500	FLAT HEAD FRAMING SCREW, STAR, MEC. GALVANIZED
	14 X 12	GTIE12	500	FLAT HEAD FRAMING SCREW, STAR, MEC. GALVANIZED

Available in 10, 50 count packs or bulk

Performance Data:

Application: Structural
Compliance with the following codes:
2012, 2009, 2006 International Building Code[®] (IBC)
2012, 2009, 2006 International Residential Code[®] (IRC)
All local code requirements must be followed and a design professional should be consulted for proper spacing requirements.

Allowable fastener strength for shear ((1,046 lbf)(37,275 psi))
Allowable fastener strength for tension ((1,492 lbf)(53,180 psi))

