

**Data Sheet** 

| Ha           | milton Acrylic Admix Bonder<br>Formulated for Hamilton compounds<br>and textures. For increased bond to<br>questionable surfaces.<br>MADE IN THE USA  |
|--------------|---|
| What is it?  | Acrylic Admix Bonder is formulated for Hamilton products as a partial<br>or whole replacement for water when mixing. It adds adhesion and<br>water resistance to questionable surfaces when applying drywall<br>finishing products. It can be used in joint compounds, textures, and<br>setting compounds.                  |
| Application: | Surfaces must be dry, clean, firm and free from dust, dirt, oil, wax, loose<br>paint, plaster or contaminants that would hinder bond. Acrylic Admix<br>can be used by adding two cups per bag/box or as a complete<br>replacement for water depending on adhesion requirement. Do not<br>apply at temperatures below 50° F. |
| Cleanup:     | Wash tools with water before materials harden.  |
| Storage:     | Keep this product tightly sealed. Store in a dry location at room temperature. Keep the product from freezing.  |

P: (360) 225-6888 • P: (877) 443-7683 • Main Fax: (800) 871-5007 • CS Fax: (877) 5-FAX-HDP 295 North Pekin Road • Woodland, Washington 98674 • www.hamiltonnw.com