



Powdered Wall Textures

LEED Material Data Sheet

Date Prepared: February 5, 2021

Details of the supplier of the L.E.E.D. data sheet

Hamilton Drywall Products 295 N. Pekin Road Woodland, WA, 98674	Phone number: 1-800-871-4998 Fax number: 1-800-871-5007 Emergency number: Chemtrec: 1-800-424-9300	Website: www.hamiltonnw.com www.hamiltondp.com
-----------------------------------------------------------------------	----------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------

Section 1 – Quick Identifier – Common Name (on label)	Packaging	Product Code
Green Line (E-Z Spray)	50 lb (22.7 kg) bag	895900000515
Green Line II (MV Tinted)	50 lb (22.7 kg) bag	895900000546
White Line	50 lb (22.7 kg) bag	895900000522
Blue Line II (White line II)	50 lb (22.7 kg) bag	895900000539
Pure-TEX	50 lb (22.7 kg) bag	895900000553
Blue Line	50 lb (22.7 kg) bag	895900000263

Section 2 – Recycled Content (% by weight) – LEEDS ® Recycled Content Credit 4.1:	
Total Recycled Content	0%

Section 3 – Local/Regional Materials – LEEDS ® Local/Regional Materials Credit 5.1		
To determine the distance from the manufacturing facility to the job site, use the suggested Google maps (https://www.google.com/maps/) straight-line distance measurement calculator: <u>Instructions when using Google Maps on a computer web browser (recommended):</u> <ul style="list-style-type: none"> ○ Search the manufacturing facility address. ○ Right click the red pin and select "Measure distance" from the pop-up menu. ○ Search the job site address, left click on the new red pin. ○ Distance found in white box on bottom of screen (in miles and kilometers). <u>Instructions when using Google Maps app for Android and iOS:</u> <ul style="list-style-type: none"> ○ Search the manufacturing facility address. ○ Tap the address or name of the location that is shown at the bottom of the screen and scroll down to select "Measure distance." ○ Use your finger to slide the map and black targeting circle to the job site location, so the circle is over the site location (zoom-out/in as required). ○ The direct mileage (or kilometers) total is shown at the bottom of the screen. 		
<table border="0"> <tr> <td style="text-align: right;">Manufacturing Facility Address</td> <td> <ul style="list-style-type: none"> • 295 N. Pekin Road, Woodland, WA, 98674, USA • 341 West Meats Avenue, Orange, CA, 92865, USA </td> </tr> </table>	Manufacturing Facility Address	<ul style="list-style-type: none"> • 295 N. Pekin Road, Woodland, WA, 98674, USA • 341 West Meats Avenue, Orange, CA, 92865, USA
Manufacturing Facility Address	<ul style="list-style-type: none"> • 295 N. Pekin Road, Woodland, WA, 98674, USA • 341 West Meats Avenue, Orange, CA, 92865, USA 	

Section 4 – VOC Content:	
VOC content (VOC of material)	< 2 g/L
VOC content for the South Coast Air Quality Management District (SCAQMD) – Regulatory VOC (less water and exempts)	Not Applicable

Section 5 – Other
Environmental Product Declaration (EPD) – see website at www.hamiltonnw.com under Technical Data – LEED Reports section.

The information and data herein are believed to be accurate and have been compiled from sources believed to be reliable and is offered for your consideration. LEED ® applicants should use their own subjective determinations for LEED certification purposes. Hamilton Drywall Products will not be liable for claims relating to any party's use of or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete or otherwise misleading.