

#362 Channel Slot Seismic Anchor

SECTION 04 00 00 MASONRY  
Section 04 05 19.16 Masonry Anchors

**PART 1: GENERAL**

1.1 RELATED SECTIONS

A. Provide shop drawings for all product locations.

1.2 SUBMITTALS

A. Manufacturer Certificate of Compliance for materials.

B. Product Data: Manufacturer's data sheet on each type of product furnished.

**PART 2: MANUFACTURER**

2.1 MANUFACTURER

Acceptable Manufacturer:  
Heckmann Building Products  
110 Richards Ave.  
Norwalk, CT 06854-1685  
800-621-4140  
Email: [info@heckmannanchors.com](mailto:info@heckmannanchors.com)  
Website: [www.heckmannanchors.com](http://www.heckmannanchors.com)

2.2 APPLICATIONS

A. Provide anchoring systems that comply with the Building Code Requirements for Masonry Structures TMS 402-16.

B. ASTM A 36/A36M-14 Standard Specification for Carbon Structural Steel.

C. ASTM A1008/A1008M Sheet Metal Anchors and Ties (Plain Steel)

D. ASTM A153/A153M-16 Standard Specification for Zinc Coating (Hot-Dip) on Iron and Steel Hardware

E. Stainless Steel AISI [Type 304] [or] [Type 316]

F. ASTM A240/A240M-15b Standard Specification for Chromium and Chromium-Nickel Stainless Steel Plate, Sheet, and Strip for Pressure Vessels and for General Application.

G. ASTM A666-15 Standard Specification for Annealed or Cold-Worked Austenitic Stainless Steel Sheet, Strip, Plate, and Flat Bar.

H. Zinc Alloy 710 for use as a firewall anchor.

## 2.3 MATERIALS

### **NO 362 CHANNEL SLOT SEISMIC ANCHOR**

[14 gage] x [1-1/4" wide] x [length from face of channel slot]

[Seismic notch centered 1" from end]

Materials: [Hotdip Galvanized After Fabrication] [Stainless Steel] [Zinc Alloy 710 Firewall]

## **PART 3: EXECUTION**

- A. Install in backup walls with #130 Heckmann Channel Slots or #133 Heckmann Continuous Channel Slots.
- B. Install as specified in applicable masonry section(s).