

#84 WEEP-THRU MORTAR DEFLECTOR

SECTION 04 00 00 MASONRY Section 04 05 23 Masonry Accessories

PART 1: GENERAL

1.1 RELATED SECTIONS

A. Section 07 25 00 - WeatherBarriers

1.2 SUBMITTALS

A. Manufacturer Certificate of Compliance for materials.

B. Product Data: Manufacturer's data sheet on each type of product furnished.

PART 2: MANUFACTURER

2.1 MANUFACTURER

Acceptable Manufacturer:
Heckmann Building Products
110 Richards Ave.
Norwalk, CT 06854-1685
800-621-4140
Email: info@heckmannanchors.com
Website: www.heckmannanchors.com

2.2 APPLICATIONS

A. Provide systems that comply with the Building Code Requirements for Masonry Structures TMS 402-16.

2.3 MATERIALS

Open mesh to collect and prevent mortar droppings from clogging weep vents.

PART 3: EXECUTION

- A. Install as specified in applicable masonry section(s).
 - a. Extend flashing at least 6" above the top of the Weep-Thru Mortar Deflector.
 - b. Remove all mortar droppings at the bottom of the cavity before

- installing the Weep-Thru Mortar Deflector.
- c. Install a continuous row of the Weep-Thru Mortar Deflector in the cavity at the base directly on the flashing with the dovetail facing upward.

END OF SECTION