

## SECTION 04 00 00 MASONRY

### 04 05 23.19 Masonry Cavity Drainage, Weepholes, and Vents

#### **PART 1 GENERAL**

##### 1.1 RELATED SECTIONS

01 33 23 Provide shop drawings for all product locations.

##### 1.2 SUBMITTALS

- A. Manufacturer Certificate of Compliance for materials.
- B. Product Data: Manufacturer's data on each type of product furnished.

#### **PART 2 PRODUCTS**

##### 2.1 MANUFACTURER

Acceptable Manufacturer:  
Heckmann Building Products  
110 Richards Ave.  
Norwalk, CT 06854-1685  
800-621-4140  
Email: info@heckmannanchors.com  
Website: www.heckmannanchors.com

##### 2.2 APPLICATIONS

- A. Provide anchoring systems that comply with the Building Code Requirements for Masonry Structures TMS 402-16.

##### 2.3 MATERIALS

- A. **Cell Vent: No. 85**; One piece flexible extrusion made from UV-resistant polypropylene copolymer, full height and width of head joint and depth 1/8" less than depth of outer wythe, in color selected from manufacturer's standard.  
**[Regular: 3/8 inch wide x 2-1/2 inches high x 3-3/8 inches long] [Jumbo: 3/8 inch wide x 3-3/8 inches wide x 4 inches long]**

#### **PART 3 EXECUTION**

##### 3.1 INSTALLATION

- A. Install as specified in applicable masonry section(s).