

SECTION 04085

MASONRY ANCHORS AND ACCESSORIES

PART 1 GENERAL

1.1 SECTION INCLUDES

NOTE: Delete items below not required for project.

- A. Masonry veneer anchors and ties.
- B. Stone veneer anchors and ties.
- C. Masonry accessories.

1.2 RELATED SECTIONS

- A. Section 04810 - Unit Masonry Assemblies.
- B. Section 04851 - Cut Stone Veneer.
- C. Section 04852 - Stone Masonry Veneer.

1.3 REFERENCES

NOTE: Delete references from the list below that are not actually
required by the text of the edited section.
*****4

SUBMITTALS

- A. Submit under provisions of Section 01300.
- B. Product Data: Manufacturer's data on each type of product furnished.

PART 2 PRODUCTS

2.1 MANUFACTURERS

- A. Acceptable Manufacturer: Heckmann Building Products Inc., 1501 n. 31st Avenue Melrose Park, IL 60160-2911
Tel: (708)-865-2403 Fax: (708)-865-2640
Email: Heckmann@worldnet.att.net.
Website: www.heckmannbuildingprods.com.

NOTE: Delete paragraph below; coordinate with Division 1 requirements.

B. Requests for substitutions will be considered in accordance with provisions of Section 01600.

C. Substitutions: Not permitted.

2.2 APPLICATIONS

A. Provide anchoring systems that comply with ACI 530.1/ASCE 6/TMS 602.

2.3 MATERIALS

NOTE: Delete all but one style of vent or weep below, unless drawings or specifications indicate clearly where each type is to be used.

- A. Trash Mortar™ Cavity Moisture Diverter: No. 365; corrugated polystyrene, V-shaped, with weep holes; for insertion into cavity.
- B. Cavity Vent™ Weep System: No. 366; corrugated polystyrene, designed to be set in mortar joint without impairing bond or bending.
- C. Core Cavity Vent™ Weep System: No 367; corrugated polystyrene, designed to be set in mortar joint without impairing bond or bending.
- D. Weepholes: No. 330; clear plastic tube, ¼ inch (6 mm) inside diameter, 4 inches (100 mm) long.
- E. Cell Vent: No. 85; rectangular polypropylene vertical joint vent. [Regular: 3/8 inch wide x 2-1/2 inches high x 3-3/8 inches long] [Jumbo: 3/8 inch wide x 3-3/8 inches wide x 4 inches long]

PART 3 EXECUTION

3.1 INSTALLATION

- A. Install as specified in applicable masonry section(s) and in accordance with manufacturer's instructions.

END OF SECTION