

Product Certification

Henry® Air-Bloc® 17MR Vapor Permeable Air Barrier

Henry Air-Bloc 17MR is a fluid-applied vapor permeable air barrier comprised of a water-based elastomeric membrane intended for use in above grade wall assemblies.

Henry products are tested to confirm compliance with the physical properties as stated on the product data sheet.

Air-Bloc 17MR has been evaluated in accordance with the following:

- ASTM E2357 - Assembly Air Leakage
- NFPA 285 - Complies in various wall assemblies
- Meets IBC Chapter 14, Combustible water resistive barriers NFPA 285 exception #2
- Air Barrier Association of America: Evaluated air barrier material and air barrier assembly
- Health Product Declaration (HPD)
- Declaration status: LBC Red List Free

Air-Bloc 17MR is chemically compatible with the following substrates:

- Precast and cast-in place concrete, masonry, steel, aluminum, galvanized metal, exterior grade gypsum board, foil or coated-glass faced polyisocyanurate foam sheathing, OSB and plywood

Air-Bloc 17MR is suitable for installation in conjunction with the following commonly used Henry products when installed per Henry published literature. Refer to product specific technical data sheet, guide specification, technical bulletins, and details for test data, installation guidelines, and sequencing requirements.

- Air-Bloc 16MR
- Air-Bloc All Weather STPE
- Air-Bloc LF® Liquid-Applied Flashing
- Aquatac™ Primer
- Barribond HP
- Barritech VP
- Barritech NP / Barritech NP LT
- Blue Grip™
- Blueskin Adhesive
- Blueskin LVC Adhesive
- Blueskin LVC Spray Primer
- Blueskin PE200HT
- Blueskin SA / Blueskin SA LT
- Blueskin Spray Prep
- Blueskin TWF Thru-Wall Flashing
- Blueskin VP160
- Blueskin WP200
- Blueskin Zero Flash™
- CAV-GRIP™
- CCW-702
- CCW-702LV
- CCW-702WB
- CCW-705 / CCW-705 XLT
- CCW-705-TWF
- Henry 925 BES Sealant
- Hi-Tac™ Primer
- Metal Clad 705FR / Metal Clad 705FR LT
- MiraDRI 860
- Travel Tack

Air-Bloc 17MR has a VOC content of 50 g/L, max.

*Information is based on Henry test data, experience, and knowledge and is considered to be true and accurate. Refer to Henry Technical Data sheets and Safety Data Sheets prior to use. No warranty or guarantee, expressed or implied, is given other than those required by law.