

Safety Data Sheet

Material Name: Barricoat-R

Product #:304919

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

Barricoat-R

Synonyms

Modified Water Based Asphalt Emulsion

Product Use

Water based non-permeable membrane for air and vapor barrier applications

Restrictions on Use

None known

Phone Numbers:

Medical Emergency
CHEMTREC (USA): 800-424-9300

MSDS Assistance; 972-442-6545
Technical Assistance: 888-229-2199
Customer Service: 888-229-0199

Manufacturer Information

Carlisle Coatings and Waterproofing Incorporated
900 Hensley Lane
Wylie, TX 75098
www.carlisle-ccw.com

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Reproductive Toxicity - Category 1B

GHS Label Elements

Symbol(s)



Signal Word

Danger

Hazard Statement(s)

May damage fertility or the unborn child

Precautionary Statement(s)

Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves/protective clothing/eye protection/face protection

Response

IF exposed or concerned: Get medical advice/attention

Safety Data Sheet

Material Name: Barricoat-R

Product #:304919

Storage

Store locked up

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

Other Hazards

Repeated or prolonged skin contact may result in irritation or dermatitis.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent
8052-42-4	Asphalt	30-60
Mixture	Acrylic polymer mixture	1-5
Trade Secret	Fuller's earth + Silica, crystalline	3-7
14808-60-7	Quartz	0.1-1

Section 4 - FIRST AID MEASURES

Description of Necessary Measures

IF exposed or concerned: Get medical advice/attention.

Inhalation

Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.

Skin

Wash with plenty of soap and water. Remove contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

Eyes

Flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately. If eye irritation persists: Get medical advice/attention.

Ingestion

If swallowed, do not induce vomiting. Get immediate medical attention.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Most Important Symptoms/Effects

Acute

No information on significant adverse effects.

Delayed

May damage fertility or the unborn child.

Safety Data Sheet

Material Name: Barricoat-R

Product #:304919

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Use carbon dioxide, regular dry chemical, regular foam or water.

Unsuitable Extinguishing Media

None known

Special Hazards Arising from the Chemical

Slight fire hazard.

Hazardous Combustion Products

Carbon monoxide, carbon dioxide, hydrocarbons, acrid odor fumes

Advice for firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Fire Fighting Measures

Do not scatter spilled material with high-pressure water streams. Move container from fire area if it can be done without risk. Dike for later disposal. Cool containers with water. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. ALWAYS stay away from tanks engulfed in fire.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Keep unauthorized personnel away. Wear personal protective clothing and equipment. Keep out of water supplies and sewers. Use dry sand or vermiculite. Collect spilled material in appropriate container. Do not touch or walk through spilled material. Avoid inhalation of material or combustion by-products.

Environmental Precautions

Avoid release to the environment.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Obtain instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged contact with skin. Wear protective gloves/protective clothing/eye protection/face protection. Avoid contact with skin and eyes.

Conditions for Safe Storage, Including any Incompatibilities

Store locked up

Store in a cool dry place. When not in use, keep containers tightly closed. Protect from freezing.

Safety Data Sheet

Material Name: Barricoat-R

Product #:304919

Incompatible Materials

Strong acids, Strong oxidizer

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Asphalt	8052-42-4	
ACGIH:	0.5 mg/m ³ TWA as benzene soluble aerosol fume, inhalable fraction	
NIOSH:	5 mg/m ³ Ceiling fume 15 min	
Mexico:	5 mg/m ³ TWA LMPE-PPT	10 mg/m ³ STEL [LMPE-CT]
Acrylic polymer mixture	Mixture	
ACGIH:	100 mg/m ³ Ceiling aerosol only	
Europe:	20 ppm TWA; 52 mg/m ³ TWA	40 ppm STEL; 104 mg/m ³ STEL
	Possibility of significant uptake through the skin	
Mexico:	100 mg/m ³ Ceiling aerosol	
Quartz	14808-60-7	
ACGIH:	0.025 mg/m ³ TWA respirable fraction	
NIOSH:	0.05 mg/m ³ TWA respirable dust	50 mg/m ³ IDLH respirable dust
OSHA (US):	((30)/(%SiO ₂ + 2) mg/m ³ TWA) total dust; ((250)/(%SiO ₂ + 5) mppcf TWA) respirable fraction; ((10)/(%SiO ₂ + 2) mg/m ³ TWA) respirable fraction	
Mexico:	0.1 mg/m ³ TWA LMPE-PPT respirable fraction	

Biological limit value

There are no biological limit values for any of this product's components.

Engineering Controls

Provide adequate ventilation. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear chemical safety goggles. Contact lenses should not be worn.

Skin Protection

Wear appropriate chemical resistant clothing.

Safety Data Sheet

Material Name: Barricoat-R

Product #:304919

Respiratory Protection

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Glove Recommendations

Wear appropriate chemical resistant gloves.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	thick liquid	Physical State	liquid
Odor	ASPHALT	Color	brown-black
Odor Threshold	Not available	pH	10 - 11
Melting Point	Not available	Boiling Point	212 °F
Freezing point	Not available	Evaporation Rate	30 - 45 % (vol)
Boiling Point Range	Not available	Flammability (solid, gas)	Not available
Autoignition	Not available	Flash Point	Not available
Lower Explosive Limit	Not available	Decomposition	Not available
Upper Explosive Limit	Not available	Vapor Pressure	<1 mmHg
Vapor Density (air=1)	Not available	Specific Gravity (water=1)	Not available
Water Solubility	souble	Partition coefficient: n-octanol/water	Not available
Viscosity	Not available	Solubility (Other)	Not available
Density	1.031	VOC	<20 g/L (less water)

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal conditions of use.

Possibility of Hazardous Reactions

Will not polymerize.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Avoid extreme heat for extended periods of time. Avoid contact with incompatible materials.

Safety Data Sheet

Material Name: Barricoat-R

Product #:304919

Incompatible Materials

Strong acids, Strong oxidizer

Hazardous decomposition products

Carbon monoxide, carbon dioxide, hydrocarbons, acrid odor fumes

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

No information on significant adverse effects.

Skin Contact

Hot asphalt may cause thermal burns. May cause smarting of the skin with first degree burns upon short exposure.

Eye Contact

Vapors may cause slight smarting of the eyes.

Ingestion

No information on significant adverse effects.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Asphalt (8052-42-4)

Oral LD50 Rat >5000 mg/kg

Dermal LD50 Rabbit >2000 mg/kg

Acrylic polymer mixture (Mixture)

Oral LD50 Rat >5000 mg/kg

Dermal LD50 Rat >5000 mg/kg

Quartz (14808-60-7)

Oral LD50 Rat 500 mg/kg

Immediate Effects

No information on significant adverse effects.

Delayed Effects

May damage fertility or the unborn child.

Irritation/Corrosivity Data

Vapors may cause slight smarting of the eyes.

Respiratory Sensitization

No information available for the product.

Dermal Sensitization

No information available for the product.

Component Carcinogenicity

Asphalt	8052-42-4
---------	-----------

Safety Data Sheet

Material Name: Barricoat-R

Product #:304919

ACGIH:	A4 - Not Classifiable as a Human Carcinogen (fume, coal tar-free)
IARC:	Monograph 103 [2013]; Supplement 7 [1987] (extracts of steam-refined and air-refined); Monograph 35 [1985] (Group 2B (possibly carcinogenic to humans))
NTP:	Reasonably Anticipated To Be A Human Carcinogen (related to Polycyclic aromatic hydrocarbons)
DFG:	Category 2 (considered to be carcinogenic for man, aerosol and vapor)
OSHA:	Present
Acrylic polymer mixture	Mixture
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
Quartz	14808-60-7
ACGIH:	A2 - Suspected Human Carcinogen
IARC:	Monograph 100C [2012]; Monograph 68 [1997] (Group 1 (carcinogenic to humans))
NTP:	Known Human Carcinogen (respirable size)
DFG:	Category 1 (causes cancer in man, alveola fraction)
OSHA:	Present (respirable size)

Germ Cell Mutagenicity

No information available for the product.

Tumorigenic Data

No information available for the product.

Reproductive Toxicity

May damage fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure

No target organs identified.

Specific Target Organ Toxicity - Repeated Exposure

No target organs identified.

Aspiration hazard

No information available for the product.

Medical Conditions Aggravated by Exposure

No data available.

Safety Data Sheet

Material Name: Barricoat-R

Product #:304919

Additional Data

This product contains crystalline silica, which is a known carcinogen. However, this component is bound by the polymer portion of the sealant. The only way this component would be released is through incineration. Therefore, this product is not considered a carcinogen.

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity

Acrylic polymer mixture	Mixture
Fish:	LC50 96 h Oncorhynchus mykiss 41000 mg/L; LC50 96 h Oncorhynchus mykiss 14 - 18 mL/L [static]; LC50 96 h Lepomis macrochirus 27540 mg/L [static]; LC50 96 h Oncorhynchus mykiss 40761 mg/L [static]; LC50 96 h Pimephales promelas 40000 - 60000 mg/L [static]; LC50 96 h Poecilia reticulata 16000 mg/L [static]
Algae:	EC50 96 h Pseudokirchneriella subcapitata 6500 - 13000 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna 46300 mg/L IUCLID

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 14 - TRANSPORT INFORMATION

US DOT Information:

UN/NA #: Not regulated

IATA Information:

UN#: Not regulated

IMDG Information:

UN#: Not regulated

TDG Information:

UN#: Not regulated

Safety Data Sheet

Material Name: Barricoat-R

Product #:304919

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Acrylic polymer mixture	Mixture
SARA 313:	1 % de minimis concentration
CERCLA:	5000 lb final RQ; 2270 kg final RQ

SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: No Chronic Health: Yes Fire: No Pressure: No Reactivity: No

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Asphalt	8052-42-4	Yes	Yes	Yes	Yes	Yes
Acrylic polymer mixture	Mixture	Yes	Yes	Yes	Yes	Yes
Quartz	14808-60-7	No	Yes	Yes	Yes	Yes

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause cancer

Quartz	14808-60-7
Carc:	carcinogen , 10/1/1988 (airborne particles of respirable size)

Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Acrylic polymer mixture	Mixture
	1 %
Quartz	14808-60-7
	1 %

WHMIS Classification

D2A

Safety Data Sheet

Material Name: Barricoat-R

Product #:304919

Component Analysis - Inventory

Asphalt (8052-42-4)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

Acrylic polymer mixture (Mixture)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Fuller's earth + Silica, crystalline (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

Quartz (14808-60-7)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Section 16 - OTHER INFORMATION

HMIS Rating

Health: 1* Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

NFPA Ratings

Health: 1 Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes

New SDS: 7/20/2015

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic

Safety Data Sheet

Material Name: Barricoat-R

Product #:304919

Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

Other Information

Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, CCWI Company must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.