

# Product Certification

## Henry® Blueskin® PE200HT Self-Adhered Roofing Underlayment

Henry Blueskin PE200HT is a self-adhered high temperature roofing underlayment comprised of a rubberized asphalt adhesive factory-applied to a poly film with a slip-resistant coating intended for use in roofing assemblies. Henry products are tested to confirm compliance with the typical physical properties as stated on the product data sheet.

Blueskin PE200HT has been evaluated in accordance with the following:

- ASTM D1970 – Standard Specification for Self-Adhering Polymer Modified Bituminous Sheet Materials Used as Steep Roofing Underlayment for Ice Dam Protection
- ASTM E96 – Standard Test Methods for Water Vapor Transmission of Materials
- ASTM E2178 – Standard Test Method for Determining Air Leakage Rate and Calculation of Air Permeance of Building Materials

Blueskin PE200HT is chemically compatible with the following substrates:

- Precast and cast-in-place concrete, masonry, steel, aluminum, wood, and rigid PVC

Blueskin PE200HT is suitable for installation in conjunction with the following commonly used Henry products when installed per Henry published literature. Refer to product specific technical data sheet, and technical bulletins for test data and installation guidelines.

- Air-Bloc® 16MR
- Air-Bloc 17MR
- Air-Bloc LF® Liquid-Applied Flashing
- Aquatac™ Primer
- Barribond HP
- Barritech VP
- Barritech NP / Barritech NP LT
- BlueGRIP™
- Blueskin Adhesive
- Blueskin Butyl Flash
- Blueskin LVC Adhesive
- Blueskin LVC Spray Primer
- Blueskin SA / Blueskin SA LT
- Blueskin Spray Prep
- Blueskin TWF Thru-Wall Flashing
- Blueskin VP160
- Blueskin ZeroFlash™
- CAV-GRIP™
- CCW-702
- CCW-705-TWF
- Henry 925 BES Sealant
- Hi-Tac™ Adhesive
- Metal Clad 705FR / Metal Clad 705FR LT
- Travel Tack

Blueskin PE200HT is suitable for installation in conjunction with Air-Bloc All Weather STPE when installed prior to Air-Bloc All Weather STPE per Henry published literature. Install Blueskin ZeroFlash with Aquatac Primer as a transition flashing where asphaltic membranes are installed onto cured Air-Bloc All Weather STPE.

Blueskin PE200HT has a VOC content of 0 g/L, max.

\*Information is based on Henry test data, experience, and knowledge and is considered to be true and accurate. Refer to Henry Technical Data sheets and Safety Data Sheets prior to use. No warranty or guarantee, expressed or implied, is given other than those required by law.