

## Safety Data Sheet

Material Name: CCW 702 WB Primer

Product #: 315109

---

### Section 1 - PRODUCT AND COMPANY IDENTIFICATION

---

**Material Name**

CCW 702 WB Primer

**Synonyms**

Contact Adhesive

**Chemical Family**

Adhesive

**Product Use**

High-tack, water-based contact adhesive for promoting adhesion of CCW membranes in air/vapor barrier, window flashing, thru-wall flashing, foundation waterproofing, and steepslope roofing underlayment applications

**Restrictions on Use**

For industrial use only.

**Manufacturer Information**

Carlisle Coatings and Waterproofing, Inc.  
900 Hensley Lane  
Wylie, TX 75098  
www.carlisleccw.com

**Phone Numbers:**

Medical Emergency  
CHEMTREC (USA): 800-424-9300

MSDS Assistance: 972-442-6545  
Technical Assistance: 888-229-2199  
Customer Service: 888-229-0199

---

### Section 2 - HAZARDS IDENTIFICATION

---

**Classification in accordance with paragraph (d) of 29 CFR 1910.1200.**

Reproductive Toxicity - Category 1B

Specific Target Organ Toxicity - Single Exposure - Category 1 ( body, central nervous system, systemic toxicity, eyes )

Specific Target Organ Toxicity - Single Exposure - Category 3

Specific Target Organ Toxicity - Repeated Exposure - Category 1 ( eyes,central nervous system )

**GHS Label Elements**

**Symbol(s)**



**Signal Word**

Danger

**Hazard Statement(s)**

## Safety Data Sheet

**Material Name: CCW 702 WB Primer**

**Product #: 315109**

May damage fertility or the unborn child  
Causes damage to organs  
May cause respiratory irritation. May cause drowsiness or dizziness  
Causes damage to organs through prolonged or repeated exposure

### Precautionary Statement(s)

#### Prevention

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use only outdoors or in a well-ventilated area  
Wear protective gloves/protective clothing/eye protection/face protection  
Do not breathe dust/fume/gas/mist/vapours/spray  
Wash thoroughly after handling  
Do not eat, drink or smoke when using this product

#### Response

If exposed: Call a POISON CENTER or doctor/physician  
IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing  
Call a POISON CENTER or doctor if you feel unwell  
Specific treatment (see label)

#### Storage

Store in a well-ventilated place. Keep container tightly closed  
Store locked up

#### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

#### Statement of Unknown Toxicity

10.3232% of the mixture consists of ingredient(s) of unknown acute toxicity.

#### Other Hazards

No additional information available.

---

### Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

---

| CAS          | Component Name                               | Percent |
|--------------|----------------------------------------------|---------|
| Mixture      | Acrylic polymer emulsion                     | 60-100  |
| Trade Secret | De-foaming agent                             | 0.1-1   |
| Mixture      | Polymer, ethyl acrylate and methacrylic acid | 0.1-1   |
| 67-56-1      | Methanol                                     | 1-5     |
| Mixture      | 1,2-Benzisothiazolin-3-one mixture           | 0.1-1   |
| Mixture      | Polyurethane resin                           | 0.5-1.5 |

## Safety Data Sheet

Material Name: CCW 702 WB Primer

Product #: 315109

---

### Section 4 - FIRST AID MEASURES

---

#### Description of Necessary Measures

If exposed or concerned: Call a POISON CENTER or doctor/physician.

#### Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

#### Skin

Rinse skin with water/shower. If skin irritation occurs, get medical advice/attention.

#### Eyes

Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

#### Ingestion

If swallowed, get medical attention. Do NOT induce vomiting.

#### Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

#### Most Important Symptoms/Effects

##### Acute

Causes damage to central nervous system, body, eyes, systemic toxicity. May cause respiratory irritation. May cause drowsiness or dizziness.

##### Delayed

May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure: central nervous system, eyes.

#### Note to Physicians

Contains methanol.

---

### Section 5 - FIRE FIGHTING MEASURES

---

#### Extinguishing Media

##### Suitable Extinguishing Media

Use dry chemical, carbon dioxide, alcohol-resistant foam or water spray.

##### Unsuitable Extinguishing Media

None reported.

#### Special Hazards Arising from the Chemical

Slight fire hazard. Sealed containers may rupture or explode if exposed to heat.

#### Hazardous Combustion Products

Oxides of carbon, oxides of nitrogen, hydrocarbons, fumes: acrid odor

## Safety Data Sheet

Material Name: CCW 702 WB Primer

Product #: 315109

### Advice for firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

### Fire Fighting Measures

Remove product from area of fire. Stay upwind and keep out of low areas.

---

## Section 6 - ACCIDENTAL RELEASE MEASURES

---

### Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

### Methods and Materials for Containment and Cleaning Up

Avoid inhalation of material or combustion by-products. Absorb with earth, sand or other non-combustible material and transfer to container. Dike for later disposal. Dispose in accordance with all applicable regulations.

### Environmental Precautions

Avoid release to the environment.

---

## Section 7 - HANDLING AND STORAGE

---

### Precautions for Safe Handling

This product contains crystalline silica, which is a known carcinogen: Do not grind or sand. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. KEEP OUT OF REACH OF CHILDREN.

### Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed

Store locked up

Store above 0 C. Store below 45 C. Do not cut, puncture, or weld on or near this container. Keep away from incompatible materials.

### Incompatible Materials

strong acids, strong oxidizing agents

---

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### Component Exposure Limits

|              |                                                                                                                   |
|--------------|-------------------------------------------------------------------------------------------------------------------|
| Phthalo blue | Mixture                                                                                                           |
| ACGIH:       | 2 mg/m <sup>3</sup> TWA particulate matter containing no asbestos and <1% crystalline silica, respirable fraction |

## Safety Data Sheet

Material Name: CCW 702 WB Primer

Product #: 315109

|                         |                                                                                      |                            |
|-------------------------|--------------------------------------------------------------------------------------|----------------------------|
| NIOSH:                  | 2 mg/m3 TWA (containing no Asbestos and <1% Quartz) respirable dust                  |                            |
|                         | 1000 mg/m3 IDLH (containing no Asbestos and <1% Quartz)                              |                            |
| OSHA (US):              | 20 mppcf TWA (if 1% Quartz or more, use Quartz limit)                                |                            |
| Mexico:                 | 2 mg/m3 TWA LMPE-PPT respirable fraction                                             |                            |
|                         |                                                                                      |                            |
| <b>Methanol</b>         | 67-56-1                                                                              |                            |
| ACGIH:                  | 200 ppm TWA                                                                          | 250 ppm STEL               |
|                         | Skin - potential significant contribution to overall exposure by the cutaneous route |                            |
|                         | Potential for dermal absorption                                                      |                            |
|                         | 6000 ppm IDLH                                                                        |                            |
| Europe:                 | 200 ppm TWA; 260 mg/m3 TWA                                                           |                            |
|                         | Possibility of significant uptake through the skin                                   |                            |
| OSHA (US):              | 200 ppm TWA; 260 mg/m3 TWA                                                           |                            |
| Mexico:                 | 200 ppm TWA LMPE-PPT; 260 mg/m3 TWA LMPE-PPT                                         |                            |
|                         | 250 ppm STEL [LMPE-CT]; 310 mg/m3 STEL [LMPE-CT]                                     |                            |
|                         | Skin - potential for cutaneous absorption                                            |                            |
|                         |                                                                                      |                            |
| <b>Monoethanolamine</b> | 141-43-5                                                                             |                            |
| ACGIH:                  | 3 ppm TWA                                                                            | 6 ppm STEL                 |
| NIOSH:                  | 3 ppm TWA; 8 mg/m3 TWA                                                               | 6 ppm STEL; 15 mg/m3 STEL  |
|                         | 30 ppm IDLH                                                                          |                            |
| Europe:                 | 1 ppm TWA; 2.5 mg/m3 TWA                                                             | 3 ppm STEL; 7.6 mg/m3 STEL |
|                         | Possibility of significant uptake through the skin                                   |                            |
| OSHA (US):              | 3 ppm TWA; 6 mg/m3 TWA                                                               |                            |
| Mexico:                 | 3 ppm TWA LMPE-PPT; 8 mg/m3 TWA LMPE-PPT                                             |                            |
|                         | 6 ppm STEL [LMPE-CT]; 15 mg/m3 STEL [LMPE-CT]                                        |                            |

### Biological limit value

There are no biological limit values for any of this product's components.

## Safety Data Sheet

Material Name: CCW 702 WB Primer

Product #: 315109

### Engineering Controls

Provide adequate ventilation. Ensure compliance with applicable exposure limits.

### Individual Protection Measures, such as Personal Protective Equipment

#### Eye/face protection

Wear splash resistant safety goggles with a faceshield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

#### Skin Protection

Wear work clothes with long sleeves.

#### Respiratory Protection

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

#### Glove Recommendations

Wear protective gloves. Recommended material: Hycron(R), neoprene, nitrile.

---

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

---

|                              |                  |                                               |                    |
|------------------------------|------------------|-----------------------------------------------|--------------------|
| <b>Appearance</b>            | pale blue liquid | <b>Physical State</b>                         | liquid             |
| <b>Odor</b>                  | latex            | <b>Color</b>                                  | pale blue          |
| <b>Odor Threshold</b>        | Not available    | <b>pH</b>                                     | Slightly acidic    |
| <b>Melting Point</b>         | Not available    | <b>Boiling Point</b>                          | 212 °F             |
| <b>Freezing point</b>        | Not available    | <b>Evaporation Rate</b>                       | 53 - 55 % volatile |
| <b>Boiling Point Range</b>   | Not available    | <b>Flammability (solid, gas)</b>              | Not available      |
| <b>Autoignition</b>          | Not available    | <b>Flash Point</b>                            | Not available      |
| <b>Lower Explosive Limit</b> | Not available    | <b>Decomposition</b>                          | Not available      |
| <b>Upper Explosive Limit</b> | Not available    | <b>Vapor Pressure</b>                         | 17 mmHg            |
| <b>Vapor Density (air=1)</b> | <1               | <b>Specific Gravity (water=1)</b>             | Not available      |
| <b>Water Solubility</b>      | Soluble          | <b>Partition coefficient: n-octanol/water</b> | Not available      |
| <b>Viscosity</b>             | 3 - 4 Kcps       | <b>Solubility (Other)</b>                     | Not available      |
| <b>Density</b>               | 1.02 (relative)  | <b>VOC</b>                                    | 54 g/L             |

### Other Information

No additional information available.

## Safety Data Sheet

Material Name: CCW 702 WB Primer

Product #: 315109

---

### Section 10 - STABILITY AND REACTIVITY

---

#### Reactivity

No reactivity hazard is expected.

#### Chemical Stability

Stable under normal conditions of use.

#### Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

#### Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

#### Incompatible Materials

Strong acids, strong oxidizing agents

#### Hazardous decomposition products

Oxides of carbon, oxides of nitrogen, hydrocarbons, fumes: acrid odor

---

### Section 11 - TOXICOLOGICAL INFORMATION

---

#### Information on Likely Routes of Exposure

##### Inhalation

May cause respiratory irritation. May cause drowsiness or dizziness.

##### Skin Contact

May cause mild skin irritation.

##### Eye Contact

May cause mild eye irritation.

##### Ingestion

Methanol can produce blindness with onset of symptoms being delayed for 18-24 hours.

#### Acute and Chronic Toxicity

##### Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Acrylic polymer emulsion (Mixture)

Oral LD50 Rat >5000 mg/kg

Dermal LD50 Rabbit >5000 mg/kg

De-foaming agent (Trade Secret)

Oral LD50 >2000 mg/kg

Polymer, ethyl acrylate and methacrylic acid (Mixture)

Oral LD50 Rat >5000 mg/kg

Dermal LD50 Rabbit >5000 mg/kg

Methanol (67-56-1)

## Safety Data Sheet

**Material Name: CCW 702 WB Primer**

**Product #: 315109**

Oral LD50 Rat 6200 mg/kg  
Inhalation LC50 Rat 22500 ppm 8 h

1,2-Benzisothiazolin-3-one mixture (Mixture)  
Oral LD50 Rat 2342 mg/kg  
Dermal LD50 Rabbit >5000 mg/kg  
Inhalation LC50 Rat 900 mg/m<sup>3</sup> 4 hr

Monoethanolamine (141-43-5)  
Oral LD50 Rat 1515 mg/kg  
Dermal LD50 Rabbit 2504 mg/kg  
Inhalation LC50 Rat >1.3 mg/L 6 hr

Polyurethane resin (Mixture)  
Oral LD50 Rat >5000 mg/kg  
Dermal LD50 Rabbit >5000 mg/kg

### Immediate Effects

Causes damage to central nervous system, body, eyes, systemic toxicity. May cause respiratory irritation. May cause drowsiness or dizziness.

### Delayed Effects

May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure: central nervous system, eyes.

### Irritation/Corrosivity Data

May cause respiratory irritation.

### Respiratory Sensitization

No data available.

### Dermal Sensitization

No data available.

### Component Carcinogenicity

|                     |                                                                                                      |
|---------------------|------------------------------------------------------------------------------------------------------|
| <b>Phthalo blue</b> | Mixture                                                                                              |
| ACGIH:              | A4 - Not Classifiable as a Human Carcinogen (containing no asbestos fibers)                          |
| IARC:               | Monograph 93 [2010] (inhaled); Supplement 7 [1987]; Monograph 42 [1987] (Group 3 (not classifiable)) |
| DFG:                | Category 3B (could be carcinogenic for man, free of asbestos fibers)                                 |

### Germ Cell Mutagenicity

No data available.

### Reproductive Toxicity

May damage fertility or the unborn child.

### Specific Target Organ Toxicity - Single Exposure

Central nervous system, body, systemic toxicity, eyes

### Specific Target Organ Toxicity - Repeated Exposure

Central nervous system, eyes



## Safety Data Sheet

**Material Name:** CCW 702 WB Primer

**Product #:** 315109

**Aspiration hazard**

No data available.

**Medical Conditions Aggravated by Exposure**

No data available.

**Additional Data**

No additional information available.

### Section 12 - ECOLOGICAL INFORMATION

**Ecotoxicity**

Avoid release to the environment.

**Component Analysis - Aquatic Toxicity**

|                                                     |                                                                                                                                                                                                                                                                                                              |
|-----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Polymer, ethyl acrylate and methacrylic acid</b> | Mixture                                                                                                                                                                                                                                                                                                      |
| Fish:                                               | LC50 96 hr Pimephales promelas >1000 mg/L                                                                                                                                                                                                                                                                    |
| Invertebrate:                                       | EC50 48 hr Daphnia magna >1000 mg/L                                                                                                                                                                                                                                                                          |
|                                                     |                                                                                                                                                                                                                                                                                                              |
| <b>Phthalo blue</b>                                 | Mixture                                                                                                                                                                                                                                                                                                      |
| Fish:                                               | LC50 96 h Brachydanio rerio >100 g/L [semi-static]                                                                                                                                                                                                                                                           |
|                                                     |                                                                                                                                                                                                                                                                                                              |
| <b>Methanol</b>                                     | 67-56-1                                                                                                                                                                                                                                                                                                      |
| Fish:                                               | LC50 96 h Pimephales promelas 28200 mg/L [flow-through];<br>LC50 96 h Pimephales promelas >100 mg/L [static];<br>LC50 96 h Oncorhynchus mykiss 19500 - 20700 mg/L [flow-through];<br>LC50 96 h Oncorhynchus mykiss 18 - 20 mL/L [static];<br>LC50 96 h Lepomis macrochirus 13500 - 17600 mg/L [flow-through] |
|                                                     |                                                                                                                                                                                                                                                                                                              |
| <b>1,2-Benzisothiazolin-3-one mixture</b>           | Mixture                                                                                                                                                                                                                                                                                                      |
| Fish:                                               | LC50 96 hr Rainbow trout 21 mg/L [flow-through]                                                                                                                                                                                                                                                              |
| Invertebrate:                                       | EC50 48 hr Daphnia magna 26 mg/L                                                                                                                                                                                                                                                                             |
|                                                     |                                                                                                                                                                                                                                                                                                              |
| <b>Monoethanolamine</b>                             | 141-43-5                                                                                                                                                                                                                                                                                                     |
| Fish:                                               | LC50 96 h Pimephales promelas 227 mg/L [flow-through];                                                                                                                                                                                                                                                       |

## Safety Data Sheet

Material Name: CCW 702 WB Primer

Product #: 315109

|               |                                                                                                                                                                                                                                                                                                                  |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|               | LC50 96 h Brachydanio rerio 3684 mg/L [static];<br>LC50 96 h Lepomis macrochirus 300 - 1000 mg/L [static];<br>LC50 96 h Oncorhynchus mykiss 114 - 196 mg/L [static];<br>LC50 96 h Oncorhynchus mykiss >200 mg/L [flow-through];<br>LC50 96 hr Cyprinus carpio 349 mg/L;<br>LC50 96 hr Carassius auratus 170 mg/L |
| Algae:        | EC50 72 h Desmodesmus subspicatus 15 mg/L IUCLID                                                                                                                                                                                                                                                                 |
| Invertebrate: | EC50 48 h Daphnia magna 65 mg/L IUCLID                                                                                                                                                                                                                                                                           |

**Persistence and Degradability**

No information available for the product.

**Bioaccumulative Potential**

No information available for the product.

**Mobility**

No information available for the product.

**Other Toxicity**

No additional information available.

---

**Section 13 - DISPOSAL CONSIDERATIONS**

---

**Disposal Methods**

Dispose of contents/container in accordance with local/regional/national/international regulations.

---

**Section 14 - TRANSPORT INFORMATION**

---

**US DOT Information:**

UN/NA #: Not regulated

**IATA Information:**

UN#: Not regulated

**IMDG Information:**

UN#: Not regulated

**TDG Information:**

UN#: Not regulated

---

**Section 15 - REGULATORY INFORMATION**

---

**U.S. Federal Regulations**

## Safety Data Sheet

**Material Name: CCW 702 WB Primer**

**Product #: 315109**

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

|           |                                    |
|-----------|------------------------------------|
| Methanol  | 67-56-1                            |
| SARA 313: | 1 % de minimis concentration       |
| CERCLA:   | 5000 lb final RQ; 2270 kg final RQ |

### SARA Section 311/312 (40 CFR 370 Subparts B and C)

**Acute Health:** Yes **Chronic Health:** Yes **Fire:** No **Pressure:** No **Reactivity:** No

### U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

| Component        | CAS      | CA  | MA  | MN  | NJ  | PA  |
|------------------|----------|-----|-----|-----|-----|-----|
| Phthalo blue     | Mixture  | Yes | Yes | Yes | Yes | Yes |
| Methanol         | 67-56-1  | Yes | Yes | Yes | Yes | Yes |
| Monoethanolamine | 141-43-5 | Yes | Yes | Yes | Yes | Yes |

### The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects

|                |                                    |
|----------------|------------------------------------|
| Methanol       | 67-56-1                            |
| Repro/Dev. Tox | developmental toxicity , 3/16/2012 |

### Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

|                  |          |
|------------------|----------|
| Methanol         | 67-56-1  |
|                  | 1 %      |
| Monoethanolamine | 141-43-5 |
|                  | 1 %      |

### Component Analysis - Inventory

Polymer, ethyl acrylate and methacrylic acid (Mixture)

| US  | CA  | EU | AU  | PH  | JP - ENCS | JP - ISHL | KR - KECI/KECL | KR - TCCA | CN  | NZ  | MX  |
|-----|-----|----|-----|-----|-----------|-----------|----------------|-----------|-----|-----|-----|
| Yes | DSL | No | Yes | Yes | Yes       | No        | Yes            | No        | Yes | Yes | Yes |

Phthalo blue (Mixture)

## Safety Data Sheet

Material Name: CCW 702 WB Primer

Product #: 315109

| US  | CA  | EU  | AU  | PH  | JP - ENCS | JP - ISHL | KR - KECI/KECL | KR - TCCA | CN  | NZ  | MX  |
|-----|-----|-----|-----|-----|-----------|-----------|----------------|-----------|-----|-----|-----|
| Yes | DSL | EIN | Yes | Yes | Yes       | No        | Yes            | No        | Yes | Yes | Yes |

### Methanol (67-56-1)

| US  | CA  | EU  | AU  | PH  | JP - ENCS | JP - ISHL | KR - KECI/KECL | KR - TCCA | CN  | NZ  | MX  |
|-----|-----|-----|-----|-----|-----------|-----------|----------------|-----------|-----|-----|-----|
| Yes | DSL | EIN | Yes | Yes | Yes       | No        | Yes            | No        | Yes | Yes | Yes |

### 1,2-Benzisothiazolin-3-one mixture (Mixture)

| US  | CA  | EU  | AU  | PH  | JP - ENCS | JP - ISHL | KR - KECI/KECL | KR - TCCA | CN  | NZ  | MX  |
|-----|-----|-----|-----|-----|-----------|-----------|----------------|-----------|-----|-----|-----|
| Yes | DSL | EIN | Yes | Yes | Yes       | No        | Yes            | No        | Yes | Yes | Yes |

### Monoethanolamine (141-43-5)

| US  | CA  | EU  | AU  | PH  | JP - ENCS | JP - ISHL | KR - KECI/KECL | KR - TCCA | CN  | NZ  | MX  |
|-----|-----|-----|-----|-----|-----------|-----------|----------------|-----------|-----|-----|-----|
| Yes | DSL | EIN | Yes | Yes | Yes       | No        | Yes            | No        | Yes | Yes | Yes |

## Section 16 - OTHER INFORMATION

### HMIS Rating

Health: 2\* Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

### NFPA Ratings

Health: 2 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

### Summary of Changes

Revision Date: June 1, 2018

Revision Note: General Update

### Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency

## Safety Data Sheet

**Material Name: CCW 702 WB Primer**

**Product #: 315109**

for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

### Other Information

#### Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, CCWI Company must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use