

Physical Properties

Appearance Smooth gloss black	Drying Time @ 50% R.H. 68°F (20°C) 8 hrs set to touch	Solids By Weight 74% minimum
Base Refined asphalt	Flash Point 105° F (ASTM D-3278)	Specific Gravity @ 77° F (25°C) 0.93
Brookfield Viscosity 2000-4000 cPs	Gloss (60°) >80	Weight Per Gallon 7.6- 8.2 lbs (ASTM D-1475)
Consistency @ 77° F Brush, Spray	Maximum VOC 247 g/l	

Description

HE026 - HIGH GLOSS ASPHALT COATING is a cold-applied, non-fibered, liquid asphalt coating in a solvent system, which forms a high gloss dried film that is smooth and tough. The durable film bonds tightly to most clean, firm and dry surfaces. This product has good resistance to temperature change and demonstrates excellent weatherability.

BULK PRODUCT. NOT TO BE SOLD IN CALIFORNIA.

Coverage

Coverage rate will vary depending on method of application, as well as porosity and roughness of the surface. Apply at minimum temperature of 40°F.

Surface Preparation

All surfaces to be coated must be dry, swept clean, and free of oil, grease, rust, scale, loose paint and dirt.

Cleanup

Equipment may be cleaned using suitable solvents such as mineral spirits, kerosene or petroleum naphtha. Care should be used in handling these solvents. Clean hands with a waterless hand cleaner.

Caution

CAUTION! COMBUSTIBLE! Contains petroleum distillate. Keep away from heat and flame. Do not heat container or store at temperatures greater than 110°F. CLOSE AIR INTAKES until solvents dissipate. Contains volatile solvents that might contaminate potable water. Close container after each use. Dispose of container and unused contents in accordance with Local, State and Federal regulations.

DANGER! HARMFUL OR FATAL IF SWALLOWED! If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY! Use protective measures to avoid contact with eyes and skin. In case of eye contact, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. In case of accidental injection by power spray equipment, GET MEDICAL ATTENTION IMMEDIATELY!

USE ONLY WITH ADEQUATE VENTILATION!

Avoid breathing of vapor. If you experience eye watering, headaches or dizziness, leave area or increase fresh air or wear respirator (NIOSH/MSHA TC23 or equal). Repeated and prolonged occupational overexposure to solvent vapor may cause permanent brain and nervous system damage, and may cause liver or kidney damage.

KEEP OUT OF REACH OF CHILDREN.

WARNING: This product contains detectable amounts of chemicals known to the State of California to cause cancer, or birth defects or other reproductive harm.

Employers should obtain a copy of the **Material Safety Data Sheet (MSDS)** from your supplier or directly from Henry at the toll free number or website below.

Product Sizes

BULK (GALLONS) (7.7 lb)

Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.**