Henry.

SAFETY DATA SHEET

Issue Date 24-Apr-2015

Revision Date 15-May-2015

Version 1

1. IDENTIFICATION

Product identifier Product Name

QUICKDRY ASPHALT PRIMER

Other means of identificationProduct CodeHE104QUN/ID no.UN1950SynonymsNone

Recommended use of the chemical and restrictions on useRecommended UseSealant.Uses advised againstNo information available

Details of the supplier of the safety data sheet Manufacturer Address

HENRY COMPANY 999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716 Company Contact: Technical Services Telephone Number: 800-486-1278 Web Site: www.henry.com www.ca.henry.com

Emergency telephone number

Emergency Telephone

CHEMTREC: 800-424-9300 CHEMTREC: 703-527-3887 CANUTEC: 613-966-6666

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status


This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Not classified
Acute toxicity - Dermal	Not classified
Acute toxicity - Inhalation (Gases)	Not classified
Acute toxicity - Inhalation (Vapors)	Not classified
Acute toxicity - Inhalation (Dusts/Mists)	Not classified
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Respiratory sensitization	Not classified
Skin sensitization	Not classified
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Not classified
Aspiration toxicity	Not classified
Flammable aerosols	Category 1

Label elements

Emergency Overview

Danger



Precautionary Statements - Prevention

Wear protective gloves/protective clothing/eye protection/face protection Keep away from heat/sparks/open flames/hot surfaces. - No smoking Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use Wash face, hands and any exposed skin thoroughly after handling

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water If skin irritation occurs: Get medical advice/attention IF INHALED: Call a POISON CENTER or doctor if you feel unwell In case of fire: Use Water spray, fog or regular foam for extinction

Precautionary Statements - Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F Store in a well-ventilated place Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

May be harmful in contact with skin Harmful to aquatic life with long lasting effects Harmful to aquatic life IARC has classified occupational exposure to straight-run bitumen and their emissions during road paving as a carcinogen (category 2B - possibly carcinogenic to humans).

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Chemical Name	CAS No.	Weight-%	Trade Secret
Petroleum Asphalt	8052-42-4	30 - 60	*
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	10 - 30	*
Petroleum naphtha, light aromatic	64742-95-6	10 - 30	*
Propane	74-98-6	3 - 7	*

Isobutane	75-28-5	3 - 7	*
1,3,5-Trimethylbenzene	108-67-8	1 - 5	*
1,2,4 Trimethylbenzene	95-63-6	1 - 5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.		
Skin contact	Wash skin with soap and water.		
Inhalation	Remove to fresh air.		
Ingestion	Clean mouth with water and drink afterwards plenty of water.		
Most important symptoms and effects, both acute and delayed			
Symptoms	Drowsiness.		
Indication of any immediate medical attention and special treatment needed			
Note to physicians	Treat symptomatically.		

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, CO2, alcohol-resistant foam or water spray.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Flash back possible over considerable distance.

Explosion data Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

Cool containers with flooding quantities of water until well after fire is out.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Personal precautions Ensure adequate ventilation, especially in confined areas. Environmental precautions See Section 12 for additional ecological information. Methods and material for containment and cleaning up Prevent further leakage or spillage if safe to do so. Methods for cleaning up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Petroleum distillates

No information available

Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice.		
Conditions for safe storage, including any incompatibilities			
Storage Conditions	Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).		
Incompatible materials	Strong oxidizing agents.		

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum Asphalt 8052-42-4	TWA: 0.5 mg/m ³ benzene soluble aerosol fume, inhalable fraction	-	Ceiling: 5 mg/m ³ fume 15 min
Propane 74-98-6	: See Appendix F: Minimal Oxygen Content	TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
Isobutane 75-28-5	STEL: 1000 ppm	-	TWA: 800 ppm TWA: 1900 mg/m ³
1,3,5-Trimethylbenzene 108-67-8	-	-	TWA: 25 ppm TWA: 125 mg/m ³
1,2,4 Trimethylbenzene 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m ³

Appropriate engineering controls

Engineering Controls	Showers
	Eyewash stations
	Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin and body protection	Wear protective gloves and protective clothing.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Appearance Color	Aerosol Liquefied gas black	Odor Odor threshold
<u>Property</u> pH Melting point / freezing point Boiling point / boiling range Flash point Evaporation rate	<u>Values</u> No information available No information available < 0 °C < -20 °C No information available	<u>Remarks • Method</u>

Flammability (solid, gas) Flammability Limit in Air	No information available
Upper flammability limit:	9%
Lower flammability limit:	1%
Vapor pressure	No information available
Vapor density	No information available
Relative density	0.9 - 1.3
Water solubility	No information available
Solubility in other solvents	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	>100 mm2/s
Dynamic viscosity	No information available
Explosive properties	No information available
Oxidizing properties	No information available
Other Information	
Softening point	No information available
Molecular weight	No information available
VOC Content (%)	No information available

@ 40 °C

10. STABILITY AND REACTIVITY

No information available

No information available

Reactivity No data available

Density

Bulk density

Chemical stability

Stable under recommended storage conditions. Possibility of Hazardous Reactions None under normal processing. Conditions to avoid Extremes of temperature and direct sunlight. Incompatible materials Strong oxidizing agents. Hazardous Decomposition Products None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	No data available	No data available May cause irritation of respiratory tract. May cause drowsiness or dizziness.		
Inhalation	May cause irritation of re-			
Eye contact	Irritating to eyes.			
Skin contact	Irritating to skin.			
Ingestion	No data available.			
Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50	
Petroleum Asphalt 8052-42-4	> 5000 mg/kg(Rat)	> 2000 mg/kg (Rabbit)	-	

8052-42-4		2 2000 mg/kg (Rabbit)	
Solvent naphtha (petroleum), medium aliphatic 64742-88-7	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat)4 h
Petroleum naphtha, light aromatic	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h

64742-95-6			
Propane 74-98-6	-	-	= 658 mg/L (Rat)4 h
lsobutane 75-28-5	-	-	= 658 mg/L (Rat)4 h
1,3,5-Trimethylbenzene 108-67-8	= 5000 mg/kg (Rat)	-	= 24 g/m³(Rat)4 h
1,2,4 Trimethylbenzene 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m³(Rat)4 h

Information on toxicological effects

Symptoms

Vapors may cause drowsiness and dizziness.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ cell mutagenicity Carcinogenicity		on available. on available. on available.		
Chemical Name	ACGIH	IARC	NTP	OSHA
Petroleum Asphalt 8052-42-4	-	Group 2B	-	X
Reproductive toxicity STOT - single exposure STOT - repeated exposure Aspiration hazard	No informati No informati	No information available. No information available. No information available. No information available.		

Numerical measures of toxicity - Product Information

ATEmix (oral)	5,183.00
ATEmix (dermal)	3,600.00
ATEmix (inhalation-gas)	3,148,048.14
ATEmix (inhalation-dust/mist)	15.00
ATEmix (inhalation-vapor)	99,999.00

12. ECOLOGICAL INFORMATION

Ecotoxicity

^{10 %} of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Solvent naphtha (petroleum), medium aliphatic 64742-88-7	450: 96 h Pseudokirchneriella subcapitata mg/L EC50	800: 96 h Pimephales promelas mg/L LC50 static	100: 48 h Daphnia magna mg/L EC50
Petroleum naphtha, light aromatic 64742-95-6	-	9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
1,2,4 Trimethylbenzene 95-63-6	-	7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50
1,3,5-Trimethylbenzene 108-67-8	-	3.48: 96 h Pimephales promelas mg/L LC50	50: 24 h Daphnia magna mg/L EC50
Xylene 1330-20-7	-	 13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L 	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50

	LC50 static	

Persistence and degradability

Not readily biodegradable.

Bioaccumulation

Bioaccumulative potential.

Chemical Name	Partition coefficient
Petroleum Asphalt 8052-42-4	>6
Propane 74-98-6	2.3
Isobutane 75-28-5	2.88
1,2,4 Trimethylbenzene 95-63-6	3.63

Other adverse effects

No information available

Ozone

Not applicable

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

Do not reuse container.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene	-	Included in waste stream:	-	U239
1330-20-7		F039		

14. TRANSPORT INFORMATION

DOT UN/ID no. Proper shipping name Hazard Class Description	UN1950 Aerosols 2.1 May be shipped as a limited quantity or as a consumer commodity (ORM-D)
TDG UN/ID no. Proper shipping name Hazard Class Description	UN1950 Aerosols 2.1 May be shipped as a limited quantity.
<u>IATA</u> UN/ID no. Proper shipping name Hazard Class Special Provisions	UN1950 Aerosols 2.1 May be shipped as a limited quantity.
IMDG UN/ID no. Proper shipping name Hazard Class	UN1950 Aerosols 2.1

May be shipped as a limited quantity.

Revision Date 15-May-2015

15. REGULATORY INFORMATION

All components used in this product are on the TSCA Inventory and the Canadian DSL.

International Inventories

TSCA	Complies
	•
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Does not comply
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances ENCS - Japan Existing and New Chemical Substances IECSC - China Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains chemicals known to the state of California to cause birth defects or other reproductive harm

U.S. State Right-to-Know Regulations

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

HE104Q - QUICKDRY ASPHALT PRIMER

NFPA	Health hazards 2	Flammability 4	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 2	Flammability 4	Physical hazards 0	Personal protection X
Issue Date Revision Date Revision Note No information available	24-Apr-20 15-May-2			

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet