

Physical Properties

Appearance Black fluid	Flash Point >212°F	Solids By Weight 55-65% (ASTM D-1644)
Application Temperature 50°F and rising	Maximum VOC <10 g/l	Specific Gravity @ 77° F (25°C) 1.35
Brookfield Viscosity 6,000 - 15,000 cPs (ASTM D-2196)	Solids By Volume 55-65% (ASTM D-2697)	Weight Per Gallon 11.0 - 11.4 lbs. (ASTM D-2939)
Color Black		

Description

HE127 - HE127 PAVEMENT SEALER is an asphalt-based product designed to seal and protect asphalt pavement.

Usage

For use in sealing parking lots, driveways, residential streets, and other slow traffic asphaltic surfaces.

Coverage

Coverage averages about 30 gallons per 1000 square feet.

Surface Preparation

Remove and replace all damaged asphalt paving, including areas completely saturated by oil or grease. Clean and fill surface cracks 1/4" or wider to the level of adjacent areas. Use **Henry #93 DuroFlex (Hot Pour) Asphalt Crack and Joint Sealant** or **Henry #82 DuraFill (Cold Pour) Crack Filler**. Sweep, flush, or blow patched surface area free of dust, dirt and foreign matter. Scrub oily and greasy areas with strong detergent, then flush with water. The surface to be coated may be damp, but must be free of standing water prior to application. Allow sufficient time for freshly patched asphalt concrete or newly laid asphalt to cure.

Application

Apply **HE127 - HE127 PAVEMENT SEALER** in continuous parallel lines, by pouring directly from the container, a wheeled container or a mechanized spreader. Spread immediately by hand, power squeegee, or broom. Pull **HE127 - HE127 PAVEMENT SEALER** on an angle toward the operator, overlapping uniformly and evenly to eliminate gaps and ridges. The finished surface should be smooth and level. Apply an average total of 30 gallons per 1000 square feet. Use two coats. The condition of the pavement to be sealed will determine the amount of material needed. For excessively rough areas, add three pounds of 30 or 60 mesh sand to each gallon of **HE127 - HE127 PAVEMENT SEALER**. Water may be added to product for a more liquid, spreadable consistency (not to exceed 20% volume).

Precautions

Recommended ambient temperature range for application is 50°F and rising. Application should be postponed if wet or freezing weather is expected 24 hours following application. When transporting this product, be sure the container is secured and the lid is tight. Do not allow container to tumble, as this may loosen the lid and allow leakage to occur.

Cleanup

Wash tools in water. Use a paint thinner if material has dried.

Caution

CAUTION! Do not heat container or store at temperatures greater than 120°F. Close container after each use. DO NOT TAKE INTERNALLY! Use protective measures to avoid contact with eyes and skin. **If swallowed**, CALL PHYSICIAN IMMEDIATELY! **In case of eye contact**, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. **In case of accidental injection** by power spray equipment, GET MEDICAL ATTENTION IMMEDIATELY. Dispose of container and unused contents in accordance with Local, State and Federal regulations. **KEEP OUT OF REACH OF CHILDREN! DO NOT ALLOW THIS PRODUCT TO FREEZE!**

WARNING: This product contains detectable amounts of chemicals known to the State of California to cause cancer, or birth defects, or other reproductive harm.

Employers should obtain a copy of the **Material Safety Data Sheet (MSDS)** from your supplier or directly from Henry at the toll free number or website below.

Product Sizes

BULK (GALLONS) (11.2 lb)

5 GALLON (46.2 lb)

275 GALLON (2365 lb)

Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.**