

# SAFETY DATA SHEET

Issue Date 05-Dec-2015 Revision Date 05-Dec-2015 Version 1

### 1. IDENTIFICATION

**Product identifier** 

Product Name ELASTOMERIC EMULSION CRACK FILLER

Other means of identification

Product Code HE305 Synonyms None

Recommended use of the chemical and restrictions on use
Recommended Use Adhesives and/or sealants
Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

HENRY COMPANY

999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716

Web Site: www.henry.com www.ca.henry.com

Emergency telephone number

Company Phone Number 800-486-1278

Emergency Telephone CHEMTREC: 800-424-9300 CHEMTREC: 703-527-3887

CANUTEC: 613-966-6666

# 2. HAZARDS IDENTIFICATION

#### Classification

### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3

### Label elements

#### **Emergency Overview**

### Warning

#### **Hazard statements**

Causes skin irritation Causes serious eye irritation May cause respiratory irritation



Revision Date 05-Dec-2015

### Appearance viscous Physical state liquid Odor Slight

#### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

### **Precautionary Statements - Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

#### **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed Store locked up

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

Not applicable

### Other Information

May be harmful in contact with skin.

### **Unknown acute toxicity**

15.68775515% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

### **Substance**

Not applicable

### <u>Mixture</u>

Chemical Name	CAS No	Weight-%
Asphalt *	8052-42-4	30 - 60
Water *	7732-18-5	30 - 60
Polyvinyl alcohol *	9002-89-5	1 - 5

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

#### Description of first aid measures

General advice In case of accident or unwellness, seek medical advice immediately (show directions for

use or safety data sheet if possible). If symptoms persist, call a physician.

**Eye contact** Keep eye wide open while rinsing. Immediately flush with plenty of water. After initial

flushing, remove any contact lenses and continue flushing for at least 15 minutes. If

symptoms persist, call a physician.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. If symptoms persist, call a physician. Wash contaminated clothing

Revision Date 05-Dec-2015

before reuse.

**Inhalation** Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration.

Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If

symptoms persist, call a physician.

Ingestion Call a physician or poison control center immediately. Do not induce vomiting without

medical advice. Rinse mouth. Never give anything by mouth to an unconscious person.

**Self-protection of the first aider**Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin

irritation.

Indication of any immediate medical attention and special treatment needed

### 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical, CO2, sand, earth, water spray or regular foam.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

#### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas. Use personal protective

equipment as required.

**Environmental precautions** 

**Environmental precautions** See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Use personal protective equipment as required. Soak up with inert absorbent material (e.g.

sand, silica gel, acid binder, universal binder, sawdust). Take up mechanically, placing in

appropriate containers for disposal.

### 7. HANDLING AND STORAGE

### Precautions for safe handling

#### **HE305 - ELASTOMERIC EMULSION CRACK FILLER**

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Handle in accordance with good

industrial hygiene and safety practice. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Wash contaminated clothing before reuse.

### Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Keep in properly labeled

containers.

**Incompatible materials** Strong oxidizing agents. Strong acids. Strong bases.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Asphalt	TWA: 0.5 mg/m³ benzene soluble	-	Ceiling: 5 mg/m <sup>3</sup> fume 15 min
8052-42-4	aerosol fume, inhalable fraction		

NIOSH IDLH Immediately Dangerous to Life or Health

# **Appropriate engineering controls**

Engineering Controls Showers

Eyewash stations Ventilation systems.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin and body protection** Wear protective gloves and protective clothing.

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

Tag Closed Cup

provided in accordance with current local regulations.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state liquid Appearance viscous

Appearance viscous Odor Slight

ColorblackOdor thresholdNo information available

Property Values Remarks • Method

**pH** 6-10

Melting point / freezing point

No information available

Boiling point / boiling range > 100 °C / 212 °F Flash point > 100 °C / 212 °F

Evaporation rate

No information available

Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available
No information available

Relative density 1.0 - 1.2 Water solubility dispersible

#### **HE305 - ELASTOMERIC EMULSION CRACK FILLER**

@ 40 °C

Solubility in other solventsNo information availablePartition coefficientNo information availableAutoignition temperatureNo information availableDecomposition temperatureNo information available

Kinematic viscosity > 100 mm2/s

Dynamic viscosity

Explosive properties

Oxidizing properties

No information available

Not an explosive

Not applicable

Other Information

Softening point
Molecular weight
VOC Content (%)
Density
No information available

### 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### **Chemical stability**

Stable under recommended storage conditions.

#### Possibility of Hazardous Reactions

None under normal processing.

#### Conditions to avoid

elevated temperature. Incompatible materials. Keep at >0 °C.

### **Incompatible materials**

Strong oxidizing agents. Strong acids. Strong bases.

### **Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

### 11. TOXICOLOGICAL INFORMATION

## Information on likely routes of exposure

#### **Product Information**

**Inhalation** May cause irritation of respiratory tract.

**Eye contact** Severely irritating to eyes.

**Skin contact** Irritating to skin.

**Ingestion** No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Asphalt 8052-42-4	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
Water 7732-18-5	> 90 mL/kg (Rat)	-	-
Polyvinyl alcohol 9002-89-5	= 23854 mg/kg (Rat) > 20 g/kg ( Rat)	-	-

### Information on toxicological effects

Symptoms May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin

irritation.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** No information available.

#### **HE305 - ELASTOMERIC EMULSION CRACK FILLER**

Germ cell mutagenicity No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Asphalt	-	Group 2B	-	X
8052-42-4				
Polyvinyl alcohol	-	Group 3	-	-
9002-89-5				

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.

**STOT - single exposure** Target Organs. Respiratory system. Eyes. Skin.

STOT - repeated exposure
Target Organ Effects
Aspiration hazard
No information available.
Eyes, Respiratory system, Skin.
No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

 ATEmix (oral)
 7,823.00 mg/kg

 ATEmix (dermal)
 3,158.00 mg/kg

### 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

99.68347 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

### Persistence and degradability

No information available.

### **Bioaccumulation**

Chemical Name	Partition coefficient
Asphalt	6
8052-42-4	

### Other adverse effects

No information available

### 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

# 14. TRANSPORT INFORMATION

DOTNot regulatedTDGNot regulatedIATANot regulated

\_\_\_\_

IMDG Not regulated

### 15. REGULATORY INFORMATION

### **International Inventories**

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Complies
IECSC Complies
KECL Complies
PICCS Complies
AICS Complies

### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

#### **US Federal Regulations**

#### <u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

### SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

# **US State Regulations**

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name California Proposition 65	
Benzophenone - 119-61-9	Carcinogen
Quartz - 14808-60-7	Carcinogen

# **U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Asphalt 8052-42-4	X	X	X
Potassium hydroxide 1310-58-3	X	X	X
Quartz	X	X	X

14808-60-7		

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 0 Instability 0 Physical and Chemical

Properties -

HMIS Health hazards 2 Flammability 0 Physical hazards 0 Personal protection X

Issue Date05-Dec-2015Revision Date05-Dec-2015

**Revision Note** 

No information available

**Disclaimer** 

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**