



Last Rev Date: 08/05/2013

Physical Properties

Appearance Fabric	Flash Point 212°F	Maximum VOS 0 calculated
Color Black	Maximum VOC 0 calculated	

Approvals and Certifications

Manufactured to meet the requirements of ASTM D-4601

UL listed for Class A and B fire rated roof coverings.

Consult Henry Representative for specific assembly ratings and requirements - (800) 486-1278. See Henry Specification Manual for detailed Roofing, Re-roofing, and Roof Maintenance & Restoration.



Description

HE608 - SBS BASE SHEET is suitable for use as a base sheet for hot asphalt, cold process or torch applications. This high-performance base sheet may be used over various combustible and non-combustible decks as the initial ply or multiple interplies for a specified roof system.

This product is manufactured on tested fiberglass mat impregnated and coated with an SBS modified asphalt and lightly surfaced with a mineral release material. It is approved for use on all fire-rated roofs. Contains the asphalt equivalent of Type G2 base sheet and may be used where a quality base sheet is specified.

Coverage

Approximately 300 sq. ft.

Application

Application details as specified for each particular roof system or project are to be followed, as they may vary. Prior to application, cut the rolls into lengths suitable for installation and lay flat to eliminate curl. Unless otherwise specified, the base ply is laid with 2" side laps and 4" end laps and nailed, spot-adhered or fully adhered with cold application cement or hot asphalt. Subsequently, plies are completely adhered, cold or hot method.

Cleanup

Asphalt can be removed by use of mineral spirits, paint remover or kerosene. Use caution when handling solvents.

Caution

WARNING: This product contains detectable amounts of chemicals known to the State of California to cause cancer, or birth defects or other reproductive harm.

Employers should obtain a copy of the **Material Safety Data Sheet (MSDS)** from your supplier or directly from Henry at the toll free number or website below.

Product Sizes

39 3/8IN X 99FT ROLL (92 lb)

Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.**