

Typical Physical Properties

-Apparent Opening Size (AOS) -Grab Tensile -Permittivity -CBR Puncture -Grab Elongation	80 US Sieve (ASTM D4751) 205 lbs. (ASTM D4632) 1.35 sec ⁻¹ (ASTM D4491) 535 lbs. (ASTM D6241) 50% (ASTM D4632)	-Trapezoid Tear -UV Resistance -Water Flow Rate -Weight (Typical)	85 lbs. (ASTM D4533) 70% @ 500 hrs. (ASTM D4355) 90 gpm/ft² (ASTM D4491) 8.0 oz/yd² (ASTM D5261)
---	---	--	---

Packaging

4 ft. x 300 ft. roll

Description

HE974 Protection Fabric – GR08 is a non-woven geotextile fabric made up of polypropylene fibers. It is non-biodegradable and resistant to most soil chemicals, acids and alkali with a pH range of 3 to 12.

Used as a protection course and/or separation sheet in a Henry CM100 waterproofing system.

Features

- Non-biodegradable
- Resistant to most soil chemicals, acids and alkali
- Good tear resistance
- High permeability separation sheet

Precautions

If **HE974 Protection Fabric** – **GR08** is loose laid over **Henry CM100** or insulation, temporary ballasting is recommended prior to the installation of subsequent permanent covering materials.

Limited Warranty

Many factors beyond our control affect the results obtained from this product - such as weather, workmanship, equipment utilized, and prior condition of the substrate. We, the manufacturer, warrant only that we will replace, at no charge, any product proved to have a material defect in original manufacturing within 12 months of purchase, provided the product has been applied in accordance with our written directions for uses we recommend as suitable for this product. Proof of purchase must be provided. DISCLAIMER OF CONDITIONS/WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER CONDITIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED CONDITION OR WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. NO ONE, INCLUDING THE MANUFACTURER, SHALL HAVE ANY LIABILITY OF ANY KIND, INCLUDING FOR NEGLIGENCE OR FOR DIRECT, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, RESULTING FROM ANY MISUSE, DEFECTS, ANY DELAYS CAUSED BY REPLACEMENT, OR OTHERWISE BEYOND PRODUCT REPLACEMENT. IF PURCHASER DOES NOT ACCEPT THESE TERMS, PURCHASER MAY RETURN ALL UNOPENED CONTAINERS OR PACKAGES OF PRODUCT PURCHASED FOR A FULL REFUND WITHIN 30-DAYS OF PURCHASE. RETENTION OF PRODUCT BEYOND 30-DAYS, OR USE OF PRODUCT SHALL CONSTITUTE ACCEPTANCE OF THESE TERMS, CONDITIONS, AND DISCLAIMERS. THIS LIMITED WARRANTY AND LIABILITY DISCLAIMER PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY, FROM ANYONE, FOR ANYTHING RELATING TO THE PRODUCT. To the extent that any part of this LIMITED PRODUCT WARRANTY AND LIABILITY DISCLAIMER is determined unenforceable under the law of the place of purchase of the product, that part is severed and the remainder of these terms remain in full force and effect. To the extent permitted by law, the duration of any implied conditions or warranties is limited to the duration of Henry's express warranty.

STATEMENT OF RESPONSIBILITY

The technical and application information herein is based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use. Henry Company data sheets are updated on a regular basis; it is the user's responsibility to obtain and to confirm the most recent version. Information contained in this data sheet may change without notice.