Henry.

SAFETY DATA SHEET

Issue Date 11-Nov-2015

Revision Date 11-Nov-2015

Version 1

1. IDENTIFICATION

Product identifier	
Product Name	ASPHA

ASPHALT PRIMER

Other means of identificationProduct CodeHE910SynonymsNone

Recommended use of the chemical and restrictions on useRecommended UseCoatings SealantUses advised againstNo information available

Details of the supplier of the safety data sheet Manufacturer Address HENRY COMPANY 999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716 Web Site: www.henry.com www.ca.henry.com

Emergency telephone number Company Phone Number Emergency Telephone

800-486-1278 CHEMTREC: 800-424-9300 CHEMTREC: 703-527-3887 CANUTEC: 613-966-6666

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 3

Label elements

Emergency Overview

Warning

Hazard statements Causes skin irritation Causes serious eye irritation May cause respiratory irritation. May cause drowsiness or dizziness Flammable liquid and vapor



Physical state liquid

Odor Solvent

Precautionary Statements - Prevention

Appearance viscous

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ ventilating / lighting/ mixing / equipment Use only non-sparking tools Take precautionary measures against static discharge

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention If skin irritation occurs: Get medical advice/attention IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower Wash contaminated clothing before reuse IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed Store locked up Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

May be harmful in contact with skin. Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

Unknown acute toxicity

24.67952% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable

<u>Mixture</u>

Chemical Name	CAS No	Weight-%
Asphalt *	8052-42-4	40 - 70
Solvent naphtha, petroleum, medium aliphatic *	64742-88-7	15 - 40

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	Immediate medical attention is required. In case of accident or unwellness, seek medical		
	advice immediately (show directions for use or safety data sheet if possible).		
Eye contact	Keep eye wide open while rinsing. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If symptoms persist, call a physician.		
Skin contact	Wash off immediately with plenty of water.		
Inhalation	Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If symptoms persist, call a physician.		
Ingestion	Call a physician or poison control center immediately. Do not induce vomiting without medical advice. Rinse mouth. Never give anything by mouth to an unconscious person.		
Self-protection of the first aider	Remove all sources of ignition.		
Most important symptoms and effe	ects, both acute and delayed		
Symptoms	May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin irritation. Drowsiness. Dizziness.		
Indication of any immediate medical attention and special treatment needed			
Note to physicians	Treat symptomatically.		
5. FIRE-FIGHTING MEASURES			

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical, CO2, sand, earth, water spray or regular foam.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical Flammable.

Explosion data Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Use personal protective equipment as required.	
Environmental precautions		
Environmental precautions	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do	

	not flush into surface water or sanitary sewer system.	
Methods and material for containment and cleaning up		
Methods for containment	Prevent further leakage or spillage if safe to do so.	
Methods for cleaning up	Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers.	
	7. HANDLING AND STORAGE	
Precautions for safe handling		
Advice on safe handling	Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.	
Conditions for safe storage, including any incompatibilities		
Storage Conditions	Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).	
Incompatible materials	Strong oxidizing agents. Strong acids. Strong bases.	

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

	-		
Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Asphalt	TWA: 0.5 mg/m ³ benzene soluble	-	Ceiling: 5 mg/m ³ fume 15 min
8052-42-4	aerosol fume, inhalable fraction		
Solvent naphtha, petroleum,	-	TWA: 500 ppm	-
medium aliphatic		TWA: 2900 mg/m ³	
64742-88-7			

NIOSH IDLH Immediately Dangerous to Life or Health

Appropriate engineering controls

Engineering Controls	Showers	
	Eyewash stations	
	Ventilation systems.	

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin and body protection	Wear protective gloves and protective clothing.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General Hygiene Considerations	When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Appearance Color	liquid viscous black	Odor Odor threshold	Solvent No information available
<u>Property</u> pH Melting point / freezing point Boiling point / boiling range Flash point Evaporation rate Flammability (solid, gas)	Values_ No information available No information available > 150 °C / 302 °F 42 °C / 108 °F No information available No information available	Remarks • Method	Cup (PMCC)
Flammability Limit in Air Upper flammability limit: Lower flammability limit: Vapor pressure Vapor density Relative density Water solubility Solubility in other solvents Partition coefficient Autoignition temperature Decomposition temperature Kinematic viscosity Dynamic viscosity Explosive properties Oxidizing properties	6 1 No information available 3.6 1 - 1.1 Insoluble in water No information available >250 °C / 482 °F No information available > 100 mm2/s No information available Not an explosive Not applicable	@ 40 °C	
Other Information Softening point Molecular weight VOC Content (%) Density Bulk density	No information available No information available No information available No information available No information available		

10. STABILITY AND REACTIVITY

Reactivity No data available

<u>Chemical stability</u> Stable under recommended storage conditions. <u>Possibility of Hazardous Reactions</u> None under normal processing. <u>Conditions to avoid</u> Heat, flames and sparks. <u>Incompatible materials</u> Strong oxidizing agents. Strong acids. Strong bases. <u>Hazardous Decomposition Products</u> Thermal decomposition can lead to release of irritating and toxic gases and vapors.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact Irritating to eyes.

Skin contact	Irritating to skin.
--------------	---------------------

Ingestion No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Asphalt	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
8052-42-4			
Solvent naphtha, petroleum,	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat)4 h
medium aliphatic			
64742-88-7			

Information on toxicological effects

Symptoms

May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin irritation. Vapors may cause drowsiness and dizziness.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Germ cell mutagenicity	No information available.				
Carcinogenicity	The table be	low indicates whether each	agency has listed any ing	redient as a carcinogen	
Chemical Name	ACGIH	IARC	NTP	OSHA	
Asphalt 8052-42-4	-	Group 2B	-	х	
IARC (International Age	ency for Research on Cance	er)			
Group 1 - Carcinogenic te	o Humans				
Group 2B - Possibly Card					
Not classifiable as a hum	5				
NTP (National Toxicolo					
Known - Known Carcinog	•				
	Reasonably Anticipated to b	3	flabor		
X - Present	liety and Health Administra	ation of the US Department of	Labor)		
Reproductive toxicity	No information available.				
STOT - single exposure	Target Organs. Respiratory system. Eyes. Skin. Central nervous system.				
STOT - repeated exposure	0 0				
Chronic toxicity	•	•			
,	May cause adverse effects on the bone marrow and blood-forming system.				
Target Organ Effects	 Eyes, Respiratory system, Skin, blood, Central nervous system. No information available. 				
Aspiration hazard	ino informatio	on available.			
Numerical measures of t	oxicity - Product Inform	nation			
<u></u>		· · · · · · · · · ·			
The following values are	calculated based on ch	apter 3.1 of the GHS docu	iment .		
ATEmix (oral)	5,252.00 mg	g/kg			
	2 E72 00 m	- //			

ATEmix (dermal)2,573.00 mg/kgATEmix (inhalation-dust/mist)67.40 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects

65.68642 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

Chemical Name	Partition coefficient	
Asphalt	6	

8052-42-4

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS			
Waste treatment methods Disposal of wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.		
Contaminated packaging	Do not reuse container.		
US EPA Waste Number	D001		

42 DISDOGAL CONSIDERATIONS

14. TRANSPORT INFORMATION

DOT	Not regulated (If shipped in NON BULK packaging by ground transport)
TDG	Not regulated (If shipped in NON BULK packaging by ground transport)
IATA UN/ID no Proper shipping name Hazard Class Packing Group ERG Code Special Provisions Description	UN1999 Tars, liquid 3 III 3L A3 UN1999, Tars, liquid, 3, III
IMDG UN/ID no Proper shipping name Hazard Class Packing Group EmS-No Special Provisions Description	Non-regulated per 2.3.2.5 UN1999 Tars, liquid 3 III F-E, S-E 955 UN1999, Tars, liquid, 3, III, (42°C c.c.)

15. REGULATORY INFORMATION

International Inventories	
TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances ENCS - Japan Existing and New Chemical Substances IECSC - China Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories	
Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

<u>CERCLA</u>

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Asphalt 8052-42-4	Х	X	Х
Solvent naphtha, petroleum, medium aliphatic 64742-88-7	Х	-	-
Benzene, 1,2,4-trimethyl- 95-63-6	Х	X	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 2	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 2	Flammability 2	Physical hazards 0	Personal protection X
Issue Date Revision Date Revision Note No information available	11-Nov-2 11-Nov-2	• • •		

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet