



A step 1 component of the Henry® 1-2-3 Moisture Control System™

**Henry**  
A CARLISLE COMPANY



# Henry® Jumbo Tex® Weather-Resistive Barrier

## OUTSTANDING, COST-EFFECTIVE PROTECTION

Designed to withstand the rigors of the jobsite and the elements, **Henry Two-Ply Jumbo Tex** sets the industry standard for effectiveness and durability as a weather-resistive barrier. It offers ideal water and moisture protection behind all major exterior wall claddings.

**Two-Ply Jumbo Tex** is specifically engineered for production and custom residential construction applications requiring a tough water intrusion and moisture barrier behind stucco, fiber cement siding, brick, vinyl or wood siding. It delivers over ten times the water resistance of regular Grade “D” building paper. When two layers of Grade “D” building paper are required, Two-Ply Jumbo Tex can be applied in one pass saving costly labor dollars.

**Two-Ply Jumbo Tex** is a premier grade weather-resistive barrier and is backed by an industry-leading 15-year warranty that covers defective product and provides materials PLUS labor for warranted repairs when installed as part of the Henry® 1-2-3 Moisture Control System™.

## FEATURES AND BENEFITS:

- ✓ Excellent protection against water intrusion and moisture
- ✓ Ideal balance between water resistance and permeability
- ✓ Saves labor cost
- ✓ Rugged and durable — withstands jobsite rigors
- ✓ For stucco, fiber cement siding, brick, vinyl and wood siding



**Building Confidence®**

# PERFORMANCE STANDARDS YOU CAN TRUST

**Two-Ply Jumbo Tex®** is a premier grade weather-resistive barrier chosen by builders and architects to protect millions of homes and commercial buildings. It is extremely cost effective — a single pass provides two layers of protection. Other weather-resistive barriers that cannot surpass its proven performance can cost up to three times more.

Physical/performance property	Typical value	Test method
Water vapor transmission	70 grams 10 perms (MVT)	ASTM E96 (A)
Water resistance	110 minutes	ASTM D779
Tensile strength	MD - 110 lb./inch CD - 46 lb./inch	ASTM D828

\*Two-Ply Jumbo Tex is tested in accordance with ASTM International procedures. The values shown in Table 1 are typical values obtained in these tests.

## Product characteristics

Composition	Two-Ply Jumbo Tex is an Asphalt-Saturated Kraft Grade "D" breather type sheathing paper.
Roll size	40" x 48.6 lineal ft. (covers 162 sq. ft.)
Weight	7.2 lbs. per 100 sq. ft.

## Product approvals, certifications and specifications

Exceeds Federal Specification UU-B-790a, Type 1, Grade "D", Style 2
Complies with the International Code Council Evaluation Services Acceptance Criteria for Water Resistive Barriers (AC 38)
Complies as an alternative to the water-resistive barrier specified in Section 1404.2 of the 2012 and 2015 International Building Code® and Section 1403.2 of the 2018 International Building Code®
Complies as an alternative to the weather-resistant barriers specified in Section R703.2 of the International Residential Code®
Complies as a water-resistant barrier specified in Section R703.6.3 of the 2012 International Residential Code® and Section R703.7.3 of the 2015 and 2018 International Residential Code®
Complies as a water-resistive barrier specified in Section 2510.6 of the 2012 International Building Code®
Meets the 2015 and 2018 International Building Code® requirements for an intervening layer when installed over an ASTM E2556, Type II in accordance with the Exception in Section 2510.6
ICC Evaluation Service Report 1027
ASTM D779 – Standard Test Method for Water Resistance of Paper, Paperboard and Other Sheet Materials by the Dry Indicator Test Method
ASTM D828 – Tensile Properties of Paper and Paperboard Using Constant-Rate-of-Elongation Apparatus



Featuring a range of compatible weather barriers, flashings and sealants, the Henry® 1-2-3 Moisture Control System™ makes it easier than ever to build with confidence.

**Limitations:** Product should be covered as soon as possible. Inspect product to ensure it is free of any protrusions or damage which may detract from the weather-resistive barrier integrity. Holes, tears or punctures should be sealed with Moistop® Sealant or Henry Sheathing Tape. This product is not recommended for horizontal, below grade or roofing applications.

**Installation:** Two-Ply Jumbo Tex should be installed in accordance with the local applicable building code. The International Residential Code Section R703.2 states that weather-resistive barriers should be applied horizontally, with the upper layers overlapping the lower layer by a minimum of 2" (3" is recommended), and all vertical joints should be lapped a minimum of 6". Do not tape horizontal or vertical seams.

**Availability:** Henry products are distributed nationwide. For product information and pricing, please call a Henry distributor near you. If you need assistance locating a participating distributor, please call our Customer Service Department at 800.773.4777.

**Henry Product Warranty Information:** This product may be eligible for the 15-year Henry 1-2-3 Moisture Control System Warranty when used in conjunction with other products. See [henry.com/warranty](http://henry.com/warranty) for details.

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product – such as weather, workmanship, equipment utilized, and prior condition of the substrate – are all beyond our control. We will replace at no charge any product proved to have a material defect within 12-months of purchase, provided it has been applied in accordance with our written directions for uses we recommend as suitable for this product. Proof of purchase must be provided.

DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. NO ONE, INCLUDING THE MANUFACTURER, SHALL HAVE ANY LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR NEGLIGENCE OR FOR DIRECT, CONSEQUENTIAL, EXEMPLARY OR INCIDENTAL DAMAGES, RESULTING FROM ANY MISUSE, DEFECTS OR DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. IF PURCHASER DOES NOT ACCEPT THESE TERMS, PURCHASER MAY RETURN WITHIN 30-DAYS OF PURCHASE ALL UNOPENED CONTAINERS OR PACKAGES OF PRODUCT PURCHASED FOR A FULL REFUND. RETENTION OF PRODUCT BEYOND 30-DAYS, OR USE OF PRODUCT SHALL CONSTITUTE ACCEPTANCE OF THESE TERMS, CONDITIONS, AND DISCLAIMERS. THIS LIMITED WARRANTY AND LIABILITY DISCLAIMER PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANYTHING RELATING TO THE PRODUCT.

To the extent that any part of this LIMITED PRODUCT WARRANTY AND LIABILITY DISCLAIMER is determined unenforceable under the law of the place of purchase of the product, that part is severed and the remainder of these terms remain in full force and effect. To the extent permitted by law, the duration of any implied warranties is limited to the duration of Henry's express warranty.

This warranty language supersedes any language found elsewhere, including product labels, sell sheets and/or technical documents.