



TECHNICAL DATA SHEET  
**MiraPLY™ Detail Tape**  
Self-adhering Tape

Property	Description
Color	White with pressure sensitive adhesive
Roll Size	6 in. X 50 ft. (150 mm X 15 m) 8/CTN
Storage Temperature	40°F to 110°F (4°C to 43°C)
Minimum Application Temperature	< 25°F (-4°C) requires special tools and techniques
Shelf Life	24 Months

### Description

**Henry MiraPLY™ Detail Tape** is a reinforced double-sided self-adhering tape for use with **MiraPLY** and **MiraWELD™** Pre-Applied Waterproofing Systems. **MiraPLY Detail Tape** offers an aggressive bond and remains flexible during application, ensuring immediate adhesion on contact and long-term bonding.

### Usage

Designed for commercial construction applications, **MiraPLY Detail Tape** is used in detailing the **MiraPLY** and **MiraWELD** Pre-Applied Waterproofing systems at corners, seam edges, penetrations, **Henry Tie-Back Covers**, repairs, etc. The white side of the **MiraPLY Detail Tape** should be applied facing the concrete pour.

### Application

**Substrate Preparation:** Clean substrate to receive **MiraPLY Detail Tape** and remove any dirt, dust, contaminants, or moisture. Clean the surface of penetrations or protrusions with a stiff nylon brush to remove dirt, dust, rust and loose particles. **Sure-Seal Weathered Membrane Cleaner** may be used for hard to clean areas.

**Installation:** Unroll the tape, remove the release liner, and adhere the exposed pressure sensitive adhesive to the membrane, penetration, or detail condition. The white side of the tape should face toward the concrete to be cast onto the tape. Ensure minimum 3-inch overlaps are achieved. The use of rollers is required to maximize adhesion.

Refer to **MiraPLY** and **MiraWELD** Pre-Applied Waterproofing System detail drawings for additional information

**Precautions:** Do not apply this product where the temperature will exceed 200°F. Do not exceed 60 days of UV exposure without prior written consent from Henry Technical Services. Keep out of the reach of children. Review SDS for safety information prior to use.

For more information, visit [www.henry.com](http://www.henry.com) or for technical assistance call us at 800-486-1278. For more information on Henry's® product warranty and liability disclaimer please visit [www.henry.com/warranty](http://www.henry.com/warranty). Refer to the Safety Data Sheet prior to using this product. The Safety Data Sheet is available at [www.henry.com](http://www.henry.com) or by emailing Henry® Product Support at [productsupport@henry.com](mailto:productsupport@henry.com) or by calling 800-486-1278.

Henry is a registered trademark of Henry Company.

The technical and application information herein is based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use. Henry® Company data sheets are updated on a regular basis; it is the user's responsibility to obtain and to confirm the most recent version. Information contained in this data sheet may