

Product Certification

Henry® MiraSEAL™ Cold Fluid-Applied Waterproofing

Henry MiraSEAL is a fast curing, elastomeric cold fluid waterproofing/roofing system intended for use on decks and foundation walls. Henry products are tested to confirm compliance with the physical properties as stated on the product data sheet.

MiraSEAL has been evaluated in accordance with the following:

- ASTM C836 – Standard Specification for High Solids Content, Cold Liquid-Applied Elastomeric Waterproofing Membrane for Use with Separate Wearing Course

MiraSEAL is chemically compatible with the following substrates:

- Precast and cast-in place concrete, masonry, steel, aluminum, wood, and rigid PVC.

MiraSEAL is chemically compatible with the following commonly used Henry products when installed per Henry published literature. Refer to product specific technical data sheet, guide specification, technical bulletins, and details for test data, installation guidelines, and sequencing requirements.

- | | |
|---------------------------------|--------------------------------|
| • Barribond HP | • Henry Polyester Fabric |
| • Henry 300HV Protection Fabric | • Henry Protection Board-HS |
| • Henry 925 BES Sealant | • Henry Pumadeq System |
| • Henry 990-31 Protection Board | • Henry Termination Bar |
| • Henry EJ-500 Expansion Joint | • MiraDRAIN Drainage Composite |
| • Henry Filter Fabric | • ModifiedPLUS G100s/s |
| • Henry LiquiSEAL 703 | |

MiraSEAL does not contain lead, PBDE or PCBs, and has a VOC content of <40 g/L, max.

*Information is based on Henry test data, experience, and knowledge and is considered to be true and accurate. Refer to Henry Technical Data sheets and Safety Data Sheets prior to use.
No warranty or guarantee, expressed or implied, is given other than those required by law.