

Neoflash Adhesive

Physical Properties

-Color	Pale amber	-Service Temperature	-22°F to 122°F (glue line)
-Solids by Volume	20% (approx.)	-Application Temperature	Min. 40°F preferred
-Weight per gallon	8 lbs. (approx.)	-Flammability	
-Coverage	Approx. 200 ft ² /gal per coat	Wet	Flammable
-Drying Time	@ 50 % R.H. 68°F	Dry	Flame spread 1.0 (ASTM E162-67)
Initial Bond	Dry Substrate		
Set Through	Up to 30 minutes		
-Maximum V.O.C.	One hour		
	350 grams/liter		

Description

A quick setting, pressure sensitive, contact adhesive of thin brush consistency with good tack retention.

Uses

Used for bonding uncured neoprene flashing to masonry, concrete and itself (lap).

Packaging

Neoflash Adhesive is packaged in 5 gallon pails.

Application

Apply by brush an even coating of Henry Neoflash Adhesive to substrate and back of uncured neoprene flashing sheet. Allow sufficient open time to develop full tack. Apply sheet to substrate smoothing out wrinkles or gaps.

Clean Up

Use mineral spirits.

Caution

DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE. Contains hexane, acetone, and methanol. Vapors may ignite explosively. Keep away from heat, sparks, and flame. Vapors may cause flash fire. Do not smoke. Extinguish all flames and pilot lights; turn off all stoves, heaters, electric motors, and other sources of ignition during use and until all vapors are gone. Do not heat container or store at temperatures greater than 120°F. For exterior use only; **CLOSE AIR INTAKES** until solvents dissipate. Contains volatile solvents that might contaminate potable water. Close container after each use. **DANGER! HARMFUL OR FATAL IF SWALLOWED! If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!** May be harmful if absorbed through skin. Use protective measures to avoid contact with eyes and skin. In case of eye contact, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. **GET MEDICAL ATTENTION! USE ONLY WITH ADEQUATE VENTILATION!**

Avoid breathing of vapor. If you experience eye watering, headaches or dizziness, leave area or increase fresh air or wear respirator (NIOSH/MSHA TC 23C or equal). Repeated and prolonged occupational exposure to solvents can result in permanent brain and nervous system damage. **KEEP OUT OF REACH OF CHILDREN.**

Limited Warranty

We, the manufacturer, warranty only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES:** The Limited Warranty is IN LIEU OF any other warranties express or implied including but not limited to any implied warranty of MERCHANTABILITY or fitness for a particular purpose, and we, the manufacturer, shall have no further liability of any kind including liability for consequential or incidental damages resulting from any defects or any delays caused by replacement or otherwise.

<>