

HE850AA - NEOPRENE FLASHING

Last Rev Date: 12/11/2014

Physical Properties		
Brittleness Point: -40° F	Ozone Resist.(168 hrs/100 PPHM 104ºF/20% Ext)	Thickness (mils, dry)
(ASTM D2137) Does not break	No cracks at 7X magnification	60 mils (approx.)
Color	Tear Resistance	Water Absorption
Black	(ASTM D624 Die C) 125 lbs/in. min.	(ASTM D471) 8.5%
Elongation (Initial)	Tensile Strength, Membrane	
(ASTM D412) 300%	(ASTM D412 Die C) 1800 psi min.	

Description

HE850AA - NEOPRENE FLASHING is used with **790-11 Hot Rubberized Asphalt Membrane** at expansion joints and exposed flashing details.

Features:

- Excellent elongation and flexibility
- · Designed for use as exposed flashing
- Excellent compatibility with either 790-11 Hot Rubberized Asphalt Membrane or Blueskin Adhesive LVC

Limitations: Non resistant to oils and solvents.

Application

May be applied either with 790-11 Hot Rubberized Asphalt Membrane or Blueskin Adhesive LVC.

Product Sizes		
6IN X 100FT ROLL (25 lb)	12IN X 100FT ROLL (40 lb)	18IN X 100FT ROLL (50 lb)
24IN X 100FT ROLL (65 lb)	36IN X 100FT ROLL (132 lb)	
Limited Warranty		

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.