

ACRYPRIME – RECOAT

TECHNICAL INFORMATION

DESCRIPTION

ACRYPRIME-RECOAT is a high property acrylic primer based on advanced acrylic technology. It has excellent adhesion over previously coated polyurethane roof systems.



TYPICAL PHYSICAL PROPERTIES

Color	Lt. Gray
Weight per Gallon	11 ± 0.2 lbs.
Solvent	Water
% Solids (by weight)	45 - 50%
Application Rate	0.3 to 0.5 gal./100 sq ft.
Shelf Life	6 Months
Elongation	1000 %
Tensile Strength	500 psi
Permeance @ 20 mils (ASTM D6083)	9 perms

THE INFORMATION HEREIN IS TO ASSIST CUSTOMERS IN DETERMINING WHETHER OUR PRODUCTS ARE SUITABLE FOR THEIR APPLICATIONS. WE REQUEST THAT CUSTOMERS INSPECT AND TEST OUR PRODUCTS BEFORE USE AND SATISFY THEMSELVES AS TO CONTENTS AND SUITABILITY. OUR PRODUCTS ARE INTENDED FOR SALE TO INDUSTRIAL AND COMMERCIAL CUSTOMERS. WE WARRANT THAT OUR PRODUCTS WILL MEET OUR WRITTEN SPECIFICATIONS. NOTHING HEREIN SHALL CONSTITUTE ANY OTHER WARRANTY EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS, NOR IS PROTECTION FROM ANY LAW OR PATENT TO BE INFERRED. THE EXCLUSIVE REMEDY FOR ALL PROVEN CLAIMS IS REPLACEMENT OF OUR MATERIALS AND IN NO EVENT SHALL WE BE LIABLE FOR SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

REV: 5/2004