

ACRYPRIME – SUBSTRATE II

TECHNICAL INFORMATION

DESCRIPTION

Acryprime Substrate II is a waterbased pure acrylic primer designed to minimize the bleed problem when applying elastomeric acrylic topcoats to asphaltic based built-up roofing.

TYPICAL PHYSICAL PROPERTIES

Color	Lt. Gray or Black
Weight per gallon	8.7
Solids, % by wt.	50 + 1%
PH	9.0
Viscosity (cps)	300 - 500
Application Rate	.5 to .75 gal/100 sq ft
Shelf Life	6 months

THE INFORMATION HEREIN IS TO ASSIST CUSTOMERS IN DETERMINING WHETHER OUR PRODUCTS ARE SUITABLE FOR THEIR APPLICATIONS. WE REQUEST THAT CUSTOMERS INSPECT AND TEST OUR PRODUCTS BEFORE USE AND SATISFY THEMSELVES AS TO CONTENTS AND SUITABILITY. OUR PRODUCTS ARE INTENDED FOR SALE TO INDUSTRIAL AND COMMERCIAL CUSTOMERS. WE WARRANT THAT OUR PRODUCTS WILL MEET OUR WRITTEN SPECIFICATIONS. NOTHING HEREIN SHALL CONSTITUTE ANY OTHER WARRANTY EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS, NOR IS PROTECTION FROM ANY LAW OR PATENT TO BE INFERRED. THE EXCLUSIVE REMEDY FOR ALL PROVEN CLAIMS IS REPLACEMENT OF OUR MATERIALS AND IN NO EVENT SHALL WE BE LIABLE FOR SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.