



ACRYPRIME SUBSTRATE SG

TECHNICAL INFORMATION DESCRIPTION

Acryprime Substrate SG is a high property acrylic primer based on advanced acrylic technology and has excellent adhesion to built up roofing systems . The deep black color is designed to raise the solar gain on the substrate for quicker drying.

TYPICAL PHYSICAL PROPERTIES

Color	Black
Weight per gallon	8.5
Solvent	water
% Solids(weight)	28%
Application rate	0.3 to 0.5 gal/100 sq. ft
Shelf Life	6 months
Permeance @ 20 mils	9 perms

THE INFORMATION HEREIN IS TO ASSIST IN DETERMINING WHETHER OUR PRODUCTS ARE SUITABLE FOR THEIR APPLICATIONS. WE REQUEST THAT CUSTOMERS INSPECT AND TEST OUR PRODUCTS BEFORE USE AND SATISFY THEMSELVES AS TO CONTENTS AND SUITABILITY. OUR PRODUCTS ARE INTENDED FOR SALE TO INDUSTRIAL AND COMMERCIAL CUSTOMERS. WE WARRANT THAT OUR PRODUCTS WILL MEET OUR WRITTEN SPECIFICATIONS. NOTHING HEREIN SHALL CONSTITUTE ANY OTHER WARRANTY EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS, NOR IS PROTECTION FROM ANY LAW OR PATENT TO BE INFERRED. THE EXCLUSIVE REMEDY FOR ALL PROVEN CLAIMS IS REPLACEMENT OF OUR MATERIALS AND IN NO EVENT SHALL WE BE LIABLE FOR SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.