



HOHMANN & BARNARD, INC.  
a MiTek company

## Flashing and Reglets

# ENVIRO-BARRIER™ MASTIC

### PRODUCT DESCRIPTION & USES

ENVIRO-BARRIER™ Mastic is water based single component gun or trowel applied mastic. It is designed to patch air barrier repairs, terminate edges of vertical transitional tapes, and fill voids during the air barrier application process. On vertical applications, the mastic must be applied to both the top and bottom terminations.

- Excellent adhesion – bonds to substrate and remains permanently pressure sensitive.
- Aggressive tack – provides a tenacious bond to substrates such as CMU, glass faced sheathing panels, plywood and OSB.
- Fast Drying – allows for tight application schedules
- VOC compliant – water-based and contains no hazardous or flammable solvents.
- Low odor – no noxious fumes.

### INSTALLATION

**Surface Preparation:** All surfaces to receive mastic must be free from frost, dirt, grease, oil or other contaminants. Failure to remove excessive dirt may result in mastic adhesion failure.

**Application:** Apply mastic in dry weather with ambient and substrate temperatures above 40°F (5°C). Surface must be dry and clean. Mastic should be applied a 1/8" - 1/4" X 1 - 1 1/2" onto both surfaces in detail applications.

**Drying:** Allow mastic to dry until surface becomes tacky. Drying times may vary depending on temperature and humidity conditions. Typical drying time ranges from 10-30 minutes or more depending on thickness of mastic application.

**Cleanup:** Wet uncured mastic may be removed with soapy water. For dry fully cured primer, a citrus based cleaner may be used.

### STORAGE & HANDLING

ENVIRO-BARRIER™ Mastic should be stored under cover in original sealed containers above 40°F (4°C) and below 100°F (38°C). The shelf life is 1 year for unopened containers

### PACKAGING

ENVIRO-BARRIER™ Mastic is available in:

- 30 oz. tubes.
- 5-gallon pails



**NOTE:** When sealing non-asphalt Hohmann & Barnard flashing products use HB Sealant.

**IMPORTANT:** Since each construction project is unique, the appropriate selection and use of any product contained herein must be determined by competent architects, engineers and other appropriate professionals who are familiar with the specific requirements of the project in question.

HOHMANN & BARNARD, Inc.  
30 Rasons Court | Hauppauge, NY 11788  
CORPORATE HEADQUARTERS  
T: 800.645.0616 F: 631.234.0683  
[www.h-b.com](http://www.h-b.com)

Branch/Subsidiary Locations:  
ALABAMA - ILLINOIS - MARYLAND  
NEW YORK - PENNSYLVANIA - TEXAS  
UTAH - CANADA

© HOHMANN & BARNARD, INC. - 2015