


Aluminum Brick Vents Extruded Aluminum Brick Vent - Style "F"





DRAWINGS FOR ILLUSTRATIVE PURPOSES ONLY

Style "F" Brick Vent Description:

- Extruded Aluminum, minimum .125" 6063-T5 alloy
- 1 1/2" deep with 1" flanges
- Extruded stop for screen retention
- Overlapping blades, all at 45°, with storm lip
- Continuous weepage on bottom
- Standard 204-RI clear anodized finish (Non-standard finishes include medium or dark bronze anodized, kynar or baked enamel.)
- Special custom sizes available
- Lengths up to 8 ft. available without front mullions-continuous blade effect.

Note: Can be equipped with operable damper and ducts

Free Area Calculations: (measurements expressed in Square Feet)

		Outside Height (in inches)				
		2 %"	4 3/4"	7 3/4"	11 ¾"	15 ¾"
	8"	.029	.080	.136	.207	.279
	12"	.044	.120	.204	.310	.418
Width (in inches)	15 %"	.056	.156	.263	.400	.540
	16 ½"	.060	.196	.280	.426	.575
	24"	.088	.271	.408	.620	.836
	32"	.117	.321	.543	.816	1.115

H&B manufactures aluminum brick vents from a minimum of 41% pre-consumer and 23% post-consumer recycled material.

Model Number	W x H (Nominal)			
F 825	8 1/8" x 2 3/8"			
F 847	8 1/8" x 4 3/4"			
F 808	8 1/8" x 7 3/4"			
F 125	12" x 4 ¾"			
F 128	12" x 7 ¾"			
F 1212	12" x 11 ¾"			
F 157	15 %" x 7 ¾"			
F 1516	15 %" x 15 ¾"			
F 162	16 ½" x 2 ¾"			
F 164	16 ½" x 4 ¾"			
F 168	16 ½" x 7 ¾"			
F 1616	16 ½" x 15 ¾"			
F 244	24" x 4 ¾"			
F 248	24" x 7 ¾"	Note: "F" Vents add 1"		
F 3208	32" x 7 ¾"	face flange on 4 sides to		
F 4808	48" x 7 ¾"	nominal size. Add ½" to nominal width for mechanical fastener heads.		
Custom				

Mullions: YES NO

*Vents can be made to any specified height or width WITHOUT exposed mullions.

HOHMANN & BARNARD, Inc.

30 Rasons Court | Hauppauge, NY 11788 CORPORATE HEADQUARTERS

T: 800.645.0616 F: 631.234.0683 www.h-b.com

Branch/Subsidiary Locations: ALABAMA - ILLINOIS - MARYLAND NEW YORK - PENNSYLVANIA - TEXAS CANADA © HOHMANN & BARNARD, INC. - 2012