

#### 1. Identification

Product Identifier: **#341 Round Weep Holes, PTA Tubes & Plastic Termination Bar – Pellets Rigid Vinyl Compound** Manufacturer: Telephone Numbers

Hohmann & Barnard, Inc. 30 Rasons Court Hauppauge, NY 11788 (631) 234-0600 www.h-b.com Telephone Numbers During normal business hours call: (800) 645-0616 24-hour emergency call Chemtrec: (800) 255-3924

#### 2. Hazards Identification

In pelletized form rigid PVC compounds present no known acute or chronic health hazards. Routes of entry via skin, inhalation or ingestion are improbable. If ingestion should occur consult a physician.

If thermal degradation of the PVC should occur, exposure to the resulting hydrogen chloride fumes should be minimized. Direct exposure to sufficient quantities of hydrogen chloride may cause breathing difficulties. Move the individual to fresh air and provide appropriate first aid. Exposure to large quantities of hydrogen chloride may result in acute and/or chronic health problems. Treatment by a physician is recommended. In smaller quantities, hydrogen chloride is primarily an irritant to the eyes, mucous membranes and skin. Washing the skin with soap and water and flushing the eyes with clean, cool water is usually sufficient. If the irritation persists, see a physician.

#### 3. Composition/Information on Ingredients

Rigid PVC compounds may contain one or more of the following ingredients that by themselves may be considered" hazardous".

Organometallic Stabilizers Titanium Dioxide Acrylic Polymers/Styrenic Polymers Inorganic Fillers Pigments

Note that use of the word "hazardous" is as required and defined in the OSHA Hazard Communication Standard (20 CFR1 910, 1200) and does not necessarily imply that the materials are hazardous of the levels and/or in the physical forms used.

The exact compositions of Prime PVC rigid PVC formulations are "Trade Secrets", as defined in section (1) of the above standard. If more detailed information is required, please contact Hohmann& Barnard, Inc.



#### 4. First-Aid Measures

Ingestion: Consult physician.

# 5. Fire-fighting measures

Rigid PVC compounds are self-extinguishing and will not support combustion. When exposed to sufficient heat from other burning materials, the compounds may thermally decompose. See Section 10 below.

If PVC compounds are present in a fire lighting situation, use of a NIOSH approved self-contained breathing apparatus with a full face mask is required. Fire fighting procedures may include the use of water spray, fog or foam, dry chemicals or carbon dioxide. However the presence of other materials and/or equipment in the area should be considered in selecting an appropriate fire fighting medium.

# HOHMANN & BARNARD, INC.

## 6. Accidental release measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Sweep or vacuum immediately to avoid slips and falls. WASTE DISPOSAL METHODS: Landfill disposal. CLEAN WATER ACT REQUIREMENTS: No data found.

RESOURCE CONSERVATION AND RECOVERY ACT (RCRA) REQUIREMENTS: No data found.

#### 7. Handling and storage

Because of the physical form of the pelletized PVC compound spilled material should be swept or vacuumed up immediately to avoid slips and falls .

Rigid PVC pellets would not normally be considered "Hazardous Waste" and therefore could be disposed of via landfill, the user is responsible for complying with federal, state and local disposal regulations. If the material is supplied in boxes, or bags, the material should be stored in a sprinkled area, since the containers themselves may be combustible.

In addition, safe stacking practices should be observed. Stacking boxes or pelletized bags more than two layers high is not recommended.

#### 8. Exposure controls/personal protection ENGINEERING CONTROLS: No data found. ADMINISTRATIVE CONTROLS: No data found.

## PERSONAL PROTECTIVE EQUIPMENT

Not required under normal circumstances, however industrial hygiene practices suggest that gloves and/or safety glasses be used in the workplace, especially if working with hot PVC Polymer.

VENTILATION No data found

#### 9. Physical and chemical properties

Boiling Point: N/A Vapor Pressure: N/A Vapor Density: N/A Solubility in Water: N/A Appearance and Odor: Roughly cylindrical pellets or beads with no appreciable odor . Specific Gravity: 1.30-1.50 Melting Point: 300"F Evaporation Rate: N/A % Volatiles: Nil

#### 10. Stability and reactivity

Materials to Avoid: acetal or acetal copolymers in elevated temperature processing equipment.

Under normal conditions, rigid PVC compounds are quite stable and inert. When materials based on PVC resin are exposed to heat for a period of time, they may thermally decompose. The onset of decomposition is accelerated by higher temperatures (e.g. above 400°F). Such thermal decomposition will produce primarily hydrogen chloride gas plus smaller quantities of carbon monoxide, carbon dioxide and smoke.

Hydrogen Chloride is an extremely hygroscopic acid gas. That means it will dissolve instantly in any available water, including perspiration, tears or saliva to form hydrochloric acid Exposure to small amounts of hydrogen chloride will cause irritation of the skin, eyes and the membranes in the mouth and nose, Exposure to large quantities of hydrogen chloride can cause disruption of breathing due to displacement of oxygen and to the body's instinctive suppression of the inhalation reflex.

If thermal degradation should occur, use of a NJOSH approved self-contained breathing apparatus with a full face mask is required for any employees exposed to the hydrogen chloride will be minimized by isolating any material that has begun to degrade and then cooling it by any practical means, including water spray.

Mechanical ventilation should be used to clear enclosed spaces of fumes.

11. Toxicological information ROUTES OF ENTRY: Inhalation TARGET ORGANS: eyes, mucous membranes and skin CARCINOGENICITY: No data found.

# 12. Ecological Information

No data found.

- **13. Disposal Considerations** Follow state and local regulations.
- **14. Transport information** No data found.
- **15. Regulatory Information** No data found.

# 16. Other information

Issue Date: May 31, 2015 Revision Date: May 31, 2015

The data in this Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. This information is taken from sources or based upon data believed to be reliable; however, Hohmann & Barnard, Inc. disclaims any warranty, express or implied, as to the absolute correctness or sufficiency of any of the foregoing or that additional or other measures may be required under particular conditions.

The information contained herein is based on current knowledge and experience; no responsibility is accepted and that the information is sufficient or correct in all cases. Users should consider this data only as a supplement to other information. Users should make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials, the safety and health of employees and customer, and the protection of the environment.

