	TAINLESS STEEL STONE ANCHORS 407 STONE ANCHOR therein must be determined by competent architects, engineers and other professionals who are familiar with the specific requirements of the project.
	Washer
QUANTITY:	
ST/ST Rounds Min. Fy. = 75,000 p.s.i. (ASTM A580/A580M) DRAWINGS FOR ILLUSTRATIVE PURPOSES ONLY	
FINISH:	DIAMETER:
TYPE 304 Stainless Ste	el 🗌 3/16"/4.7 mm 🗌 3/8"/9.5 mm 🗌 3/4"/19 mm
TYPE 316 Stainless Ste	
	5/16"/7.9 mm 5/8"/15.8 mm
H&B recommends the exclusive use of 304 or 316 Stainless Steel for stone anchorage.	
PROJECT NAME:	CONTACT INFO
LOCATION:	Name :
NOTES:	Company: Phone: FAX:
	Email:
Due to fabrication requirements and lead times, once a custom anchor order has been scheduled it cannot be cancelled and will not be returnable. Verify all measurements before signing this form. Any changes after the initial order is placed will require a new signed form, and an additional charge. By signing this document, you agree to the terms stated above and accept full responsibility for the accuracy of measurements. Dread and a comparison of the accuracy of measurements. Dread and the accuracy of th	
HOHMANN & BARNARD, Inc. CORPORATE HEADQUARTERS	Branch/Subsidiary Locations: ALABAMA - ILLINOIS
150 Motor Parkway   Suite 410 Hauppauge, NY 11788	MARYLAND - NEW YORK - PENNSYLVANIA TEXAS - MARYLAND - UTAH - CANADA
TF: 800.645.0616 www.h-b.com	© 2013-2023