	AINLESS STEEL STONE ANCHOUSE AND	selection and use of
QUANTITY:	c	
ST/ST Plate Min. Fy. = 45,000 p.s.i. (ASTM A666)		
FINISH:	THICKNESS:	
TYPE 304 Stainless Ste	el 🗌 12 ga./2.78 mm 🗌 3/16"/4	.7 mm 🗌 3/8"/9.5 mm
TYPE 316 Stainless Ste	el 🗌 1/8"/3.2 mm 🗌 1/4"/6.3	3 mm 🗌 OTHER
H&B recommends the exclusive use of 304 or 316 Stainless Steel for stone anchorage.		
PROJECT NAME: LOCATION: NOTES:	CONTACT INFO Name : Company: Phone: Email:	FAX:
Due to fabrication requirements and lead tim order has been scheduled it cannot be cancer returnable. Verify all measurements before s changes after the initial order is placed will re and an additional charge. By signing this door terms stated above and accept full responsite measurements.	Iled and will not be Orders without a signatur gning this form. Any anew signed form, ument, you agree to the ACCEPTED BY:	
HOHMANN & BARNARD, Inc. CORPORATE HEADQUARTERS 150 Motor Parkway Suite 410 Hauppauge, NY 11788 TF: 800.645.0616 www.h-b.com	Branch/Subsidiary Locations: ALABAMA - ILLINOIS MARYLAND - NEW YORK - PENNSYLVANIA TEXAS - MARYLAND - UTAH - CANADA	© 2013-2023