



# Asphalt Cement (Asphalt)

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Revision Date: 05/12/2021

Date of Issue: 05/18/2015

Supersedes Date: 08/10/2018

Version: 3.0

### SECTION 1: IDENTIFICATION

#### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** Asphalt Cement (Asphalt)

**Synonyms:** Asphalt Cement, Petroleum Asphalt, Unmodified Asphalt Cement, Polymer Modified Asphalt Cement, Neat Asphalt Cement, Bitumen, 40-50, 60-70, 85-100, 120-150, 150-200, 160-180, 200-300, 300-400, AC-10, AC-20, PG 46-34, PG 52-28, PG 52-34, PG 52-34 PMA, PG 52-40, PG 52-40 PMA, PG 58-22, PG 58-28, PG 58-34, PG 58-34 PMA, PG 58-40, PG 58-40 PMA, PG 64-22, PG 64-22 PMA, PG 64-28, PG 64-28 PMA, PG 64-34, PG 64-34 PMA, PG 64-40, PG 64-40 PMA, PG 70-22, PG 70-22 PMA, PG 70-28, PG 70-28 PMA, PG 70-34, PG 70-34 PMA, PG 76-22, PG 76-22 PMA, PG 76-28, PG 76-28 PMA

**Note:** This SDS covers many types of Asphalt Cements. Individual composition of hazardous constituents will vary between types of asphalt.

#### 1.2. Intended Use of the Product

HMA is used for paving roads, driveways, parking lots and other surface, base, or sub-base applications.

#### 1.3. Name, Address, and Telephone of the Responsible Party

##### Company

LafargeHolcim in the US

8700 West Bryn Mawr Avenue, Suite 300

Chicago, IL 60631

Information: (888) 646-5246 (9am to 5pm CST)

Email: [us-sds-inquiries@lafargeholcim.com](mailto:us-sds-inquiries@lafargeholcim.com)

Website: [www.MaterialsThatPerform.com](http://www.MaterialsThatPerform.com)

The LafargeHolcim companies in the US include Holcim (US)

Inc., Aggregate Industries Management Inc., and their

subsidiaries and affiliates.

#### 1.4. Emergency Telephone Number

**Emergency Number** : CHEMTREC 1-800-424-9300 (24 hours)

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the Substance or Mixture

##### GHS-US/CA Classification

Carc. 2 H351

Full text of hazard classes and H-statements : see section 16

#### 2.2. Label Elements

##### GHS-US/CA Labeling

**Hazard Pictograms (GHS-US/CA)** :



GHS08

**Signal Word (GHS-US/CA)** : Warning

**Hazard Statements (GHS-US/CA)** : H351 - Suspected of causing cancer.

**Precautionary Statements (GHS-US/CA)** : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P280 - Wear protective gloves, protective clothing, and eye protection.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

#### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions. Hot asphalt can release toxic Hydrogen Sulfide gas! Hydrogen Sulfide can accumulate in vapor space of tanks and vessels during transfer and storage of this material.

# Asphalt Cement (Asphalt)

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### 2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Synonyms	Product Identifier	% *	GHS Ingredient Classification
Asphalt	Asphalt (petroleum) / Bitumens / Bitumen / Bituminous asphalt / Bitumens, asphalt / Hydrocarbon resin / Asphalt (A very complex combination of high molecular weight organic compounds containing a relatively high proportion of hydrocarbons having carbon numbers predominantly greater than C25 with high carbon-to-hydrogen ratios. It also contains small amounts of various metals such as nickel, iron, or vanadium. It is obtained as the non-volatile residue from distillation of crude oil or by separation as the raffinate from a residual oil in a deasphalting or decarbonization process.)	(CAS-No.) 8052-42-4	80 – 100	Carc. 2, H351
Sulfur	Sulphur / Sulphur, molten / Elemental sulfur / Brimstone / Elemental sulphur / Sulfur, elemental	(CAS-No.) 7704-34-9	≤ 7	Skin Irrit. 2, H315 Aquatic Acute 3, H402 Aquatic Chronic 3, H412 Comb. Dust
Hydrogen sulfide	Hydrogen sulfide (H2S) / Hydrogen sulphide / Sulfur hydride / Dihydrogen sulphide / Hydrogen sulphide, hydrogen sulfide	(CAS-No.) 7783-06-4	**	Flam. Gas 1, H220 Press. Gas (Liq.), H280 Acute Tox. 2 (Inhalation:gas), H330 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT SE 1, H370 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-phrases: see section 16

\*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

\*\*May be formed during processing.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Remove contaminated clothing. Removal of solidified molten material from skin requires medical assistance. Drench affected area with water for at least 5 minutes. If exposed or concerned: Get medical advice/attention.

**Eye Contact:** Removal of solidified molten material from the eyes requires medical assistance. Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** This product, if heated may release asphalt fumes. During processing, inhalation of fumes may cause dizziness and/or irritation to the eyes, nose, and throat. Hot molten product will cause thermal burns to the skin. Suspected of causing cancer.

# Asphalt Cement (Asphalt)

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Inhalation:** Toxic fumes may be generated from heating asphalt and may be harmful if inhaled. WARNING: irritating and toxic hydrogen sulfide gas may be present. Greater than 15-20ppm continuous exposure can cause mucous membrane and respiratory tract irritation. 50-500 ppm can cause headache, nausea, and dizziness. Continued exposure at these levels can lead to loss of reasoning and balance, difficulty in breathing, fluid in the lungs, and possible loss of consciousness. Greater than 500ppm can cause rapid unconsciousness and death if not promptly revived. Hydrogen sulfide may cause respiratory paralysis. Prolonged exposure may cause irritation.

**Skin Contact:** Prolonged exposure may cause skin irritation. Risk of thermal burns on contact with molten product.

**Eye Contact:** May cause slight irritation to eyes. Risk of thermal burns on contact with molten product.

**Ingestion:** Ingestion may cause adverse effects.

**Chronic Symptoms:** Emissions from asphalt are suspected of causing cancer. If dust is generated, repeated exposure through inhalation may cause cancer or lung disease. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Water spray, dry chemical, foam, carbon dioxide.

**Unsuitable Extinguishing Media:** Do not use water when molten material is involved, may react violently or explosively on contact with water. Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not considered flammable but may burn at high temperatures.

**Explosion Hazard:** In molten state: reacts violently with water (moisture).

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and oxides of sulfur and/or nitrogen. Hydrogen sulfide and other sulfur-containing gases can evolve from this product particularly at elevated temperatures.

### 5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not get in eyes, on skin, or on clothing. Do not breathe dust.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Recover the product by vacuuming, shoveling or sweeping. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

# Asphalt Cement (Asphalt)

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### SECTION 7: HANDLING AND STORAGE

#### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** If stored under heat for extended periods or significantly agitated, this material might evolve or release hydrogen sulfide, a flammable gas, which can raise and widen this material's actual flammability limits and significantly lower its auto-ignition temperature. Hydrogen sulfide is a toxic gas that can be fatal. It also has a rotten egg smell that causes odor fatigue very quickly and shouldn't be used as an indicator for the presence of gas.

**Precautions for Safe Handling:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Do not breathe dust. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

#### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers. Fluorine.

**Storage Temperature:** Unlimited

#### 7.3. Specific End Use(s)

HMA is used for paving roads, driveways, parking lots and other surface, base, or sub-base applications.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Asphalt (8052-42-4)		
USA ACGIH	ACGIH OEL TWA	0.5 mg/m <sup>3</sup> (fume, inhalable particulate matter)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen fume, coal tar-free
USA ACGIH	BEI (BLV)	2.5 µg/l Parameter: 1-Hydroxypyrene with hydrolysis - Medium: urine - Sampling time: end of shift at end of workweek (background) Parameter: 3-Hydroxybenzo(a)pyrene with hydrolysis - Medium: urine - Sampling time: end of shift at end of workweek (nonquantitative)
USA NIOSH	NIOSH REL (Ceiling)	5 mg/m <sup>3</sup> (fume)
Alberta	OEL TWA	5 mg/m <sup>3</sup> (Petroleum-fume)
British Columbia	OEL TWA	0.5 mg/m <sup>3</sup> (inhalable fume)
Manitoba	OEL TWA	0.5 mg/m <sup>3</sup> (fume, inhalable particulate matter)
New Brunswick	OEL TWA	5 mg/m <sup>3</sup> (petroleum fumes)
Newfoundland & Labrador	OEL TWA	0.5 mg/m <sup>3</sup> (fume, inhalable particulate matter)
Nova Scotia	OEL TWA	0.5 mg/m <sup>3</sup> (fume, inhalable particulate matter)
Nunavut	OEL STEL	1.5 mg/m <sup>3</sup> (Bitumen-fume)
Nunavut	OEL TWA	0.5 mg/m <sup>3</sup> (Bitumen-fume)
Northwest Territories	OEL STEL	1.5 mg/m <sup>3</sup> (Bitumen-fume)
Northwest Territories	OEL TWA	0.5 mg/m <sup>3</sup> (Bitumen-fume)
Ontario	OEL TWA	0.5 mg/m <sup>3</sup> (fume, inhalable particulate matter)
Prince Edward Island	OEL TWA	0.5 mg/m <sup>3</sup> (fume, inhalable particulate matter)
Québec	VEMP (OEL TWA)	5 mg/m <sup>3</sup> (fume)
Saskatchewan	OEL STEL	1.5 mg/m <sup>3</sup> (fume and inhalable fraction)
Saskatchewan	OEL TWA	0.5 mg/m <sup>3</sup> (fume and inhalable fraction)
Yukon	OEL STEL	10 mg/m <sup>3</sup> (fume)
Yukon	OEL TWA	5 mg/m <sup>3</sup> (fume)
Sulfur (7704-34-9)		
Alberta	OEL TWA	10 mg/m <sup>3</sup>
Hydrogen sulfide (7783-06-4) * May be formed during processing.		

# Asphalt Cement (Asphalt)

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

USA ACGIH	ACGIH OEL TWA [ppm]	1 ppm
USA ACGIH	ACGIH OEL STEL [ppm]	5 ppm
USA OSHA	OSHA PEL C [ppm]	20 ppm
USA OSHA	Acceptable Maximum Peak Above The Acceptable Ceiling Concentration For An 8-Hr Shift	50 ppm Peak (10 minutes once, only if no other measurable exposure occurs)
USA NIOSH	NIOSH REL (Ceiling)	15 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL C [ppm]	10 ppm
USA IDLH	IDLH [ppm]	100 ppm
Alberta	OEL C	21 mg/m <sup>3</sup>
Alberta	OEL Ceiling [ppm]	15 ppm
Alberta	OEL TWA	14 mg/m <sup>3</sup>
Alberta	OEL TWA [ppm]	10 ppm
British Columbia	OEL Ceiling [ppm]	10 ppm
Manitoba	OEL STEL [ppm]	5 ppm
Manitoba	OEL TWA [ppm]	1 ppm
New Brunswick	OEL STEL	21 mg/m <sup>3</sup>
New Brunswick	OEL STEL [ppm]	15 ppm
New Brunswick	OEL TWA	14 mg/m <sup>3</sup>
New Brunswick	OEL TWA [ppm]	10 ppm
Newfoundland & Labrador	OEL STEL [ppm]	5 ppm
Newfoundland & Labrador	OEL TWA [ppm]	1 ppm
Nova Scotia	OEL STEL [ppm]	5 ppm
Nova Scotia	OEL TWA [ppm]	1 ppm
Nunavut	OEL STEL [ppm]	15 ppm
Nunavut	OEL TWA [ppm]	10 ppm
Northwest Territories	OEL STEL [ppm]	15 ppm
Northwest Territories	OEL TWA [ppm]	10 ppm
Ontario	OEL STEL [ppm]	15 ppm
Ontario	OEL TWA [ppm]	10 ppm
Prince Edward Island	OEL STEL [ppm]	5 ppm
Prince Edward Island	OEL TWA [ppm]	1 ppm
Québec	VECD (OEL STEL)	21 mg/m <sup>3</sup>
Québec	VECD (OEL STEL) [ppm]	15 ppm
Québec	VEMP (OEL TWA)	14 mg/m <sup>3</sup>
Québec	VEMP (OEL TWA) [ppm]	10 ppm
Saskatchewan	OEL STEL [ppm]	15 ppm
Saskatchewan	OEL TWA [ppm]	10 ppm
Yukon	OEL STEL	27 mg/m <sup>3</sup>
Yukon	OEL STEL [ppm]	15 ppm
Yukon	OEL TWA	15 mg/m <sup>3</sup>
Yukon	OEL TWA [ppm]	10 ppm

## 8.2. Exposure Controls

**Appropriate Engineering Controls:** Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Suitable eye/body wash equipment should be available in the vicinity of any potential exposure.

**Personal Protective Equipment:** Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear protective gloves.

# Asphalt Cement (Asphalt)

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Eye and Face Protection:** Chemical safety goggles.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

**Thermal Hazard Protection:** If material is hot, wear thermally resistant protective gloves.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	: Solid
Appearance	: Black Granular Solid
Odor	: Slight Petroleum Odor
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: > 93.3 °C (199.94 °F)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20°C	: Not available
Relative Density	: Not available
Specific Gravity	: 2.0 - 2.5 (Water = 1)
Solubility	: Water: Insoluble in water
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available

## SECTION 10: STABILITY AND REACTIVITY

**10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.

**10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).

**10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.

**10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers. Fluorine.

**10.6. Hazardous Decomposition Products:** Thermal decomposition may produce: Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and oxides of sulfur and/or nitrogen. Hydrogen sulfide and other sulfur-containing gases can evolve from this product particularly at elevated temperatures.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects - Product

**Acute Toxicity (Oral):** Not classified

**Acute Toxicity (Dermal):** Not classified

**Acute Toxicity (Inhalation):** Not classified

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Not classified

**Eye Damage/Irritation:** Not classified

**Respiratory or Skin Sensitization:** Not classified

# Asphalt Cement (Asphalt)

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** Suspected of causing cancer.

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** Toxic fumes may be generated from heating asphalt and may be harmful if inhaled. WARNING: irritating and toxic hydrogen sulfide gas may be present. Greater than 15-20ppm continuous exposure can cause mucous membrane and respiratory tract irritation. 50-500 ppm can cause headache, nausea, and dizziness. Continued exposure at these levels can lead to loss of reasoning and balance, difficulty in breathing, fluid in the lungs, and possible loss of consciousness. Greater than 500ppm can cause rapid unconsciousness and death if not promptly revived. Hydrogen sulfide may cause respiratory paralysis. Prolonged exposure may cause irritation.

**Symptoms/Injuries After Skin Contact:** Prolonged exposure may cause skin irritation. Risk of thermal burns on contact with molten product.

**Symptoms/Injuries After Eye Contact:** May cause slight irritation to eyes. Risk of thermal burns on contact with molten product.

**Symptoms/Injuries After Ingestion:** Ingestion may cause adverse effects.

**Chronic Symptoms:** Emissions from asphalt are suspected of causing cancer. If dust is generated, repeated exposure through inhalation may cause cancer or lung disease. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss.

## 11.2. Information on Toxicological Effects - Ingredient(s)

### LD50 and LC50 Data:

<b>Asphalt (8052-42-4)</b>	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 94.4 mg/m <sup>3</sup>
<b>Sulfur (7704-34-9)</b>	
LD50 Oral Rat	> 3000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 9.23 mg/l/4h
<b>Hydrogen sulfide (7783-06-4)</b>	
LC50 Inhalation Rat	444 ppm/4h
<b>Asphalt (8052-42-4)</b>	
IARC Group	2A, 2B
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

**Ecology - General:** Not classified.

<b>Sulfur (7704-34-9)</b>	
LC50 Fish 1	866 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 - Crustacea [1]	736 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	14 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
<b>Hydrogen sulfide (7783-06-4)</b>	
LC50 Fish 1	0.0448 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
LC50 Fish 2	0.016 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

### 12.2. Persistence and Degradability

<b>Asphalt Cement (Asphalt)</b>	
Persistence and Degradability	Not established.

### 12.3. Bioaccumulative Potential

<b>Asphalt Cement (Asphalt)</b>	
Bioaccumulative Potential	Not established.

# Asphalt Cement (Asphalt)

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>Asphalt (8052-42-4)</b>	
<b>BCF Fish 1</b>	(no bioaccumulation expected)
<b>Partition coefficient n-octanol/water (Log Pow)</b>	> 6
<b>Hydrogen sulfide (7783-06-4)</b>	
<b>BCF Fish 1</b>	(no bioaccumulation expected)
<b>Partition coefficient n-octanol/water (Log Pow)</b>	0.45 (at 25 °C)

**12.4. Mobility in Soil** Not available

### 12.5. Other Adverse Effects

**Other Information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

**Ecology - Waste Materials:** Avoid release to the environment.

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

### 14.1. In Accordance with DOT

**Proper Shipping Name** : ELEVATED TEMPERATURE SOLID, N.O.S.(Asphalt)  
**Hazard Class** : 9  
**Identification Number** : UN3258  
**Label Codes** : 9  
**Packing Group** : III  
**ERG Number** : 128



### 14.2. In Accordance with IMDG

**Proper Shipping Name** : ELEVATED TEMPERATURE SOLID, N.O.S.(Asphalt)  
**Hazard Class** : 9  
**Identification Number** : UN3258  
**Label Codes** : 9  
**Packing Group** : III  
**EmS-No. (Fire)** : F-A  
**EmS-No. (Spillage)** : S-P



### 14.3. In Accordance with IATA

**Proper Shipping Name** : ELEVATED TEMPERATURE SOLID, N.O.S. (Asphalt)  
**Hazard Class** : 9  
**Identification Number** : UN3258  
**Label Codes** : 9  
**ERG Code (IATA)** : 9L



### 14.4. In Accordance with TDG

**Proper Shipping Name** : ELEVATED TEMPERATURE SOLID, N.O.S.(Asphalt)  
**Hazard Class** : 9  
**Identification Number** : UN3258  
**Label Codes** : 9  
**Packing Group** : III



## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

<b>Asphalt Cement (Asphalt)</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Health hazard - Carcinogenicity



# Asphalt Cement (Asphalt)

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>Asphalt (8052-42-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Sulfur (7704-34-9)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Hydrogen sulfide (7783-06-4)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on the United States SARA Section 302	
Subject to reporting requirements of United States SARA Section 313	
<b>CERCLA RQ</b>	100 lb
<b>SARA Section 302 Threshold Planning Quantity (TPQ)</b>	500 lb
<b>SARA Section 313 - Emission Reporting</b>	1 %

### 15.2. US State Regulations

#### California Proposition 65



**WARNING:** This product can expose you to Bitumens, extracts of steam-refined and air refined, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemical Name	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Bitumens, extracts of steam-refined and air refined	X			

<b>Asphalt (8052-42-4)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List
<b>Sulfur (7704-34-9)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List
<b>Hydrogen sulfide (7783-06-4)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

### 15.3. Canadian Regulations

<b>Asphalt (8052-42-4)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Sulfur (7704-34-9)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Hydrogen sulfide (7783-06-4)</b>
Listed on the Canadian DSL (Domestic Substances List)

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Date of Preparation or Latest Revision** : 05/12/2021

#### Other Information

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

#### GHS Full Text Phrases:

Acute Tox. 2 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 2
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1

# Asphalt Cement (Asphalt)

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Carc. 2	Carcinogenicity Category 2
Comb. Dust	Combustible Dust
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Gas 1	Flammable gases Category 1
Press. Gas (Liq.)	Gases under pressure Liquefied gas
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H315	Causes skin irritation
H319	Causes serious eye irritation
H330	Fatal if inhaled
H335	May cause respiratory irritation
H351	Suspected of causing cancer
H370	Causes damage to organs
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

*LafargeHolcim in the US believes the information contained herein is accurate; however, LafargeHolcim in the US makes no guarantees with respect to such accuracy and assumes no liability in connection with the use of the information contained herein which is not intended to be and should not be construed as legal advice or as insuring compliance with any federal, state or local laws or regulations. Any party using this product should review all such laws, rules, or regulations prior to use, including but not limited to US and Canada Federal, Provincial and State regulations.*

**NO WARRANTY IS MADE, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OTHERWISE.**

NA GHS SDS 2015 (Can, US)