

1. Identification

Product identifier	Gypsum
Other means of identification	
Synonyms	Alabaster, Gypsum Stone, Land Plaster, Terra Alba, Native Calcium Sulfate, Calcium Sulfate Dihydrate.
Recommended use	Construction.
Recommended restrictions	Uses other than the recommended use.
Manufacturer/Importer/Supplier/Distributor information	
Company Name	Amrize Inc.
Address	8700 W Bryn Mawr Ave, Suite 300 Chicago, IL 60631
Telephone	(773) 372-1000
Website	www.amrize.com
E-mail	sdsinfo@amrize.com
Emergency Telephone Number	CHEMTREC within USA and Canada: 1-800-424-9300 CHEMTREC outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2. Hazard(s) identification

Physical hazards	Not classified.
Health hazards	Carcinogenicity (inhalation) Category 1A Specific target organ toxicity, repeated exposure (inhalation) Category 2 (Lungs)
OSHA defined hazards	Not classified.
Label elements	



Signal word	Danger
Hazard statement	May cause cancer by inhalation. May cause damage to organs (Lungs) through prolonged or repeated exposure by inhalation.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If exposed or concerned: Get medical advice/attention.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Calcium sulfate dihydrate	13397-24-5	>= 90 - <= 99
Limestone	1317-65-3	< 10

Chemical name	CAS number	%
Quartz	14808-60-7	< 2

Composition comments All concentrations are in percent by weight. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4. First-aid measures

Inhalation	Move to fresh air. If not breathing, give artificial respiration. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed. Combustion products may include: Silicon oxides. Magnesium oxide. Calcium oxides.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Use water spray to cool unopened containers.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Will burn if involved in a fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Do not breathe dust. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS. The product is insoluble in water.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Components	Type	Value
Quartz (CAS 14808-60-7)	TWA	0.05 mg/m3

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Calcium sulfate dihydrate (CAS 13397-24-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Limestone (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

Components	Type	Value	Form
Calcium sulfate dihydrate (CAS 13397-24-5)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Quartz (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
Calcium sulfate dihydrate (CAS 13397-24-5)	TWA	10 mg/m3	Inhalable fraction.
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
Quartz (CAS 14808-60-7)	IDLH	50 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Calcium sulfate dihydrate (CAS 13397-24-5)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Quartz (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment**Eye/face protection**

If contact is likely, safety glasses with side shields are recommended.

Skin protection**Hand protection**

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Skin protection	
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Solid.
Form	Solid.
Color	White or colored surface; beige/gray core.
Odor	Odorless.
Odor threshold	Not applicable.
pH	$\geq 5 - \leq 8$
pH concentration	Property has not been measured.
Melting point/freezing point	Property has not been measured.
Initial boiling point and boiling range	$> 1832^{\circ}\text{F}$ ($> 1000^{\circ}\text{C}$)
Flash point	Not applicable, material is a solid.
Evaporation rate	Not applicable, material is a solid.
Flammability (solid, gas)	Will burn if involved in a fire.

Upper/lower flammability or explosive limits

Explosive limit - lower (%)	Not applicable, material is a solid.
Explosive limit - upper (%)	Not applicable, material is a solid.
Vapor pressure	Property has not been measured.
Vapor pressure temp.	Property has not been measured.
Vapor density	Not applicable, material is a solid.
Relative density	2.3
Relative density temperature	Property has not been measured.
Solubility(ies)	
Solubility (water)	Insoluble ($< 0.1\%$)
Partition coefficient (n-octanol/water)	Not applicable, product is a mixture.
Auto-ignition temperature	Not applicable, material is a solid.
Decomposition temperature	Property has not been measured.
Viscosity	Not applicable, material is a solid.
Other information	
Density	Property has not been measured.
Explosive properties	Not explosive.
Kinematic viscosity	Not applicable, material is a solid.
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.

Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong acids. Strong bases. Strong oxidizers. Hydrofluoric acid.
Hazardous decomposition products	No hazardous decomposition products are known. In the event of fire: See Section 5.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause cancer by inhalation. Prolonged inhalation may be harmful.
Skin contact	Prolonged skin contact may cause temporary irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation. Prolonged exposure may cause chronic effects.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
------------	---------	--------------

Quartz (CAS 14808-60-7)

Chronic

Inhalation

LOEC	Human	0.0563 mg/m3
------	-------	--------------

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer by inhalation. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

IARC Monographs. Overall Evaluation of Carcinogenicity

Quartz (CAS 14808-60-7) 1 Carcinogenic to humans.

NTP Report on Carcinogens

Quartz (CAS 14808-60-7) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (CAS 14808-60-7) Cancer

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure May cause damage to organs (Lungs) through prolonged or repeated exposure by inhalation.

Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.
--------------------	--

Components	Species	Test Results
Calcium sulfate dihydrate (CAS 13397-24-5)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) > 1970 mg/l, 96 hours
Persistence and degradability	The product contains inorganic compounds which are not biodegradable.	
Bioaccumulative potential	No data available.	
Mobility in soil	The product is insoluble in water. Not expected to be mobile in soil.	
Other adverse effects	No data available.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT	Not regulated as dangerous goods.
IATA	Not regulated as dangerous goods.
IMDG	Not regulated as dangerous goods.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.

15. Regulatory information

US federal regulations	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.	
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	Not regulated.	
CERCLA Hazardous Substance List (40 CFR 302.4)	Not listed.	
SARA 304 Emergency release notification	Not regulated.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)	Quartz (CAS 14808-60-7)	
		Cancer lung effects immune system effects kidney effects
Toxic Substances Control Act (TSCA)	All components of the mixture on the TSCA 8(b) inventory are designated "active".	

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

Yes

Classified hazard categories

Carcinogenicity
Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Calcium sulfate dihydrate (CAS 13397-24-5)

Limestone (CAS 1317-65-3)

Quartz (CAS 14808-60-7)

US. New Jersey Worker and Community Right-to-Know Act

Calcium sulfate dihydrate (CAS 13397-24-5)

Limestone (CAS 1317-65-3)

Quartz (CAS 14808-60-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Calcium sulfate dihydrate (CAS 13397-24-5)

Limestone (CAS 1317-65-3)

Quartz (CAS 14808-60-7)

US. Rhode Island RTK

Calcium sulfate dihydrate (CAS 13397-24-5)

Limestone (CAS 1317-65-3)

Quartz (CAS 14808-60-7)

California Proposition 65



WARNING: This product can expose you to Quartz, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Quartz (CAS 14808-60-7)

Listed: October 1, 1988

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 22-May-2025

Revision date -

Version # 01

HMIS® ratings Health: 2*
Flammability: 1
Physical hazard: 0

Disclaimer Amrize Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.