

Material Safety Data Sheet

Issue Date: September 3, 2009

Page 1 of 4

Section I – Identification**Product Identification:** Cellulose Based Fiber Board**Product Name:** 440 Homasote, 440 Sound Barrier (S/B) PINacle440, ComfortBase, 4-Way Floor Deck, Burlap Panel, Easy-Ply Roof Deck, Homex 300, Ice Deck, Nova Cork Panel, DesignWall440**Product Use/application:** Building Material**Company:** Homasote Company

P.O. Box 7240

West Trenton, NJ, 08628-0240

Contact Numbers:

Toll Free: 800-257-9491 Ext. 1500. Telephone: 609-883-3300. Fax: 609-406-9263

Website: www.homasote.com**Section II – Composition/Information on Ingredients**

Cellulose based material containing 1 to 2% paraffin wax, CAS 8002-74-2, and less than 0.1% copper base pesticide, CAS 39290-85-2. The product contains no known hazardous or carcinogenic components.

Section III – Hazards Identification**Routes of Entry:** skin contact, eye contact and inhalation of dust**Health Effects****Inhalation:** nasal dryness and mild irritation**Eye contact:** dryness and mild irritation**Skin contact:** can cause minor irritation and dryness**Section IV – First Aid Measures****Inhalation:** Move the individual to a dust-free area. Seek medical attention if persistent coughing or difficult breathing develops.**Skin Contact:** Wash with soap and water. Get medical attention if irritation develops or persists.**Eye Contact:** Treat as a foreign object. Flush eyes with water.**Section V – Fire Fighting Measures**

Material is flammable, not explosive

Extinguishing Media: Water, carbon dioxide (CO₂)**Special Risks:** Combustion produces irritating and toxic fumes and gases, including carbon monoxide (CO) and carbon dioxide (CO₂). Dust may explode at concentrations greater than 40 grams dust per cubic meter of air.**Special Protective Equipment:** Self contained breathing apparatus recommended.**Section VI – Accidental Release Measures**

No health related procedures required. Avoid or control conditions that could result in fire.

Material Safety Data Sheet

Issue Date: September 3, 2009
Page 2 of 4

Section VII – Handling and Storage

No health related procedures required. Avoid or control conditions that could result in fire.

Section VIII – Exposure Controls/Personal Protection

Personal Protective Equipment: recommended for sanding, sawing, and other machining

Respiratory Protection: dust mask and local exhaust

Eye Protection: safety glasses

Hand Protection: as required for mechanical operations

Industrial Hygiene: Follow normal work hygiene practices. No special practices required.

Section IX – Physical and Chemical Properties

Form: solid board

Odor: none

Melting Point: na

Ignition Temperature: 450 ° F

Density: 20 to 30 lb/ft³

Color: gray

pH: na

Boiling Point: na

Flash Point: na

Solubility in water: negligible

Explosion Limit – Lower: 40 grams of dust per cubic meter air for cellulose dust

Explosion Limit – Upper: unknown

Section X – Stability and Reactivity

Conditions to be Avoided: Conditions that could cause ignition or fire

Substance to be Avoided: none known

Hazardous Decomposition Product(s): Burning produces irritating and toxic smoke and fumes including paraffin wax fumes, carbon monoxide, and carbon dioxide.

Section XI – Toxicological Information

no known toxicological effects

Section XII – Ecological Information

Significant ecotoxic effects are not expected.

Section XIII – Disposal Considerations

Dispose in accordance with local, state, federal, and provincial environmental regulations.

Section XIV – Transportation Information

Road/Rail: not regulated by DOT

Material Safety Data Sheet

Issue Date: September 3, 2009
Page 3 of 4

Section XV – Regulatory Information

CERCLA: This product does not contain any chemicals subject to reporting as a CERCLA hazardous substance under 40 CFR 302.4

EPCRA: This product does not contain any chemicals subject to reporting as a toxic chemical under EPCRA Section 313.

CIS R(isk) Phrases:

R 10: Flammable

R 43: May cause sensitization by skin contact

R 66: Repeated exposure may cause skin dryness or cracking

CIS S(afety) Phrases:

S 15: Keep away from heat

S 16: Keep away from sources of ignition

S 17: Keep away from combustible material

S 22: Do not breathe dust

S 38: In case of insufficient ventilation, wear suitable respiratory equipment

S 41: In case of fire, do not breathe fumes.

Section XVI – Other Information

HMIS Ratings:

Health	1	slight hazard
Flammability	0	minimal hazard
Reactivity	0	minimal hazard

Safety Officer Telephone No: 609-883-3300, X1188
 Safety Officer Fax No: 609-530-1584
 Safety Officer 24hr Telephone No: 609-883-3300

List of Acronyms

ACGIH	American Conferences of Governmental Industrial Hygienists
CAS(RN)	Chemical Abstracts (Registry Number)
CERCLA	Comprehensive Emergency Response, Compensation, and Liability Act
CIS	International Occupational Safety and Health Information Center
EPCRA	Emergency Planning and Community Right-to-Know Act
HMIS	Hazardous Materials Identification System
IARC	International Agency for Research on Cancer
IDLH	Immediately Dangerous to Life or Health (NIOSH)
NIOSH	National Institute for Occupational Safety and Health
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	OSHA Permissible Exposure Limit
TLV	Threshold Limit Values (Registered Trademark of ACGIH)
TWA	Time Weighted Average

Material Safety Data Sheet

Issue Date: September 3, 2009
Page 4 of 4

The information contained herein is based on the present state of our knowledge.
The information contained herein characterizes the product with regard to the appropriate safety precautions.
The information contained herein does not represent a guarantee of the properties of the product.