

# Better Seen AND Not Heard!

IBC 1207 - Sound control in floors and walls in multi-family mandates a minimum of STC 50 and IIC 50

IBC = International Building Code • STC = Sound Transmission Class • IIC = Impact Insulation Class



## Failure to meet Code = major source of tenant lawsuits

The **combined floor and ceiling assembly** needs to meet the code – **floor only is not enough** to meet the code.

**440 SoundBarrier®** – the only structural fiberboard made for floors.

*It is recommended to **use products** that are independently tested and **show how the tests were done.**  
Homasote publishes complete testing details!*



*Successfully managing noise  
“keeps heads in beds”*

**HOMASOTE®**

*Sensible. Sound.  
Solutions.*



[www.homasote.com](http://www.homasote.com)

# 440 SoundBarrier®

# Safe and Secure

Specify and Install 440 SoundBarrier with Confidence

Use 440 SoundBarrier in tested and approved fire rated floor and wall assemblies that carry the UL (Underwriter's Laboratory) hourly ratings.

Fire Ratings are assigned to entire floor/ceiling and wall assemblies – not to individual product components of those systems.



## U.L. FIRE RESISTANCE RATING DESIGN NUMBERS WITH 440 SOUNDBARRIER INCLUDE:

G203	G208	G227	G228	G229	G243	G268	G301
G524	G525	G531	J201	L210	L206	L501	L502
L503	L504	L505	L506	L507	L508	L509	L510
L511	L512	L513	L514	L515	L516	L517	L518
L519	L520	L521	L522	L523	L524	L525	L526
L527	L528	L529	L532	L533	L534	L535	L536
L537	L538	L539	L540	L541	L542	L543	L545
L546	L547	L549	L550	L551	L552	L555	L556
L562	M503	M504	U339	U341	U356	U390	V448

*Made of 98% Recycled Content • Twice the R-Value of Wood*

## HOMASOTE®

*Sensible. Sound.  
Solutions.*

800-257-9491 • Technical Support call Ext. 1332 or e-mail [techhelp@homasote.com](mailto:techhelp@homasote.com)

[www.homasote.com](http://www.homasote.com)