



PERFORMANCE

NORDIC™ & DYNASTY® SHINGLES



Nordic shingles are available in select markets.



Color Featured: **Glacier**



HI-DEF
COLORS



IKO
ARMOURZONE®



HIGH-WIND
RESISTANCE



NORDIC™



DYNASTY®

For Your Customers Who Want the Best, IKO Offers Two Best-in-Class Shingles.

Nordic: Quite possibly the best laminate asphalt shingle money can buy. Offer your customers the peace of mind that comes from knowing they are providing the best for their families. As weather patterns become more unpredictable, Nordic presents your best asphalt shingle option — no matter where your customers live. Not only has this shingle earned a Class 4 impact resistance rating,³ but it also offers unparalleled wind uplift protection derived from IKO's exclusive ArmourZone technology.

We coat Nordic's durable fiberglass mat with a polymer-modified asphalt for heavy weight, exceptional strength and resilience, high-wind resistance and added flexibility for application in cold temperatures.* This powerful combo of a durable mat and special asphalt allows IKO Nordic shingles to act as shock absorbers, to help cushion the impact of hail and earn a Class 4 impact resistance rating.**³

IKO's ArmourZone is the 1 1/4-inch reinforced nailing area that provides incredible fastening power and helps resist nail pull-through even in high winds of up to 130 mph (210 km/h)¹ with only four nails.

Dynasty: Wind resistance and fast installation nailed. Dynasty is an oversized, heavy-duty laminate asphalt shingle that utilizes standard oxidized asphalt instead of a polymer-modified coating and carries a Class 3 impact resistance rating.**³ Like Nordic, Dynasty also features the ArmourZone, which offers unparalleled nail-holding power, helping the shingle resist high winds. And IKO's FastLock® sealant on every shingle further strengthens Dynasty's defiance of Mother Nature's wrath.

The secondary benefit of ArmourZone's larger nailing area is that it allows for easier and more accurate nailing. Combined with Dynasty's (and Nordic's) 5 7/8-inch exposure and larger-than-average overall size, it goes down faster and covers more area than most average-sized comparable laminate shingles.

Both Nordic and Dynasty are available in IKO's exclusive hi-definition color blends that will make your customer's home the envy of the neighborhood.

*Manual sealing is required in cold temperatures. See application instructions for full details. **This is not a guarantee of impact resistance against hail. Damage from hail is not covered under the limited warranty. Full details on reverse.



PERFORMANCE


NORDIC™ & DYNASTY® SHINGLES



Nordic shingles are available in select markets.



SPECIFICATIONS ⁴	Limited Warranty ¹	Limited Lifetime ²	Dimensions (L x W)	40 7/8 in (1,038 mm) X 13 3/4 in (349 mm)	STANDARDS ⁵	ASTM D3462
	Iron Clad Protection ¹	15 Years	Exposure	5 7/8 in (149 mm)		ASTM D3018
	Limited Wind Warranty ¹	130 mph (210 km/h)	Coverage per Bundle	33 1/3 ft ² (3.1 m ²)		ASTM D7158 – Class H
	Blue-Green Algae Resistant ¹	Yes	Shingles per Square	60		ASTM D3161 – Class F
						ASTM E108/UL 790 – Class A
						FM 4473 – Class 4 ³ (IKO Nordic shingles) – Class 3 ³ (IKO Dynasty shingles)



IMPORTANT! To ensure complete satisfaction, please view several full-size shingles and an actual roof installation prior to final color selection as the shingle swatches and photography shown online, in our brochures and in our **ROOFViewer®** tool may not accurately reflect shingle color and do not fully represent the entire color blend range nor the impact of sunlight.

Note: Product and color availability may vary by region. Products with Miami Dade NOA and FBC product approval listings are available. Meets requirements of the Texas Department of Insurance. Please contact IKO for details. ¹See Limited Warranty at IKO.com for complete terms, conditions, restrictions and application requirements. Shingles must be applied in accordance with application instructions and local building code requirements. ²"Lifetime" means the period of time commencing on the date of the completion of the installation of the shingles on the building, and continuing so long as the Owner owns the building on which the shingles were installed. ³This impact rating is solely for the purpose of enabling residential property owners to obtain a reduction in their residential insurance premium, if available. It is not to be construed as any type of express or implied warranty or guarantee of the impact performance of this shingle by the manufacturer, supplier or installer and damage from hail is not covered by the Limited Warranty. IKO recommends the use of its Class 4 impact resistance rated Hip and Ridge cap shingle in conjunction with the use of Class 4 impact resistance rated shingles, and the use of no less than its Class 3 impact resistance rated Hip and Ridge cap shingle in conjunction with the use of Class 3 impact resistance rated shingles. For further detail concerning the FM 4473 standards, visit the FM Approvals website. ⁴All values shown are approximate. ⁵Products are developed with reference to these standards. ⁶Blue granules may fade after extensive exposure to the sun's ultraviolet rays.



The information in this literature is subject to change without notice. We assume no responsibility for errors that may appear in this literature.

Find out more about our products now by talking to an IKO sales representative or contact us directly:

In the United States, call 1-888-IKO-ROOF (1-888-456-7663).

In Canada, call 1-855-IKO ROOF (1-855-456-7663). Or visit our website at: IKO.COM.

