

ASPHALT BULK LIQUID, BAGGED, AND KEGGED



TYPE I

Available in Bulk Liquid

IKO Type I asphalt is an oxidized bitumen intended for use with organic felts, insulation and coverboards for slopes of 0-3/4:12 (0-6.25%). This asphalt conforms to all requirements of CSA specification A123.4-M, Type I, and UL55A.

TYPE 2

Available in Bulk Liquid & 100 lb Kegs

IKO's Type II Asphalt is an oxidized bitumen intended for use with organic felts, glass felts, modified membranes, insulation and coverboards with slopes of 0-1:12 (0-8%). This asphalt conforms to all requirements of CSA specification A123.4-M, Type II, and UL55A.

TYPE 3

Available in Easy-Melt 200 (50 lb Packages)

IKO's Easy-Melt 200 combines the top-of-the-line characteristics of standard Type III asphalt with greater efficiency and environmental awareness. This oxidized bitumen is formed in a rectangular shape and wrapped in polyethylene. At only 50 lbs. each, the Easy-Melt 200 package is half the weight of asphalt kegs and easy to store and handle.

Easy-Melt 200 can be used with glass felts, modified rolls, insulation, coverboards and flashing systems with slopes of 0 to vertical application [up to 16" (406 mm)]. For other applications, please consult an IKO Technical Representative. This proven waterproofing material is also suitable for use in selected dampproofing applications. A superior grade asphalt, Easy-Melt 200 conforms to all Type III requirements of CSA Standard A123.4-M and ASTM D312.

Note: Available from Canada only

Environmentally Friendly

Easy-Melt 200 is designed to go directly into the kettle, package and all, reducing clean-up and waste!

BUILT-UP ROOFING (BUR) • ASPHALT BULK LIQUID, BAGGED, AND KEGGED • MODI-MELT



MODI-MELT SEBS ASPHALT

IKO's Modi-Melt SEBS is a premium Type III modified asphalt intended for use with glass felts, modified membranes, insulation and coverboards with slopes of 0:12 to vertical application [up to 16" (406mm)]. IKO's Modi-Melt is a blend of select asphalt and SEBS rubbers which conforms to all requirements of ASTM D6152, and UL55A. Modi-Melt SEBS is sold in a convenient 50 lb. (22.7 kg) keg and has excellent elasticity, flexibility and strength over a large range of temperatures.