

Phone: (800) 976-BOLT Web: itpbolt.com Email: sales@itpbolt.com Email: purchasing@itpbolt.com BREA FRESNO RANCHO CUCAMONGA UNION CITY

## **ALL THREADED ROD**

SUBMITTAL SPECIFICATIONS Abstract of ASTM A307 Grade A

CHEMICAL REQUIREMENTS
Chemical analysis shall be performed in accordance with ASTM A751

CARBON	MANGANESE	PHOPHOROUS	SULFER
MAX	MAX	MAX	MAX
0.29	1.20	0.04	

## MECHANICAL REQUIREMENTS

HARDNESS BRINEL		HARDNESS ROCKWELL		TENSILE STRENGTH (KSI)		ELONGATION IN 2 IN (50 MM)
MIN	MAX	MIN	MAX	MIN	MAX	MIN
121	241	69	100	60	-	18

Hex Nuts ASTM A563 (ASME B18.2.2) Heavy Hex Nuts ASTM A563 (ASM	E B18.2.2)
Washers ASTM F844-04 (ASME B18.22.1)	
ALL THREAD ROD MAY BE SUPPLIED	
Plain Zinc Plated Hot Dip Galvanized	
LOCATION	
Buried Submerged Above Grade Below Grade	Other

ADDITIONAL INFORMATION: Additional information can be found in ASTM A307-07B, ASTM A563-04A