

ALDOBLOCK 708 *Bleed Blocking Primer*

DESCRIPTION:

AldoBlock 708 is a low-VOC acrylic primer with asphalt stain-blocking capabilities, formulated to enhance adhesion across a variety of substrates.

SUITABLE SUBSTRATES:

- EPDM
- Aged PVC
- Aged Hypalon Membranes
- Aged TPO
- Concrete
- BUR (asphalt)
- Modified Bitumen
- Metal
- New Spray Polyurethane Foam

INSTALLATION INSTRUCTIONS:

SURFACE PREPARATION: The surface must be free of any oils, moisture, soil or other contaminants that may interfere with good adhesion. All previous repair material must be removed from seams or other surfaces. Oil and grease should also be removed with an appropriate cleaner.

APPLICATION INSTRUCTIONS: Mix thoroughly before application. Avoid entraining air when mixing. Apply only when ambient temperatures are 50°F and rising, and substrate temperatures do not exceed greater than 130°F. For best spray application, the product should be at a minimum of 60°F. Apply at a rate of 1 gallon per 100-300 square feet (approximately 5-16 wet mils), depending on surface conditions.

PACKAGING:

5-Gal Plastic Pail	51.114 lbs	36 Per Pallet
50-Gal Plastic Pail	541.875 lbs	4 Per Pallet
250-Gal Plastic Tote	2,378 lbs	1 Per Pallet

TECHNICAL DATA:

Solids by Volume	41%
Weight (lbs/gal)	9 lbs
VOC Content	< 50 g/l
Shelf Life	18-months
Standard Color(s)	Blue

All tests were performed by independent laboratories on randomly collected samples. Results may vary by ±10%. This data supersedes all previously published information.

PRECAUTIONS:

- Do not apply this product over silicone surfaces.
- Drying times will vary based on weather and substrate conditions.
- Apply topcoat as soon as possible after the primer has cured.
- Newly installed asphalt membranes, including repair patches, should weather for at least 30-days before priming.
- Not intended for use on gravel-surfaced BUR systems or shingle roofs.
- Avoid application if rain or inclement weather is forecast within 24-hours.

HANDLING & STORAGE PROCEDURES:

Shelf life is 18-months if stored in original unopened containers. Store between 45°F and 95°F. Do not allow product to freeze. Do not heat with an open flame. All containers must be sealed when not in use. Wear protective gloves, protective clothing, eye protection, and face protection. If exposed or concerned: Get medical advice or attention. Clean equipment and any overspray with warm water and soap. Do not use mineral spirits, xylene, toluene or VM&P naphtha for cleaning. Do not thin or self-tint.

LIMITED WARRANTY:

Inland Coatings, Inc. (Inland) warrants that this product conforms to the published product specifications as of the date of manufacture. Inland does not make, nor does it authorize anyone to make, any warranty of merchantability or fitness for any purpose, or any other warranty, guarantee, or representation. INLAND HEREBY DISCLAIMS ANY AND ALL EXPRESS, IMPLIED, OR STATUTORY WARRANTIES. The sole obligation of the manufacturer, distributor, and/or seller of this product shall be the replacement of product proven to be defective in manufacturing if written notice is received within one year of the date of purchase. There shall be no liability for injury, loss, or damages, either direct or consequential, arising out of the use or inability to use this product. Failure to notify the manufacturer prior to remedy or resolution voids the warranty and the manufacturer's liability.