

RR-3000 Roof Repair**DESCRIPTION:**

RR-3000 is a solvent-based mastic with reinforcing fibers formulated to repair a variety of traditional roofing materials, making it an ideal maintenance solution for most roofs in any weather condition. High elongation and tensile strength ensure reliable performance in conditions where asphalt-based cements would fail. This specialized, trowel-grade formula can be applied even on wet or underwater surfaces. VOC compliant in all 50 states.

SUITABLE SUBSTRATES:

- Metal
- EPDM
- Aged TPO
- Aged Hypalon
- Concrete
- BUR (asphalt)
- Modified Bitumen
- New Spray Polyurethane Foam

INSTALLATION INSTRUCTIONS:

SURFACE PREPARATION: The surface must be free of any oils, moisture, rust scale, soil or other contaminants that may interfere with good adhesion. Wet and underwater surfaces must be cleaned prior to application.

APPLICATION INSTRUCTIONS: Apply only when ambient temperatures are 40°F and rising, and substrate temperatures remain below 130°F for at least 4-hours following application. Product can be applied by brush or trowel. Can be applied up to 1/4" thick.

PACKAGING:

1-Gal Metal Pail (Case of 4)	38 lbs	30 Cases Per Pallet
3-Gal Metal Pail	29 lbs	60 Per Pallet

TECHNICAL DATA:

Solids by Weight	62%
Solids by Volume	59%
Weight (lb/gal)	9.24 lbs
Elongation	300%
Tensile Strength	1700 psi
VOC Content	< 300 g/l
Shelf Life	24-months
Standard Color(s)	White

PRECAUTIONS:

- Do not apply over existing silicone coatings.
- May stain yellow over asphalt substrates.
- May cause EPDM membranes to swell.
- In cold weather, the product should be stored at room temperature for easier application.

HANDLING & STORAGE PROCEDURES:

Shelf life is 24-months if stored in original unopened containers. Store between 45°F and 95°F. Do not heat with an open flame. All containers must be sealed when not in use. Wear protective gloves, protective clothing, eye protection, and face protection. If exposed or concerned: Get medical advice or attention. Clean equipment and any overspray with mineral spirits. Do not thin or self-tint.

LIMITED WARRANTY:

Inland Coatings, Inc. (Inland) warrants that this product conforms to the published product specifications as of the date of manufacture. Inland does not make, nor does it authorize anyone to make, any warranty of merchantability or fitness for any purpose, or any other warranty, guarantee, or representation. INLAND HEREBY DISCLAIMS ANY AND ALL EXPRESS, IMPLIED, OR STATUTORY WARRANTIES. The sole obligation of the manufacturer, distributor, and/or seller of this product shall be the replacement of product proven to be defective in manufacturing if written notice is received within one year of the date of purchase. There shall be no liability for injury, loss, or damages, either direct or consequential, arising out of the use or inability to use this product. Failure to notify the manufacturer prior to remedy or resolution voids the warranty and the manufacturer's liability.