

TYPICAL PHYSICAL PROPERTIES

ELONGATION: 500%

TENSILE STRENGTH: 700 psi

Cold temperature flexibility: Passes

Solids Content: 100%

Adhesion with Inland Roof Coatings: Excellent

PRODUCT DESCRIPTION:

RST series Roofing Seam Tape is a high performance butyl adhesive tape, with instant aggressive adhesion to most substrates. The RST Series Roofing Seam Tape has a fabric backing that allows for excellent adhesion of Inland Coatings' Roof Coatings. RST series Roofing Seam Tape provides increased protection against water penetration in all roof systems that contain areas that require such, including but not limited to panel gaps on metal roofs, seams on single-ply roofs, and various roof penetrations.

RST series Roofing Seam Tape is available in the following widths: 2 and 4 inches. Rolls of RST series Roofing Seam Tape are 50 feet in length. The adhesive side of the tape is protected by a polymer release film.

RECOMMENDED USES:

RST series Roofing Seam Tape can be used to reinforce application along seams and penetrations.

LIMITATIONS AND PRECAUTIONS:

RST series Roofing Seam Tape should be kept in a dry area prior to use. Do not use RST series Roofing Seam Tape if moisture is present in the fabric product. Any moisture in product prior to application may impede adhesion and result in less than optimum product performance.

The specifications, properties and performance of materials described herein are based on information believed to be reliable. Unless otherwise expressly provided in written contract, the products discussed are sold without conditions or warranties, expressed or implied. Product specifications are subject to change without notice.