

SL 2100 SEBS Skylight Coating**DESCRIPTION:**

SL 2100 is a clear, brushable, solvent-based thermoplastic rubber skylight coating intended for waterproofing and restoring fiberglass skylights.

SUITABLE SUBSTRATES:

- Fiberglass Skylights

INSTALLATION INSTRUCTIONS:

SURFACE PREPARATION: The surface must be free of any oils, moisture, rust scale, soil or other contaminants that may interfere with good adhesion. All previous repair material must be removed from seams or other surfaces.

APPLICATION INSTRUCTIONS: Mix thoroughly before application. Avoid entraining air while mixing. Apply only when ambient temperatures are 40°F and rising, and substrate temperatures do not exceed greater than 130°F. Depending on the age and condition of the skylight, multiple coats may need to be applied. This product goes down as a milky color but when curing, turns translucent.

PACKAGING:

5-Gal Metal Pail	40 lbs	36 Per Pallet
------------------	--------	---------------

TECHNICAL DATA:

Solids by Weight	39%
Solids by Volume	37%
Weight (lb/gal)	7.5 lbs
Elongation	1000%
Tensile Strength	1800 psi
VOC Content	< 550 g/l
Shelf Life	24-months
Standard Color	Clear

PRECAUTIONS:

- Do not apply over existing silicone coatings.
- Exceeding 24 wet mils or the substrate temperature limitations may increase the risk of blistering.
- For steep slope applications, the coverage rate may need to be reduced, and multiple coats may be required.
- Avoid application when freezing temperatures, rain, high humidity, dew, or condensation are expected within 8-hours after application, as these conditions may interfere with proper curing.
- SEBS coatings cure by solvent evaporation. High humidity or low temperatures can slow the curing process.
- For cold weather application, product must be stored at room temperature prior to installation.

HANDLING & STORAGE PROCEDURES:

Shelf life is 24-months if stored in original unopened containers. Store between 45°F and 95°F. Do not heat with an open flame. All containers must be sealed when not in use. Wear protective gloves, protective clothing, eye protection, and face protection. If exposed or concerned: Get medical advice or attention. Clean equipment and any overspray with mineral spirits. Do not thin or self-tint.

LIMITED WARRANTY:

Inland Coatings, Inc. (Inland) warrants that this product conforms to the published product specifications as of the date of manufacture. Inland does not make, nor does it authorize anyone to make, any warranty of merchantability or fitness for any purpose, or any other warranty, guarantee, or representation. INLAND HEREBY DISCLAIMS ANY AND ALL EXPRESS, IMPLIED, OR STATUTORY WARRANTIES. The sole obligation of the manufacturer, distributor, and/or seller of this product shall be the replacement of product proven to be defective in manufacturing if written notice is received within one year of the date of purchase. There shall be no liability for injury, loss, or damages, either direct or consequential, arising out of the use or inability to use this product. Failure to notify the manufacturer prior to remedy or resolution voids the warranty and the manufacturer's liability.