

# RhinoRoof® RSA

## Self-Adhered Synthetic Roofing Underlayment

### RhinoRoof RSA Technical Data



RSA ROLL & PALLET SPECIFICATIONS	
LENGTH PER ROLL:	67' / 20.4 m
WIDTH PER ROLL:	36" / .914 m
WEIGHT PER ROLL:	44 lbs / 20 kg
ROLL SIZE:	2 sq / 20 m <sup>2</sup>
ROLLS PER PALLET:	25
PALLET WEIGHT:	1200 lbs / 545 kg

TEST & PROPERTIES	ASTM STANDARD	RSA TYPICAL VALUE
Color		Dark Gray
Surface		Textured fiber grip slip-resistant
Release Liner		Silicone treated split release
Nail Sealability	ASTM D1970	Pass
Weight per Square	ASTM D5261	22 lbs ( 10 kg)
Nominal Thickness	ASTM D1777	40 mils (1.0 mm)
Permeability	ASTM E96	Max. 0.10
Tensile	ASTM D1970	MD 45 lbs/in (7.9 kN/m)
	ASTM D1970	CD 32 lbs/in (5.6 kN/m)
Thermal Stability	ASTM D1970	180° F (82° C) Pass
Low Temp. Flexibility	ASTM D1970	Pass
Tear Resistance	ASTM D1970	MD 55 lbf (245 N) CD 46 lbf (205 N)
Adhesion to Plywood		Min. 5 lb/in (0.9kN/m )
Self Sealability		Pass

### RhinoRoof RSA Building Codes



- Meets ASTM D4869 & D226 Types I & II
- Florida Building Code Approved # FL17298
- Warnock Hersey
- CAN/CSA A220.1
- Class A Fire - ASTM E108
- Texas Department of Insurance listed



**CAN/CSA A220.1  
MEETS ASTM D1970  
CCRR-1017  
FBC #FL17298**



**InterWrap® Roofing Products Division**  
 Charleston, SC • Vancouver, BC • Mission, BC • Montréal, QC  
 Web: [www.InterWrap.com/roofing](http://www.InterWrap.com/roofing) | E-mail: [info@interwrap.com](mailto:info@interwrap.com)  
 Toll Free: 888 713 7663 | Tel: 778 945 2888

