

DEC-KING®

EXTERIOR WOOD SCREWS


Corrosion resistant fasteners for exterior wood applications

PRODUCT FEATURES

- Coated with Climacoat® for maximum resistance to corrosion, staining and streaking inside the lumber and on the deck.
- Recommended for ACQ treated wood.
- Pullout strength is superior over nails.
- Eliminates wood splitting, nail pops, hammer marks, and bent nails.
- Available in both #2 Phillips & #2 Square Drive.



SELECTOR GUIDE



PART NO.	DESCRIPTION	HEAD STYLE	BOX QTY	APPLICATIONS
2176500	6 x 1-1/4"	#2 Phillips	8,000	1" x 4" or 1" x 6" Base Trim; Lattice
2136500	6 x 1-5/8"	#2 Phillips	5,000	1" x 4" or 1" x 6" Base Trim; Balusters; Lattice
2138500	7 x 2"	#2 Phillips	3,500	5/4" x 4" or 5/4" x 6" Radius Edged Decking; 1" x 4" or 1" x 6" Base Trim; Balusters; Lattice
2180500	8 x 2-1/2"	#2 Square Drive	2,500	5/4" x 4" or 5/4" x 6" Radius Edged Decking; 2" x 4" or 2" x 6" Decking; 2" x 6" or 2" x 8" Rail Cap or Base Trim
2140500	8 x 2-1/2"	#2 Phillips	2,500	
2181500	8 x 3"	#2 Square Drive	2,000	2" x 4" or 2" x 6" Decking; 2" x 6"; 2" x 8" Rail Cap or Base Trim
2141500	8 x 3"	#2 Phillips	2,000	
2142500	10 x 3-1/2"	#2 Phillips	1,000	

PERFORMANCE DATA

PULLOUT VALUES IN WOOD (AVERAGE LBS. ULTIMATE)				
DESCRIPTION	EMBEDMENT IN 2 X 4 STUD GRADE S.Y. PINE			
	1/2"	3/4"	1"	1-1/4"
6 x 1-1/4"	182	329	422	—
6 x 1-5/8"	182	329	422	620
7 x 2"	189	318	440	630
8 x 2-1/2"	186	290	502	630
8 x 3"	186	290	502	645
10 x 3-1/2"	241	386	522	721

The values listed are ultimate averages achieved under laboratory conditions and apply to Buildex manufactured fasteners only. Appropriate safety factors should be applied to these values for design purposes.

HEAD STYLES

