

T4SS SINGLE SHOT TOOL



The fasteners are designed for use in Ramset T3SS/T4SS single-shot gas tool

SELECTION CHART

THREADED ROD HANGER

For suspended ceilings, piping and other items using 1/4" or 3/8" threaded rod. Fastener is pre-assembled to a 16 gage threaded rod hanger. 100 per jar.



| PART NUMBER | DESCRIPTION | MASTER CARTON QUANTITY |
|-------------|--------------------------------------|------------------------|
| 14TRHMP034 | 1/4" Rod hanger with 3/4" plated pin | 800 |
| 38TRHMP034 | 3/8" Rod hanger with 3/4" plated pin | 800 |

Shank diameter = .104/.125 Head diameter = .300

ONE HOLE STRAP

Used to attach EMT conduit or armored cable to concrete. Fastener pre-assembled to a 16 gage conduit strap. 100 per jar, 3/8" 200 per jar.



| PART NUMBER | DESCRIPTION | MASTER CARTON QUANTITY |
|-------------|---|------------------------|
| 38HSMP034* | 3/8" Hole strap with 3/4" plated pin (UL) | 1200 |
| 12HSMP034 | 1/2" Hole strap with 3/4" plated pin | 800 |
| 34HSMP034 | 3/4" Hole strap with 3/4" plated pin | 600 |
| 10HSMP034 | 1" Hole strap with 3/4" plated pin | 600 |

Shank diameter = .104/.125 Head diameter = .300 *38HSMP034 = 18 gage, 200 per jar

CONDUIT CLAMP

Used to attach conduit to concrete. Pin pre-assembled to an 18 gage conduit strap. 3/4" 25 per jar.



| PART NUMBER | DESCRIPTION | MASTER CARTON QUANTITY |
|-------------|---|------------------------|
| 34CCMP034L | 3/4" Conduit clamp with 3/4" plated pin | 300 |

Shank diameter = .104/.125 Head diameter = .300

CEILING CLIP ASSEMBLY

Pre-assembled Ceiling Clip. Plated 14 gage clip. 100 per jar.



| PART NUMBER | DESCRIPTION | MASTER CARTON QUANTITY |
|-------------|---|------------------------|
| 34CLIP | 3/4" wide angle clip w/ 3/4" length pin | 800 |

Shank diameter = .104/.125 Head diameter = .300 Hole diameter = 5/16"

AVAILABLE IN CONVENIENT JARS!



The new durable plastic containers mean less waste on the jobsite, or in the back of a truck. Their wide-mouth design makes it easy to grab what you need.



Each T3SS gas accessory and pin label provides vital holding value information—taking away the guess work.

T4SS SINGLE SHOT TOOL



The fasteners are designed for use in Ramset T3SS/T4SS single-shot gas tool

SELECTION CHART

TIE STRAP HOLDER

Used to install temporary lighting and secure low voltage cable to concrete, uses a standard cable tie up to 3/8" in width. Fastener is pre-assembled to a 22 gage tie strap holder. 50 per jar.




| PART NUMBER | DESCRIPTION | MASTER CARTON QUANTITY |
|-------------|---------------------------------------|------------------------|
| TSHMP034 | Tie strap holder with 3/4" plated pin | 1250 |

Shank diameter = .104/.125 Head diameter = .300

MECHANICAL PIN WITH WASHER

Used for the attachment of light gage metal to concrete and steel such as HVAC duct strap to concrete. Plated pin pre-assembled to a 1/2" domed washer. 200 per jar, 1" 100 per jar.



| PART NUMBER | DESCRIPTION | MASTER CARTON QUANTITY |
|-------------|---|------------------------|
| M034 | 3/4" Plated pin with domed washer | 5000 |
| M034BB | 3/4" Premium step pin with domed washer | 5000 |
| M100 | 1" Plated pin with domed washer | 5000 |

MUST USE WITH MAGNETIC WORK CONTACT ELEMENT (Part #19943 for T4SS / Part #M150200 for T3SS)

TOP HAT PIN

Used for general purpose fastening to concrete. Plated pin with top hat. 200 per jar.



| PART NUMBER | DESCRIPTION | MASTER CARTON QUANTITY |
|-------------|------------------------------|------------------------|
| MPO34TH | 3/4" Plated pin with top hat | 5000 |

Shank diameter = .125 Head diameter = .300