

Hardie® Reveal® Panel System

Project Name:

Project Address:

Start Date:

Project Manager or Head Install Contact on Site:

Number of floors and building height:

(Max. building height of 75 ft. for HardieReveal panel systems)

Furring Type: Metal or Wood

GC/Installer Company Name:

Phone:

JH Rep:












Please check one:

- Single Family
- Multi-Family
- Commercial

Please check one:

- New Construction
- R&R

SKU	Description	Qty	Unit	Total Units
 <ul style="list-style-type: none"> <input type="checkbox"/> 617973 (HZ5 full pallet) <input type="checkbox"/> 6000277 (HZ5 sub pallet) <input type="checkbox"/> 217973 (HZ10 full pallet) <input type="checkbox"/> 9000277 (HZ10 sub pallet) 	HARDIE® REVEAL® PANEL Thickness 7/16 in., Width 47.5 in., Length 95.5 in.	40	full pallet	
		10	sub pallet	
		40	full pallet	
		10	sub pallet	
 <ul style="list-style-type: none"> <input type="checkbox"/> Chem Film (primed) 280101 <input type="checkbox"/> Clear Anodized (ColorPlus) 280100 	Horizontal Reveal Trim Length: 12 ft.	20 pcs.	Carton	
		20 pcs.	Carton	
 <ul style="list-style-type: none"> <input type="checkbox"/> Chem Film (primed) 280103 <input type="checkbox"/> Clear Anodized (ColorPlus) 280102 	Horizontal Reveal Trim, Termination Notch Length: 12 ft.	20 pcs.	Carton	
		20 pcs.	Carton	
 <ul style="list-style-type: none"> <input type="checkbox"/> Chem Film (primed) 280111 <input type="checkbox"/> Clear Anodized (ColorPlus) 280110 	Vertical Reveal Trim Length: 12 ft.	20 pcs.	Carton	
		20 pcs.	Carton	
 <ul style="list-style-type: none"> <input type="checkbox"/> Chem Film (primed) 280121 <input type="checkbox"/> Clear Anodized (ColorPlus) 280120 	Outside Corner Reveal Trim Length: 12 ft.	10 pcs.	Carton	
		10 pcs.	Carton	
 <ul style="list-style-type: none"> <input type="checkbox"/> Chem Film (primed) 280131 <input type="checkbox"/> Clear Anodized (ColorPlus) 280130 	Inside Corner Reveal Trim Length: 12 ft.	10 pcs.	Carton	
		10 pcs.	Carton	
 <ul style="list-style-type: none"> <input type="checkbox"/> Chem Film (primed) 280141 <input type="checkbox"/> Clear Anodized (ColorPlus) 280140 	J Channel Reveal Trim Length: 12 ft.	10 pcs.	Carton	
		10 pcs.	Carton	
 <ul style="list-style-type: none"> <input type="checkbox"/> Chem Film (primed) 9000372 	PVC Vent Strip Length: 8 ft.	50 pcs.	Carton	
 <ul style="list-style-type: none"> <input type="checkbox"/> Chem Film (primed) 280151 <input type="checkbox"/> Clear Anodized (ColorPlus) 280150 	Drainage Flashing Length: 12 ft.	10 pcs.	Carton	
		10 pcs.	Carton	








Hardie® Reveal® Panel System

Send quote to multi.family@jameshardie.com or fax to 866.653.5822

1. James Hardie will only ship Hardie® Reveal® Panel with Hardie Reveal Trims in **Full Pallet, Sub Pallet and Carton QTYs only**
2. All Reveal Panel projects will be quoted as a lump sum project price
3. Quote applies only to the parties listed on this document
4. Fill in Reveal Panel Orders to be approved by JH
5. Quotes expire in (90) days after date on quote
6. Pricing is locked for one year (365 days) from the date of the contract
7. No returns on MF orders
8. For primed panels, please order Chem Film trims. For ColorPlus® panels, please order Clear Anodized trims.

Notes:

1,260 sq.ft. per pallet of Reveal Panel

SKU	Description	Qty	Unit	Total
 <input type="checkbox"/> 9000405	EDGE SEALER (4 OZ. BOTTLE) - Conservative usage rate is two 4 oz. bottles of edge sealer for every 40 Panels	1	Bottle	
 <input type="checkbox"/> Various	COLORPLUS® TOUCH-UP KIT - Conservative usage rate is two kits per 1,000 sq. ft. of siding	1	Box	
 <input type="checkbox"/> 9000403 (Wood & Steel)	ACC REVEAL EXPOSED FASTENERS	250	Box	
	1 IN. X 4 IN. TREATED FURRING (MCA & MCQ TREATED LUMBER) 8 ft. or 10 ft. long pieces recommended		Not supplied by James Hardie	
	EPDM Minimum 1/16 in. thick EPDM to be installed on face of furring		Not supplied by James Hardie	
	PAINTING DO NOT use stain on James Hardie® products. James Hardie products must be painted within 180 days for primed product and 90 days for unprimed. Two coats of 100% acrylic topcoats with flat or satin sheen (20 or less gloss units at 60 degree angle), are recommended. Do not paint when wet. For application rates refer to paint manufacturers specifications. Back-rolling is recommended if the product is sprayed.		Not supplied by James Hardie	
	PANEL SAW WITH HARDIEBLADE® SAW BLADE IN CONJUNCTION WITH HEPA VACUUM		Not supplied by James Hardie	

*Recommended usage rates for accessories may vary according to panel design and layout.



JamesHardieCommercial.com