

Hardie® Trim

Submittal Form

09

Project Name:

Date:

Submitted to:

Submitted by:

Product:	<input type="checkbox"/> ColorPlus® Technology finish	<input type="checkbox"/> Primed for Paint					
Zone:	<input type="checkbox"/> HZ5®	<input type="checkbox"/> HZ10®					
Texture:	<input type="checkbox"/> Smooth	<input type="checkbox"/> Roughsawn	<input type="checkbox"/> Rustic Grain				
Width:	<input type="checkbox"/> 2.5 in.	<input type="checkbox"/> 3.5 in.	<input type="checkbox"/> 4.5 in.	<input type="checkbox"/> 5.5 in.	<input type="checkbox"/> 7.25 in.	<input type="checkbox"/> 9.25 in.	<input type="checkbox"/> 11.25 in.
Length:	<input type="checkbox"/> 12 ft.						
Thickness:	<input type="checkbox"/> 3/4 in.	<input type="checkbox"/> 1 in.	<input type="checkbox"/> 1.5 in.				

Hardie® Trim

Specification Sheet

09

DIVISION: 07 00 00 THERMAL AND MOISTURE PROTECTION

SECTION: 07 46 46 FIBER CEMENT SIDING

HARDIE® TRIM

Manufacturer

James Hardie Building Products Inc.

The products are manufactured at the following locations, which receive regular quality control inspections by ICC-ES.

- Cleburne, Texas
- Prattville, Alabama
- Plant City, Florida
- Peru, Illinois
- Reno, Nevada

For more information about compliances, refer to Intertek Spec ID# 39758.

Features

- Class-A Fire Rated
- Flood Damage Resistant
- Dimensionally Stable
- Resists damage from pests
- Zero Flame Spread
- Engineered for Climate®
- Weather Resistant
- Impact resistant
- Sustainable

Use

Hardie® fiber cement trim is used as an exterior wall accessory. The product complies with 2024 IBC Section 1403.9; 2018, 2021 IBC Section 1403.10; 2012, 2015 IBC Section 1404.10.

Description

Made from durable fiber cement, Hardie® Trim comes in a variety of textures and are available primed and ready for paint, or pre-finished with ColorPlus® Technology, providing the perfect finishing touch to your project. Hardie® Trim complies with ASTM C1186, Type A; and Class A Fire Rated per ASTM E84, with a flame spread index / smoke developed index of less than 0/5.

Engineered for Climate®

Hardie® Trim is engineered for performance to specific weather conditions by climate zones as identified by the following map.



Performance Properties

	General Property	Test Method	Unit or Characteristic	Requirement	Result
PHYSICAL ATTRIBUTES	Dimensional Tolerances	ASTM C1185	Length	± 0.5% or ± 1/4 in	Pass
			Width	± 0.5% or ± 1/4 in	
			Thickness	For 3/4 in, ± 0.06 in. For greater than 3/4 in, ±10%.	
			Squareness	Δ in diagonals ≤ 1/32 in/ft of sheet length. Opposite sheet sides shall not vary in length by more than 1/32 in/ft	
			Edge Straightness	≤ 1/32 in/ft of length	
	Density, lb/ft³	ASTM C1185		As reported	70
	Water Absorption, % by mass	ASTM C1185		As reported	≤ 40.2
	Water Tightness	ASTM C1185	Physical Observations	No drop formation	Pass
	Flexural Strength	ASTM C1185	Wet conditioned, psi Equilibrium conditioned, psi	>580 psi >580 psi	Pass
DURABILITY	Warm Water Resistance	ASTM C1185	Physical Observations	No visible cracks or structural alteration	Pass
	Heat/Rain Resistance	ASTM C1185	Physical Observations	No visible cracks or structural alteration	Pass
	Freeze/Thaw Resistance	ASTM C1185	Physical Observations	No visible cracks or structural alteration	Pass
			Mass Loss, %	≤ 3.0%	
			Freeze/Thaw, % strength retention	≥ 80%	
FIRE CHARACTERISTICS	UV Accelerated Weathering Test	ASTM G23	Physical Observations	No cracking, checking, or crazing	Pass
	Surface Burning Characteristics	ASTM E84	Flame Spread Index (FSI)		0
			Smoke Developed Index (SDI)		≤ 5
			Fuel Contributed		0
			NFPA Class		A
			Uniform Building Code Class	As reported	1
			International Building Code® class		A

Note 1: listed on Warnock Hersey and ESR 2290

Installation

Install Hardie® Trim in accordance with:

- Hardie® Trim installation instructions
- Requirements of authorities having jurisdiction

Warranty

Hardie® Trim: 30-year, Non-Prorated, Substrate Limited Warranty
ColorPlus® Technology finishes: 15-year, Limited Finish Warranty

Sustainable Design Contribution

- Regionally sourced content - varies by project location
- Avoidance of certain chemicals

Detailed product information for LEED® projects, Environmental Product Declaration, or other state or regional sustainability programs is available through James Hardie Technical Services or JamesHardie.com.

Storage and Handling

Store flat and keep dry and covered prior to installation.

Technical Services

Contact James Hardie Technical Services by phone at 1-888-J-HARDIE (1-888-542-7343).

IMPORTANT: Failure to install and finish this product in accordance with applicable building codes and James Hardie written application instructions may affect system performance, violate local building codes, void the product-only warranty and lead to personal injury. **DESIGN ADVICE:** Any information or assistance provided by James Hardie in relation to specific projects must be approved by the relevant specialists engaged for the project eg. builder, architect or engineer. James Hardie will not be responsible in connection with any such information or assistance.