



JL INDUSTRIES

CORNER GUARD SYSTEMS



**Division 10 26 13
Corner Guards**

ACTIVAR
INC. www.activar.com
Construction Products Group



SAF-T-GUARD SYSTEMS

VINYL CORNER GUARD SYSTEM: SGV Series



SGVS-90-2

Construction: Continuous aluminum retainer with high-impact vinyl acrylic cover completely conceals frame. End caps on top and bottom retain wings. Antimicrobial finish. NFPA 101.

Length: 48" standard". Up to 20'.

Wing Length: 2" and 3".

Angle: 90° (2" & 3" wing), 135° (3" wing).

Corner Type: Square (S), or Endwall (EW).

Mounting: Installed with screws through aluminum retainer to wallboard surface.

Flame Resistance: Meet Class A requirements & tested to ASTM E84.

Models: SGVS-90-2, SGVS-90-3, SGVS-135-3, SGV-EW-2

FLUSH VINYL CORNER GUARD SYSTEM WITH ALUMINUM BASE & WALLBOARD BEAD: SGVA Series



SGVAS-90-3

Construction: Continuous aluminum retainer with 4" cover base. High-impact vinyl acrylic cover snaps into place concealing frame. Antimicrobial finish. NFPA 101.

Length: 48" standard". Up to 20'.

Wing Length: 2" and 3" with 13/16" wallboard bead for taping over frame.

Angle: 90° (2" & 3" wing), 135° (3" wing).

Corner Type: Square (S) or Endwall (EW).

Mounting: Installed with screws through aluminum retainer to wallboard surface.

Flame Resistance: Meet Class A Requirements & tested to ASTM E84.

Models: SGVAS-90-2, SGVAS-90-3, SGVAS-135-3, SGVA-EW-2

FLUSH VINYL CORNER GUARD SYSTEM WITH 2 HR FIRE BARRIER, ALUMINUM BASE & WALLBOARD BEAD: SGVAF Series



SGVAF2S-90-3

Construction: Continuous aluminum retainer with 4" cover base. High-impact vinyl acrylic cover snaps into place concealing frame. Antimicrobial finish. NFPA 101.

Fire-Rated Insulation: 2 hour fire-rated material is adhered to the wall side of the corner guard.

Length: 48" standard". Up to 20'.

Wing Length: 2" and 3" with 13/16" wallboard bead for taping over frame.

Angle: 90° (2" & 3" wing), 135° (3" wing).

Corner Type: Square (S) or Endwall (EW).

Mounting: Installed with screws through aluminum retainer to wallboard surface.

Flame Resistance: Meet Class A Requirements & tested to ASTM E84.

Models: SGVAF2S-90-2, SGVAF2S-90-3, SGVAF2S-135-3, SGVAF2-EW-2

Endwalls



SGVA-EW Endwalls Are a Single Wrap-Around Unit

SGV-EW Endwalls are 2 Corner Guards with Matching Sheet Vinyl In the Gap



CORNER GUARDS: STAINLESS STEEL, VINYL & LEXAN

STAINLESS STEEL: CGSS Series MEDIUM TO HEAVY IMPACT



Finish & Material: 18 Gauge, Type 304, 32D #4 Satin Finish (BHMA 630).
Length: 48" standard". Up to 108".
Wing Length: Standards are 1-1/2", 2", 2-1/2", 3" and 3-1/2". Others available upon request.
Angle: Standards are 90°, 135° or "U" Shape.
Mounting: Screws and pre-drilled holes, or adhesive strips upon request.
Flame Resistance: Non-flammable.

CLEAR LEXAN® POLYCARBONATE: CGL Series LIGHT TO MEDIUM IMPACT



Length: 48" or 8' standard". Others available upon request.
Wing Length: Standards are 3/4", 1-1/8", 1-1/2", 2" and 2-1/2". Others available upon request.
Angle: Standards are 90°, 135° (135° only available in 2-1/2" wing).
Mounting: Screws and pre-drilled holes.
Flame Resistance: None.

TEXTURED STAINLESS STEEL: CGSST Series LIGHT TO MEDIUM IMPACT




CGSST-90-B CGSST-90-R

**TEXTURED CORNER GUARDS
DISCONTINUED 7/2014**

Finish & Material: Type 304 stainless, gauge varies by texture selected.
Length: 48" standard". Other lengths available upon request.
Wing Length: Standards are 1-1/2", 2", 3" and 3-1/2". Others available upon request.
Angle: Standards are 90°, 135° or "U" Shape. Others available upon request.
Mounting: Adhesive, or screws and pre-drilled holes.
Flame Resistance: Non-flammable.
Textures: (BW) Basketweave, (B) Bounce, (C) Cobblestone, (HA) Hammered, (HC) Honeycomb, (L) Leather, (PB) Pebble, (PS) Pinstripe, (S) Stucco, (W) Wave, (R) Rice, (BR) Brick.
 See Website to View Samples.

VINYL ACRYLIC: CGVA Series LIGHT TO MEDIUM IMPACT



CGVA-90-.75

Finish & Material: Pebble grain texture, .078" Vinyl Acrylic with antimicrobial agent. NFPA 101.
Length: 48" standard". Up to 16'.
Wing Length: 3/4", 1-1/2" or 2-1/2".
Angle: Standards are 90°
Mounting: Adhesive tape or none.
Flame Resistance: Meet Class A requirements & tested to ASTM E-84.

Models: CGVA-90-.75, CGVA-90-1.5, CGVA-90-2.5

Colors for all Vinyl Corner Guards:

See Color Guide Online for the most current Colors

LEED Information:

See LEED information on Website for Details

Order Format: _____ - _____ - _____ - _____ - _____ Example: CGSST-90-3.5-60-PB
 Model Degree of Angle Wing Length Total Length Texture or Color SGVAF2S-135-3-90-

TO ORDER CALL 1-800-554-6077 OR VISIT WWW.JLINDUSTRIES.COM

HEADQUARTERS: 4450 WEST 78TH ST CIRCLE, BLOOMINGTON, MN 55435-5416 **PH:** 800-554-6077 **FAX:** 952-835-2218
EMAIL: SALES@JLINDUSTRIES.COM **WWW.ACTIVARCPG.COM** **ACPG WEST COAST (SAMSON PRODUCTS):** COMMERCE, CA
ACPG SOUTHEAST (THOMAS ENTERPRISES): FT MEYERS, FL
WAREHOUSES: DALLAS TX, LANCASTER PA, CHICAGO IL, ATLANTA GA
AN ACTIVAR CONSTRUCTION GROUP COMPANY

The Activar Construction Products Group (ACPG) consists of 5 affiliated companies that serve the commercial construction industry. Our multiple product lines are a single source for architects and distributors. Air Louvers manufactures products for the openings market with door lites, louvers and rated-glass. Hiawatha is known for its quality architectural door hardware and frameless shower door products. JL Industries is an industry leader in fire protection, providing fire extinguishers, AEDs and cabinets, access panels, roof opening products and entrance flooring systems. Samson Products manufactures many of the products sold under the JL label and distributes JL products on the West Coast. Thomas Enterprises is our Southeast warehouse distributor for JL products and has a state-of-the-art aluminum fabrication facility for fire extinguisher cabinets sold under the Thomas and JL labels.

SUBMITTALS AVAILABLE AT: WWW.JLINDUSTRIES.COM

CG1002 REV E