SUBMITTAL: COSMOPOLITAN STAINLESS STEEL FIRE-FX2™ FIRE-RATED EXTINGUISHER CABINETS

PAGE 1 OF 2

The Cosmopolitan Series in Stainless Steel Is a Modern, Clean Look for Recessed & Surface-Mounted Extinguisher Cabinets.

Door & Trim Construction: # 4 stainless steel. Flush cabinet doors with a 5/8" door stop are attached by a continuous hinge and equipped with zinc-plated handle and roller catch. All models have 1-3/4" wide trim on frame and 1-1/4 trim on doors with glazing.

Trim Style & Depth: Recessed - 3/8" flat trim, Semi Recessed - 1-1/4", 1-1/2" Square Edge or 2-1/2", 3", 4", 4-1/2" Rolled Edge (4" has recessed Flush pull). See separate submittal for Trimless models.

Tub: The tub is constructed of cold rolled steel with white powder-coat finish standard. Tub forms a flange to cover cut edges of wallboard material. Fire-resistant material is attached to the exterior of the tub

Fire Rating: Fire-FX2™ cabinets are UL listed and labeled as an approved membrane penetration firestop system for up to 2 hours in accordance with UL 1479 (ASTM-E814) and CAN/ULC-S115, when properly installed in a wall assembly according to installation instructions.

STEP 1: SELECT MODEL NUMBER AND QUANTITY ON CHART (refer to chart on pg 2)

A. Determine Trim Style according to wall depth. B. Determine Tub I.D. according to size most suited for extinguisher and wall opening.

800-554-6077

sales@activarcpg.com

www.activarcpg.com

STEP 2: SELECT DOOR STYLE WITH HANDLE	Check one box below Examples on Page 2			7		
F Full Glazing	L22 Solid with SAF-T-LOK		1" Typical 3/16" Typical			
G Full Glazing with SAF-T-LOK™	L24 Sold with Cylinder Lock - No Handle					
D Horizontal Duo Panel	V Vertical Duo	Through Holes Provided				
E Horizontal Dual Panel with SAF-T-LOK	W Vertical Duo with SAF-T-LOK	Trim →				
S21 Solid Door	B Solid with 2" x 4" View Window & SAF-T-L0	OK 134° Wide	.)			
STEP 3: SELECT DOOR GLAZING	(Check one box below)	TYPICAL INSTALLATION				
10 Clear Acrylic	15 Bronze Acrylic	17 Clear Tempered Glass		1835F10FX2 Recessed	1037V10FX2	
13 Clear Wire Glass with Safety Film	16 Gray Acrylic	18 Laminated Safety Glass		Recessed	3" Rolled Edge Semi-Recessed	
STEP 4: OPTIONAL FEATURES AT ADDED COST (SELE	ECT ANY)					
Optional Tub Color: BlackRed	Black Vertical FE Letters LDCVBFE	Black Vertical Decal LDVBFE	Stainless Tub			
Futura "Fire" Pull Mill Alum Red White	Red Vertical FE Letters LDCVRFE	Red Vertical Decal LDVRFE	(CA) Commander A	larm		
Flush Pull Handle PRH	White Vertical FE Letters LDCVWFE	White Vertical Decal LDVWFE	(BA) Brigadier Alarr	(BA) Brigadier Alarm		
Polished Chrome Handle PUCH	Black Horizontal FE Letters LDCHBFE	Black Horizontal Decal LDHBFE	Vertical Red FE Silk	screen Lettering- SSFE	LVR Door Glass	
Stainless Pull Handle PUS-US32D	Red Horizontal FE Letters LDCHRFE	Red Horizontal Decal LDHRFE	Lettering: Etched or	n Glass, Engraved on Me	etal, Silkscreen; Not	
Other Stainless Finish: #6 #7 #8	White Horizontal FE Letters LDCHWFE	White Horizontal Decal LDHWFE	available for #7 or #8	finish on doors. Attach s	eparate submittal to order.	
t is the responsibility of the customer to communicate specifications an mply or represent a specification or rating, of finished products shippec						

Project:

Architect:

Item #

Quantity:

Pages: 1 of 1

Approved By:

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE SOLE PROPERTY OF ACTIVAR CONSTRUCTION PRODUCTS GROUP, INC. ANY REPRODUCTION IN PART OF AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ACTIVAR CONSTRUCTION PRODUCTS GROUP, INC. IS PROHIBITED.

Distributor:

Contractor:

Scale: N/A

Date:

9702 Newton Av S. Bloomington, MN 55431

INDUSTRIES

SUBMITTAL: COSMOPOLITAN STAINLESS FIRE-FX2 EXTINGUISHER CABINETS

TRIM & DOOR SERIES #		Т	ub I.D		Frame	O.D.	FX W	all Openi	ngs	Fits Fire		
QTY	Model	Trim Style (in)	Α	В	С	Е	F	W	Н	D	Extinguisher	
	8135	Flat 3/8" Trim ●	9	18	5 1/2	12 3/8	21 3/8	11 5/16	20 5/16	6 7/16	Cosmic & Galaxy 2 1/2-	
	8136	1 1/2 Square ●	9	18	5 1/2	12 3/8	21 3/8	11 5/16	20 5/16	5 3/16	6 (6 lb must be mounted to back of tub), Mercury 2 1/2- 5	
	8137	2 1/2 Rolled●	9	18	5 1/2	12 3/8	21 3/8	11 5/16	20 5/16	4		
	1730	2-1/4 Square •	10 1/2	24	5	13 7/8	27 3/8	12 13/16	26 5/16	4	Cosmic/Gal/Merc 2-5	
	1835	Flat 3/8" Trim ●	10 1/2	24	5 1/2	13 7/8	27 3/8	12 13/16	26 5/16		Cosmic & Galaxy 2 1/2- 6 (6 lb must be mounted to back of tub),	
	1836	1 1/2 Square ●	10 1/2	24	5 1/2	13 7/8	27 3/8	12 13/16	26 5/16	5 3/16		
	1837	3 Rolled●	10 1/2	24	5 1/2	13 7/8	27 3/8	12 13/16	26 5/16	3 11/16		
	1832	4 Rolled/Flush Pull●	10 1/2	24	5 1/2	13 7/8	27 3/8	12 13/16	26 5/16		Mercury 2 1/2- 5	
	1838	4 1/2 Rolled	10 1/2	24	5 1/2	13 7/8	27 3/8	12 13/16	26 5/16	2 3/16		
	1035	Flat 3/8" Trim ●	10 1/2	24	6	13 7/8	27 3/8	12 13/16	26 5/16			
	1036	1 1/2 Square●	10 1/2	24	6	13 7/8		12 13/16	26 5/16	5 11/16	2 1/2-10 Mercury 2 1/2-5 , Sentinel 5	
	1037	3 Rolled●	10 1/2	24	6	13 7/8		12 13/16	26 5/16			
	1032	4 Rolled/Flush Pull●	10 1/2	24	6	13 7/8	27 3/8	12 13/16	26 5/16			
	1038	4 1/2 Rolled	10 1/2	24	6	13 7/8	27 3/8	12 13/16	26 5/16			
	2035	Flat 3/8" Trim ●	12	27	7 3/4	15 3/8	30 3/8		29 5/16		(20 lb must be mounted to back of tub), Mercury, Saturn or	
	2036	1 1/4 Square ●	12	27	7 3/4	15 3/8	30 3/8		29 5/16			
	2037	2 1/2 Rolled●	12	27	7 3/4	15 3/8	30 3/8	14 5/16	29 5/16	6 7/16		
	2032	4 Rolled/Flush Pull●	12	27	7 3/4	15 3/8	30 3/8	14 5/16	29 5/16	5 1/8		
	2038	4 1/2 Rolled	12	27	7 3/4	15 3/8	30 3/8	14 5/16	29 5/16	4 7/16	Nebula 270	
	3035	Flat 3/8" Trim ●	16	32	7 3/4	19 3/8	35 3/8	18 5/16	34 5/16	8 11/16	Any Cosmic or Galaxy	
	3036	1 1/4 Square●	16	32	7 3/4	19 3/8	35 3/8	18 5/16	34 5/16	7 11/16	(20 lb must be mounted	
	3037	2 1/2 Rolled●	16	32	7 3/4	19 3/8	35 3/8	18 5/16	34 5/16	6 7/16	to back of tub), Mercury Saturn or Grenadier P,	
	3032	4 Rolled/Flush Pull●	16	32	7 3/4	19 3/8	35 3/8	18 5/16	34 5/16	5 1/8	Sentinel 5-15,	
	3038	4 1/2 Rolled	16	32	7 3/4	19 3/8	35 3/8	18 5/16	34 5/16	4 7/16	Nebula 270, 272, 250	
	4035	Flat 3/8" Trim ●	20	27	7 3/4	23 3/8	30 3/8	22 5/16	29 5/16	8 11/16	Two each of: any	
	4036	1 1/4 Square ●	20	27	7 3/4	23 3/8	30 3/8	22 5/16	29 5/16	7 11/16	Cosmic or Galaxy (20 lb must be mounted	
	4037	2 1/2 Rolled●	20	27	7 3/4	23 3/8	30 3/8	22 5/16	29 5/16	6 7/16	on tub),	
	4032	4 Rolled/Flush Pull	20	27	7 3/4	23 3/8	30 3/8	22 5/16	29 5/16	5 1/8		
	4038	4 1/2 Rolled	20	27	7 3/4	23 3/8	30 3/8	22 5/16	29 5/16	4 7/16	Sentinel 5	

Wall Opening Cabinet **Dimensions** New Lighter, FX2 Insulation 3/8" Flat Trim 1-1/2" Square 2-1/2", 3" 4" Rolled Edge Rolled Edge with Recessed Trim **Pull Standard** F - Full glass with D - Horizontal duo V - Vertical duo S21 - Solid with pull B - Small view pull handle panel with pull panel with pull handle (shown) llug diw wobniw G - Full glass handle handle L22 - Solid with pull handle above

See website for items that are available on our stock list.

ADA Cabinet Mounting Height: Standard Pull on G, E, W, L22 and B Door Styles with Saf-T-Lok are 3 5/8" Higher than Door Center, so Allow for that When Mounting Cabinet.

W - Vertical duo

panel with pull

-T-Lok (not

shown)

Lok

cylinder key lock

and no handle

handle above Saf L24 - Solid with

handle above Saf-T- Saf-T-Lok

Standard Pull with No Lock or Flush Pull are Centered on Door.

E - Horizontal duo

handle above Saf-T

-Lok (not shown)

panel with pull

with pull handle

above Saf-T-Lok

(not shown)